



Index: Licenses

A	Available subsystems	4
D	Description	5, 6
E	Ex works state	4
H	Hardware serial number	3
K	Key	3, 5, 6
L	License data	
	Activating extra licenses	5
	License serial number	3
	PIN	3
	Serial number	3
	Software license ID	3
	License serial number	3
M	Mask	5
N	Number of Licenses	6
O	Online licensing	3, 6
P	PIN	3
S	Serial number	3, 5
	Serialnumber	5
	Software license ID	3





Index: System

Numerics	1st Event index	28
A	Action	18
	Activity Monitor	7
	Activity Monitor Password	33
	admin Login Password/SNMP Community	33
B	Basic system data	3
C	Central server	13
	CLID	13, 14
	Client IP address	8
	Client UDP port	8
	Compare value	25
	Condition	25
	Contact	4
D	Description	22, 28
	DownAction	16
E	End time	26
	End value	26
	Event protocol	9
	Eventlist condition	29
	Execute command	29
	External Activity Monitor	7
	External system logging	9
F	Facility	10
	FirstIfIndex	16, 18
G	Group	15

H	Hosts	14
	HTTP Server Password	33
I	Index	22, 28
	Index value	24, 30
	Index variable	24, 30
	Interface	17, 29
	Interfaces	14
	Interval	15
	IP address	15
K	Keepalive Monitoring	13
L	LAN	13
	Last change	31
	Level	10
	Local PPP ID (default)	3
	Location	4
	Log host	9, 10
M	Maximum Number of Acctlog Entries	5
	Maximum number of syslog entries	5
	Message level for the syslog table	5
	Method	11
	Mode	28
	Monitored event	23
N	Name/Address	36
	Next index	22
	Notify	31



P	Password settings	33
	Activity Monitor	33
	admin	33
	Ex works state	33
	HTTP server	33
	read	33
	write	33
	Protocol	37
R	Range	17, 19
	read Login Password/SNMP Community	33
S	Set value active	30
	Source IP	16
	Start time	26
	Status	26, 31
	Subsystems	9
	Syslog messages	9
	Display	3
	Number	3
	Priority	3
	Syslog output on serial console	4
	System name	3
	System time	35
	Accounting	35
	Automatic	35
	Manual	35
	System Time Offset from GMT	36
T	Table	23, 30
	Time and date	35
	Time Update Interval	36
	Timestamp	10
	Trials	15
	Trigger	18
	Type	8, 10, 22



U	Update interval	8
	Update System Time from ISDN	36
V	Value inactive	30
	Variable	24, 30
W	write Login Password/SNMP Community	33



Index: External Systems

A	Admin. Password	10
	AP MAC Address	8
	Authentisierungsverhandlung	3
C	Calling Party Number	3
	CLID	3
G	Gateway Address	10
I	Interface	4, 6, 7
	IP Address	9
	IP Status	8
L	Last Change	9
	Last Run	5
N	Netmask	10
	Node Name	9
O	Operation	4, 6, 8
R	Result	5, 9



Index: Ethernet

A	Advanced settings	7, 13
B	Back Route Verify	7, 8, 9
	Bridging	6
D	DHCP Hostname	4
	DHCP MAC address	4
E	Encapsulation	5, 12
	ETH interfaces	3
	Ethernet unit	3
I	IP accounting	7, 8, 9
	IP configuration	4, 11, 13
L	Local IP number	11
	local IP-Number	4
	Local netmask	11
	local Netmask	4
M	MAC address	5, 11, 12
	Mode	5
P	Proxy ARP	7, 8, 9
R	RIP	7, 9
	V1	9
	V2	9
	RIP receive	9
	RIP send	8
	Route	7
	Routing	7
	Routing table	7



S	Second local IP number	4, 11
	Second local netmask	4, 12
V	Virtual interfaces	11
	VLAN ID	5, 12
W	WAN partner	8

Index: ISDN

B	B-channel 1	6
	B-channel 2	6
	Bearer	11
D	D-channel	6
I	IPSec	12
	ISDN Login	9, 12
	ISDN switch type	5, 6
	Item	11
L	leased dte, dce	6
	Leased line	5
M	Mode	11
N	Number	11
P	Point to multipoint	5
	Point to point	5
	PPP (routing)	9, 12
	PPP 64k	12
	PPP DOVB	12
	PPP V.110 (1200...38400)	12
	PPP V.120	12
R	Result of autoconfiguration	4
S	Specify TEI Value	13
	SPID B-channel 1	7
	SPID B-channel 1+2	7
	SPID B-channel 2	7



X	X.31 TEI Service	14
	X.31 TEI Value	13



Index: AUX

A	Active profile	5
	Analog connections	3
	Analog/GSM interface	3
D	Dispatch item	6
E	Escape char	7
G	GSM modem	3, 6
	GSM SIM PIN	6
I	Init sequence	7
L	Line speed	5
M	Modem	3
P	Profile	5
	Profile configuration	5
S	Serial port	4





Index: Wireless LAN

A	Accept Address	10
	AdminStatus	6, 10, 15
B	Bridging enabled	15
C	Channel	4
D	Default Key	7
E	Ena.	14
K	Key	8
L	local communication	11
	Local IP	14
	Local IP-Address	15
	local IP-Number	12
	local Netmask	12
	Location	4
M	MAC Address	14
	Max. Clients	6
	Maximum Bitrate	18
	Mode	11
N	Name is visible	6
	Network Name	6
	Network/Mask	14
	NITRO Burst	18
O	Operation Mode	3
P	Partner IP-Address	15



	Preshared Key	8
R	Remote IP	14
	Remote Netmask	15
	Remote Network	15
	Remote WDS MAC Address	15
S	Second Local IP-Number	12
	Second Local Netmask	12
	Security Mode	7
T	Timeout (minutes)	19
	TX Power (dBm)	18
W	Wireless Mode	18

Index: WAN Partner

A	Advanced settings	48
	Authentication	11
	Authentication negotiation	11
B	Back Route Verification	49
	Back Route Verify	50
	Bandwidth on Demand (BoD)	22
	Basic IP settings	37
	Bridge	55
	Bridging Mode	55
	C	Callback
Calling Line Identification		7
Channel bundling		16, 18
Closed User Group		35
Compression		6, 7
CUG index		35
D		D-channel queue length
	Default route	37, 40, 41
	Delay after connection failure	16
	Delay after connection failure (sec)	17
	Destination IP address	43, 46
	Destination port	47
	Direction	34
	Dynamic Name Server Negotiation	51, 53
	E	Enable NAT
Encapsulation		5, 6
Encryption		6
Encryption key negotiation		26
Extended interface settings		22
Extended IP routing		44
Extended routing		44

F	Flags	41
G	Gateway IP Address	41
	Gateway IP address	43
	Gear down threshold	25
	Gear up threshold	24
I	Idle for dynamic short hold (%)	17
	IP	37
	IP accounting	49, 50
	IP transit network	39
	ISDN ports to use	34
K	Keepalives	12
L	Layer 1 protocol	16, 17, 21
	Line utilization sample (sec)	24
	Line utilization weighting	24
	Link Quality Monitoring	12
	Local IP address	39
	Local PPP ID	11
	Local PPTP VPN IP Address	41
M	Maximum number of dialup channels	25
	Metric	44, 46
	Mode	23, 26, 46
	More routing	41
N	Netmask	43, 46
	Network	43, 44, 45
	Number	33
P	Partner / Interface	43, 46
	Partner IP address	39
	Partner name	3, 5
	Partner PPP ID	11



	PPP password	11
	PPTP VPN Partner's IP Address	40
	Pro	41
	Protocol	3, 46
	Proxy ARP	49, 51, 52
R	Remote IP address	40
	Remote netmask	40
	Remote X.25 address	18
	RIP	48
	RIP receive	50, 52
	RIP send	50, 52
	Route	37
	Route announce	49, 51
	Route type	43, 45
	Routing settings	37
	RX Key	26
S	Short hold	15
	Source interface	46
	Source IP address	46
	Source mask	46
	Source port	47
	Special interface types	19
	State	3
	Static short hold (sec)	17
T	TOS mask	46
	Total number of channels	18
	TX Key	26
	Type of Service (TOS)	46
U	Use Gateway	40
V	Van Jacobson Header Compression via IP Interface	51 40



W WAN partner numbers

33



Index: Security

Numerics

3des	44
A	
Access restrictions	13
Action	11, 20, 31
Admin status	6, 27
Adminstatus	27
aes128	44
aes192	44
aes256	44
Alias	32, 34
arc4	44
B	
blowfish	44
C	
cast128	44
Category	9
Chain	14
Challenge response	43
Classification	5
ClientAliveCountMax	41
ClientAliveInterval	42
Compression	39
Connection state	17
D	
Day	10
Deny Silent	22
Description	16
Destination	30
Destination address	17
Destination mask	17
Destination port	18
Dynamic packet filtering	25

E	Expiring date	6
F	Filter	13, 14, 20
	Filter list	8
	Filtered interfaces	6
	First rule	22
	From	10
	Full filtering	28
H	History entries	7
I	ICMP type	32
	Index	16, 20
	Insert behind Rule	20
	Interface	14, 22, 35, 51
	IP access lists	26
	IP address	34, 51
	IP mask	35
	IP range	34
L	Local filter	27
	Logging level	28, 40
	Login Grace Time	41
M	Mask	51
	Max. # of Clients	38
	md5	45
	md5-96	45
	Mode	34
N	NAT	26
	Network access control	13
	Next rule	20
O	Orange filter ticket	6
	Order	20



	Other inactivity timeout	36
P	Password	43
	Port	33
	Port # used for Connections	38
	PPTP inactivity Timeout	36
	Print LastLog	39
	Print Motd	39
	Priority	11
	Protocol	16, 32
	Protocol version	43
	Public key	43
R	Range	33
	Reporting method	23
	ripemd160	45
	Rule chains	19
S	Safety feature	25
	Service	31, 50
	shal	45
	shal-96	45
	SIF	26
	Source	18, 30
	Source address	17
	Source mask	17
	Source port	17, 18
	Specify Port	17
T	TCP inactivity Timeout	36
	TCP Keepalives	41
	Ticket status	6
	To	11
	TOS mask	18
	Type	17
	Type of Service (TOS)	18



U	UDP inactivity Timeout	36
	URL-based content filtering service	5
V	Verify interface	51
	Verify IP address	50
	Verify reverse mapping	39

Index: PPTP

B	Back Route Verification	32
	Back Route Verify	33
C	Closed User Group	20
	CUG index	20
D	Default route	24
	Delay after connection failure	12
	Destination IP address	26, 28
	Destination port	29, 30
	Direction	18
	Dynamic Name Server Negotiation	34, 35
E	Enable NAT	24
I	IP accounting	32, 33
	ISDN ports to use	18
M	Metric	27, 29
	Mode	29, 30
N	Netmask	27, 28
	Network	26, 28
	Number	17
P	Partner / Interface	27, 29
	Protocol	29
	Proxy Arp	32, 33, 35
R	Remote IP address	24
	Remote netmask	24
	RIP	31
	RIP receive	33, 34
	RIP send	33, 34



	Route announce	32, 33
	Route type	26, 28
	Routing	31
	Routing protocol	31
	Routing table	31
S	Source interface	29
	Source IP address	29
	Source mask	29
	Source port	29, 30
T	TOS mask	29
	Type of Service (TOS)	29
W	WAN partner numbers	17

Index: IPsec

Numerics

1 (768-bit MODP)	36, 65
2 (1024-bit MODP)	36, 65
3DES	32, 45, 60, 73
5 (1536-bit MODP)	37, 65

A

A	6
abort	99
ACTION	13
Action	8, 49, 50, 55
Admin Status	12
Admin status	15
aggressive	38, 66
aggressive-only	38, 67
AH (Authentication Header)	44, 72
Algorithm	78
Authentication method	58
auto/base64/binary	90
Autosave	82
Available encryption and message hash algorithms	32

B

Block time	59
Blowfish	32, 45, 60, 73

C

CA certificate	81
CA certificates	39, 59, 67
CA domain	82
CAST	32, 45, 60, 73
CEA	109
Certificate authority certificates	86
Certname	83
clear config	98
Combination of encryption and message hash algorithms for IKE phase 1	31
Cookies size	95
CRL	39, 67



CRLs	90
D	
default	38, 66
DES	32, 45, 60, 73
Description	7, 12, 14, 48, 54, 57, 78, 87, 88
Description (Idx 0)	41
Description (Idx 1)	69
dhcp	9, 50, 56
Direct ISDN call	18
DN	84
DNS	84
Don't Send Cert Chains	94
Don't Send Cert Req Payl.	94
Don't Send CRLs	94
Don't Send Initial Contact	94
Don't Send Key Hash Payl.	94
drop	50
DSA signatures	37, 65
dump messages	98
DynDNS service	18
E	
Email	84
Enable IPsec	4
ESP (Encapsulated Security Payload)	43, 71
F	
First active rule	6
Flags	87
force Comp	45, 73
Force trusted	90
G	
Group	58
H	
Heartbeats	42, 58, 70
host	8, 49, 55
I	
ID Protect Mode	21
id_protect	38, 66



	id-protect-only	38, 66
	Ignore Cert Req Payloads	93
	IKE (Phase 1) defaults	4
	Import a certificate/CRL using	89
	In	109
	Incoming ISDN number	19
	Interface IP Settings	17
	Interoperability flags	93
	IP	84
	IP address transfer	21
	IPComP	44, 72
	IPsec (Phase 2) defaults	4
	ISDN callback	19
K	Kb	64
	Key size (bits)	79
	Key to enroll	80
L	Lifetime	41, 58, 69
	Lifetime restriction based on	63
	Local	108
	Type	7, 48, 54
	Local Address	12
	Local address	5
	Local certificate	59
	Local ID	59, 106
	Local/Remote	
	Type	49, 55
	LPort	108
M	M/R	6
	Matching policy	64
	Max. Symmetric Key Length	95
	MD5	45, 73
	MD5 (Message Digest #5)	32, 61
	Method	81
	Method of operation	21

Mode	58
Modifying IKE and IPSec settings	26
MODP	36
N Name	90
Nat-Traversal	31, 59
net	8, 49, 55
no Comp	44, 72
NULL	45, 46, 73, 74
O Oper Status	12
Oper status	15
Out	109
Outgoing ISDN number	19
Own certificates	86
own/peer	9, 50, 56
P Packets in	105
pass	50
Password	82
peer	9, 50
Peer address	15
Peer certificates	86
Peer IDs	16
Peers blocked	104
Peers dormant	104
Peers up	104
Phase 1	
Authentication method	37, 65
Group	36, 64
Lifetime	62
Local certificate	39, 67
Local ID	39, 67
Mode	38, 66
NAT Traversal	39
Proposal	31, 60



Phase 2	
Lifetime	46, 74
Proposal	43, 71
Please enter certificate data	89
Port	6
Preshared key	16
Preshared keys	37, 65
Profile	49
Propagate PMTU	43, 71
Proposal	6, 41, 58, 69
protect	51
Proto	6
Protocol	7, 48, 54
Pto	108
R	
RA-Certificate (Encrypt)	86
RA-Certificate (Sign)	86
RADIUS authentication	95
range	9, 50, 56
Registration Authority Certificates	84
Remote	108
Type	8, 48, 54
Remote Address	12
Remote address	6
Remote ID	106
Remote IP	106
Request cert	79
RID	84
Rijndael	32, 45, 60, 73
RipeMD 160	33, 61
RPort	108
RSA encryption	37, 66
RSA Public Exponent	79
RSA signatures	37, 65
S	
SAs Phase 1	13
SAs phase 1	104

SAs Phase 2	13
SAs phase 2	104
Seconds	63
Serial no.	87
Server	83, 90
Setup Tool Wizard	3
SHA1	45, 73
SHA1 (Secure Hash Algorithm #1)	33, 61
Signing Algorithm to Use	83
skip	99
start (wizard)	99
Start of IKE phase 1 negotiation	21
State of last enrollment	83
Step 1 (NAT settings)	99
Step 2 (creation of proposals)	99
Step 3 (define authentication method)	99
Step 4 (request certificate)	100
Step 5 (own certificate)	100
Step 6 (CA certificate)	100
Step 7 (CRL server / peer certificate)	100
Step 8 (peer)	101
Step 9 (peer traffic / peer interface)	101
Subject Alternative Names	83
Subject Alternative Names – Type	83
Subject Alternative Names – Value	83
Subject Alternative Names (optional)	82
Subject name	82, 87
Sync SAs With Local Ifc	95
T TARSEH	106, 107
The IPsec Wizard step by step	99
Tiger 192	33, 61
Traffic List Settings	17
Trust ICMP Messages	94
Twofish	32, 45, 60, 73
Type	84
Type of certificate	88, 89



U	URI	84
	Use PFS	41, 46, 69, 74
	Use Zero Cookies	95
V	View proposals	33, 43, 62
	Virtual interface	17
W	What to do?	98



Index: IP

A	Action	34
	Add Routing Entry	5
	ADDEXT	7
	Address	60, 63, 92
	Admin Status	88
	Administrative Status	53
	Advertise Matching	93
	Alive Check (if inactive)	49
	Area ID	88, 91
	Area Range	92
	Authentication Key	89
	Authentication Type	89
B	Bandwidth Management	21
	Bandwidth on Demand	21
	Block Time (seconds)	52
	BOD	21
C	Cache Hitrate (%)	66
	Cache Hits	66
	Chain	29
	Client / Server	43
	Connection State	31
D	Default Domain	60
	Default Domains	61
	Default Interface	58
	Default Route distribution	76
	Description	22, 30
	Destination Address	31
	Destination IP Address	6
	Destination Mask	31
	Destination Port	9, 10, 32
	DHCP Assignment	58



Dialout	49
Direction	34, 81
Distribution	81
Distribution Fraction (in percent)	24
Distribution Mode	23
Distribution Policy	22, 24
Distribution Ratio	23
DNS	11, 55
DNS Proxy	11
DNS Requests	66
Domain Name	11
Domain Name Server	11, 55
Dynamic Cache	59
DynDNS Registration	67
E Edit Routing Entry	5
Encryption (recommended)	51
Export indirect static routes	89
Extended Routing	7
External Address	17
External Mask	17
External Port	18
F Filter	29, 34
First Rule	36
Flags	5
Forwarded Domains	59
Forwarded Requests	66
G Garbage Collection Timer	78
Gateway	40
Gateway IP Address	7
Generate Default Route for the AS	85
H Hold down timer	78
Host Name	68
HTTP TCP Port	12



I	Ignore	7
	Import external routes	91
	Index	30, 33
	Insert behind Rule	33
	Interface	29, 36, 39, 62, 68, 80
	Interface 1 - 3	23
	Interface Group ID	22
	Internal Address	18
	Internal Mask	18
	Internal Port	19
	Invalid DNS Packets	66
	IP Address	37, 39, 46, 80
	IP Address Pool LAN (DHCP)	39
	IP Address Pool WAN (PPP)	37
	IPCP Assignment	58
L	LAN	7, 28
	Lease Time (Minutes)	40
	Load Balancing	21
	Local Nameservers	61
	Login Authentication/Authorization	52
M	MAC Address	40
	Mask	92
	Maximum Number of DNS Records	64
	Maximum TTL for Neg Cache Entries	65
	Maximum TTL for Pos Cache Entries	65
	Metric	7, 89
	Metric Determination	88, 90
	Metric1 offset on interface dormant	82
	Metric1 offset on interface up	81
	Minimum Wait	71
	Mode	8, 9
	MX	69
N	Name	60, 61, 63, 70

Name Resolution	55
Negative Cache	57
NetBT Node Type	40
Netmask	6, 80
Network	6
Network Address Translation	14
Next Rule	34
Number of Channels	34
Number of Consecutive Addresses	37, 40
O OSPF	73, 85
Overwrite Global Nameservers	58
P Partner / Interface	7
Password	46, 68
Path	70
Permission	69
Poisoned Reverse	76
Policy	47, 51
Pool ID	37
Port	47, 70
Positive Cache	57
PPP Authentication	52
PPTP Passthrough	14
Primary BOOTP Relay Server	12
Primary Domain Name Server	11
Primary WINS	11
Priority	46, 50, 81
Propagate Routes on discard/refuse interfaces	86
Protocol	9, 16, 30, 46, 71
Provider	69
R RADIUS packets	44
Received DNS Packets	66
Ref	63
Refuse	7
Remote Address	17



Remote CAPI Server TCP Port	12
Remote Mask	17
Remote Port	17
Remote TRACE Server TCP Port	12
Resp	63
Response	60
Retransmission timer	79
Retries	48
RFC 2091 variable timer	77
RFC 2453 variable timer	76
RIP	73
RIP UDP Port	12
Route Timeout	78
Route Type	6
Routing Protocols	73
Rule	29

S Secondary BOOTP Relay Server	12
Secondary Domain Name Server	11
Secondary WINS	11
Server	70
Server Failures	66
Server's IP Address or Hostname	50
Service	16
Silent Deny	14
SNMP	41
SNMP listen UDP port	41
SNMP trap broadcasting	41
SNMP trap community	42
SNMP trap UDP port	41
Source Address	31
Source Interface	9
Source IP Address	9
Source Mask	9, 31
Source Port	9, 10, 31
Specify Port	31
State	48



Static Hosts	58
Successfully Answered Queries	66
T	
TACACS+ Accounting	52
TACACS+ Key (Secret)	51
TACACS+ Single-Connection	53
TCP Port	51
Timeout (ms)	47
Timeout (seconds)	52
TOS Mask	9, 32
TTL	60, 62, 63
Type	31
Type of Service (TOS)	9, 32
U	
Unique Source IP Address	12
Update Timer	78
User	68
V	
Validate	48
W	
WAN with transit network	7, 28
WAN without transit network	7, 28
Wildcard	69
WINS	11



Index: PPP

A	Authentication Negotiation	3
	Authentication Protocol	4
C	Calling party number	3
	CHAP	4
	CLID	3, 5
L	Link Quality Monitoring	5
M	MS-CHAP	4
P	PAP	4
	PPP Link Quality Monitoring	5
	PPPoE Ethernet Interface	6
R	RADIUS	5
	Radius Server Authentication	5



Index: BRRP

A	Advertisement Interval	3
	Advertisement Interval Errors	3
	Advertisements Received	3
	Authentication Errors	3
	Authentication Key	5
	Authentication Type	5
	Authentication Type Mismatch	3
B	Backup	8
	Become Master	3
	BRRP states	6
C	Checksum Errors	3
I	Initialize	7
	Interface	3
	Invalid Authentication Type	3
	Invalid Type Packets Received	3
	IP Address Owner	3
	IP TTL Errors	3
M	MAC address	4, 3
	Master	9
	Master Action	3
	Master Down Interval	4
	Master Interface	4
	Master Interface Protocol	3
	Master IP address	3
P	Packet Length Errors	3
	Pre-empt Mode	4
	Primary IP Address	3
	Priority	2



R	Redundant network environment	1
	RFC 2338	1
	Router redundancy procedure	1
S	Slave Admin Action	5
	Slave Interface	6
	Slave Interface Protocol	4
T	Task ID	2
V	Version Errors	3
	Virtual Router	1, 3
	Virtual Router Backup	3
	Virtual Router ID	4, 5, 2
	Virtual Router Master	3
	Virtual Router State	2
	VRRP Advertisement	3
	VRRP Router	2
	W	Watchdog Daemon

Index: CREDITS

C	Charges	3
	Credits Based Accounting System	3
I	ISDN Credits	5
	isdnlogin	5
M	Maximum Charge	7
	Maximum Number of Current Incoming Connections	8
	Maximum Number of Current Outgoing Connections	8
	Maximum Number of Incoming Connections	7
	Maximum Number of Outgoing Connections	7, 10
	Maximum Time for Incoming Connections (sec)	7
	Maximum Time for Outgoing Connections (sec)	7, 10
P	Measure Time (sec)	6, 9
	ppp	5
	PPPoE	9
S	Surveillance	6, 9
	Syslog messages	3
X	xDSL	9





Index: CAPI

C	CAPI	4
N	Name	4
P	Password	4



Index: QoS

A	Action	11
B	Bound Transmit Rate (Shaping)	24
C	Class	23
	Class ID	12, 23
	Class Type	12
	Classification of IP Packets	9
	Congestion Avoidance Algorithm	25
	Connection State	7
D	Description	6
	Destination Address	7
	Destination Mask	7
	Destination Port	8
	Direction	10
	Dropping Algorithm	26
F	Filter	10
I	Index	6, 10
	Insert behind Rule	11
	Interface	18
	IP QoS Classification via	18
L	Lower Queue Threshold (Bytes)	26
M	Maximum Burst Size (Number of Bits)	14
	Maximum Burst Size (Number of Packets)	14
	Maximum Rate (Bits per Second)	14
	Maximum Rate (Packets per Second)	14
	Maximum Transmit Rate (Bits per Second)	22
	MLPPP Fragment Size	19



	MLPPP Interleave Mode	19
N	Next Rule	11
P	Priority Protocol	25 6
Q	Queuing and Scheduling Algorithm	20
S	Set Remark Type of Service (TOS) Field	15
	Set Type of Service (TOS) Field	13
	Shaping Algorithm	25
	Source Address	7
	Source Mask	7
	Source Port	7, 8
	Specify Port	7
	Specify ToS Set Exceed Action	14
	Specify ToS Set Rate Limitation	13
	Specify Traffic Shaping	21
T	TOS Mask	8
	Transmit Rate (Bits per Second)	24
	Transmit Rate Burst	24
	Type	7
	Type of Service (TOS)	8
U	Upper Queue Threshold (Bytes)	26
W	Weight	24



Index: GRE

G	Generic Routing Encapsulation	3
	GRE Local IP Address	4
	GRE Partner's IP Address	4
	GRE V.0	3
	GRE V.1	3
K	Key Used	5
M	Mtu	5
N	Name	4
P	Partner's LAN IP Address	4
	Partner's LAN IP Mask	4
V	Value	5
	Virtual Interface	3



Index: L2TP

D	Data Packets Sequence Numbers	10
H	Hello Interval	9
L	LAC	3
	Layer 2 Tunneling Protocol	3
	LNS	3
	Local Hostname	8
	Local IP Address	7
	Local UDP Port (LAC only)	8
M	Maximum Retry Count	10
	Maximum Time Between Retries	10
	Minimum Time Between Retries	10
P	Port usage for LNS mode	5
	Profile Name	7
R	Remote Hostname	9
	Remote IP Address (LAC only)	8
	Remote UDP Port (LAC only)	8
T	Tunnel Password	9
U	UDP port number for LNS mode	5



Index: Configuration Management

B	boot	3
	Boot configuration file	3
C	Configuration information	3
F	Flash	3
	Flash EEPROM	3
N	Name in Flash	4
	New Name in Flash	4
O	Operation	4, 5
	Operations	3
R	RAM	3
S	Start Operation	5
	State of last operation	4
T	TFTP File Name	4
	TFTP Server	3
	TFTP Server IP Address	4
	Type of last operation	4
U	Unix	3
W	Windows	3

