



## Index: Licenses

<b>A</b>	Available subsystems	4
<b>D</b>	Description	5
<b>E</b>	Ex works state	4
<b>H</b>	Hardware serial number	3
<b>K</b>	Key	3, 5
<b>L</b>	License data	
	Activating extra licenses	4
	License serial number	3
	PIN	3
	Serial number	3
	Software license ID	3
	License serial number	3
<b>M</b>	Mask	5
<b>O</b>	Online licensing	3, 5
<b>P</b>	PIN	3
<b>S</b>	Serial Number	5
	Serial number	3, 5
	Software license ID	3





## Index: System

<b>Numerics</b>	1st Event index	25
<b>A</b>	Action	15
	Activity Monitor	7
<b>B</b>	Basic system data	3
<b>C</b>	Central server	11
	CLID	11
	Client IP address	8
	Client UDP port	8
	Compare value	22
	Condition	22
	Contact	4
<b>D</b>	Description	19, 25
	DownAction	13
<b>E</b>	End time	23
	End value	23
	Event protocol	9
	Eventlist condition	26
	Execute command	26
	External Activity Monitor	7
	External system logging	9
<b>F</b>	Facility	10
	FirstIfIndex	13, 16
<b>G</b>	Group	12
<b>H</b>	Hosts	11



<b>I</b>	Index	19, 25
	Index value	21, 27
	Index variable	21, 27
	Interface	15, 26
	Interfaces	11
	Interval	12
	IP address	12
<b>K</b>	Keepalive Monitoring	11
<b>L</b>	LAN	11
	Last change	28
	Level	10
	Local PPP ID (default)	3
	Location	4
	Log host	9, 10
<b>M</b>	Maximum number of syslog entries	5
	Message level for the syslog table	5
	Mode	25
	Monitored event	20
<b>N</b>	Name/Address	32
	Next index	19
	Notify	28
<b>P</b>	Password settings	29
	Activity Monitor	29
	admin	29
	Ex works state	29
	HTTP server	29
	read	29
	write	29
	Protocol	33
<b>R</b>	Range	14, 16



<b>S</b>	Set value active	27
	Source IP	13
	Start time	23
	Status	23, 28
	Subsystems	9
	Syslog messages	9
	Syslog output on serial console	4
	System name	3
	System time	31
	Accounting	31
	Automatic	31
	Manual	31
	System Time Offset from GMT	32
<b>T</b>	Table	20, 27
	Time and date	31
	Time Update Interval	32
	Timestamp	10
	Trials	12
	Trigger	15
	Type	8, 10, 19
<b>U</b>	Update interval	8
<b>V</b>	Value inactive	27
	Variable	21, 27





## Index: External Systems

<b>A</b>	Admin. Password	10
	AP MAC Address	8
	Authentisierungsverhandlung	3
<b>C</b>	Calling Party Number	3
	CLID	3
<b>G</b>	Gateway Address	10
<b>I</b>	Interface	4, 6, 7
	IP Address	9
	IP Status	8
<b>L</b>	Last Change	9
	Last Run	5
<b>N</b>	Netmask	10
	Node Name	9
<b>O</b>	Operation	4, 6, 8
<b>R</b>	Result	5, 9





## Index: Ethernet

<b>A</b>	Advanced settings	7, 13
<b>B</b>	Back Route Verify	7, 8, 9
	Bridging	6
<b>D</b>	DHCP Hostname	4
	DHCP MAC address	4
<b>E</b>	Encapsulation	5, 12
	ETH interfaces	3
	Ethernet unit	3
<b>I</b>	IP accounting	7, 8, 9
	IP configuration	4, 11, 13
<b>L</b>	Local IP number	11
	local IP-Number	4
	Local netmask	11
	local Netmask	4
<b>M</b>	MAC address	5, 11, 12
	Mode	5
<b>P</b>	Proxy ARP	7, 8, 9
<b>R</b>	RIP	7, 9
	V1	9
	V2	9
	RIP receive	9
	RIP send	8
	Route	7
	Routing	7
	Routing table	7



<b>S</b>	Second local IP number	4, 11
	Second local netmask	4, 12
<b>V</b>	Virtual interfaces	11
	VLAN ID	5, 12
<b>W</b>	WAN partner	8

## Index: Wireless LAN

<b>A</b>	Accept Address	10
	AdminStatus	7, 10
<b>C</b>	Channel	4
<b>D</b>	Default Key	8
<b>F</b>	FOUR-X Burst	14
<b>K</b>	Key	8
<b>L</b>	local communication	11
	local IP-Number	12
	local Netmask	12
	Location	4
<b>M</b>	Maximum Bitrate	14
	Mode	11
<b>N</b>	Name is visible	7
	Network Name	7
<b>O</b>	Operation Mode	4
<b>P</b>	Preshared Key	9
<b>S</b>	Second Local IP-Number	12
	Second Local Netmask	12
	Security Mode	7
<b>T</b>	TX Power (dBm)	14



**W** Wireless Mode

14

## Index: ADSL

<b>M</b>	Maximum threshold (kb/s)	6
<b>P</b>	Physical connection established	5
<b>T</b>	Transmit shaping	5



## Index: WAN Partner

<b>A</b>	Advanced settings	26
	Authentication	7
	Authentication negotiation	7
<b>B</b>	Back Route Verification	28
	Back Route Verify	29
	Basic IP settings	15
	Bridge	33
	Bridging Mode	33
<b>C</b>	Channel bundling	12
<b>D</b>	Default route	15, 18, 19
	Delay after connection failure	11
	Delay after connection failure (sec)	12
	Destination IP address	21, 24
	Destination port	25
	Dynamic Name Server Negotiation	30, 31
<b>E</b>	Enable NAT	17, 19
	Encapsulation	5, 6
	Extended IP routing	22
	Extended routing	22
<b>F</b>	Flags	19
<b>G</b>	Gateway IP Address	19
	Gateway IP address	21, 24
<b>I</b>	IP	15
	IP accounting	28, 29
	IP transit network	17

<b>K</b>	Keepalives	8
<b>L</b>	Layer 1 protocol	11, 12, 13
	Link Quality Monitoring	8
	Local IP address	17
	Local PPP ID	7
	Local PPTP VPN IP Address	19
<b>M</b>	Metric	21, 24
	Mode	24
	More routing	19
<b>N</b>	Netmask	21, 24
	Network	21, 22, 23
<b>P</b>	Partner / Interface	21, 24
	Partner IP address	17
	Partner name	3, 5
	Partner PPP ID	7
	PPP password	7
	PPTP VPN Partner's IP Address	18
	Pro	19
	Protocol	3, 25
	Proxy ARP	28, 29, 31
<b>R</b>	Remote IP address	18
	Remote netmask	18
	RIP	27
	RIP receive	29, 30
	RIP send	29, 30
	Route	15
	Route announce	28, 29
	Route type	21, 23
	Routing settings	15
<b>S</b>	Short hold	11





	Source interface	24
	Source IP address	24
	Source mask	24
	Source port	25, 26
	Special interface types	13
	State	3
	Static short hold (sec)	12
<b>T</b>	TOS mask	24
	Type of Service (TOS)	24
<b>U</b>	Use Gateway	18
<b>V</b>	Van Jacobson Header Compression via IP Interface	30 18

# Index: IPsec

## Numerics

1 (768-bit MODP)	28, 57
2 (1024-bit MODP)	28, 57
3DES	24, 37, 52, 65
5 (1536-bit MODP)	29, 57

## A

A	6
abort	91
ACTION	13
Action	8, 41, 42, 47
Admin Status	12
Admin status	15
aggressive	30, 58
aggressive-only	30, 59
AH (Authentication Header)	36, 64
Algorithm	70
Authentication method	50
auto/base64/binary	82
Autosave	74
Available encryption and message hash algorithms	24

## B

Block time	51
Blowfish	24, 37, 52, 65

## C

CA certificate	73
CA certificates	31, 51, 59
CA domain	74
CAST	24, 37, 52, 65
CEA	101
Certificate authority certificates	78
Certname	75
clear config	90
Combination of encryption and message hash algorithms for IKE phase 1	23
Cookies size	87
CRL	31, 59



CRLs	82
<b>D</b>	
default	30, 58
DES	24, 37, 52, 65
Description	7, 12, 14, 40, 46, 49, 70, 79, 80
Description (Idx 0)	33
Description (Idx 1)	61
dhcp	9, 42, 48
DN	76
DNS	76
Don't Send Cert Chains	86
Don't Send Cert Req Payl.	86
Don't Send CRLs	86
Don't Send Initial Contact	86
Don't Send Key Hash Payl.	86
drop	42
DSA signatures	29, 57
dump messages	90
<b>E</b>	
Email	76
Enable IPsec	4
ESP (Encapsulated Security Payload)	35, 63
<b>F</b>	
First active rule	6
Flags	79
force Comp	37, 65
Force trusted	82
<b>G</b>	
Group	50
<b>H</b>	
Heartbeats	34, 50, 62
host	8, 41, 47
<b>I</b>	
id_protect	30, 58
id-protect-only	30, 58
Ignore Cert Req Payloads	85
IKE (Phase 1) defaults	4



	Import a certificate/CRL using	81
	In	101
	Interface IP Settings	17
	Interoperability flags	85
	IP	76
	IPComP	36, 64
	IPsec (Phase 2) defaults	4
<b>K</b>	Kb	56
	Key size (bits)	71
	Key to enroll	72
<b>L</b>	Lifetime	33, 50, 61
	Lifetime restriction based on	55
	Local	100
	Type	7, 40, 46
	Local Address	12
	Local address	5
	Local certificate	51
	Local ID	51, 99
	Local/Remote	
	Type	41, 47
	LPort	100
<b>M</b>	M/R	6
	Matching policy	56
	Max. Symmetric Key Length	87
	MD5	37, 65
	MD5 (Message Digest #5)	24, 53
	Method	73
	Mode	50
	Modifying IKE and IPsec settings	18
	MODP	28
<b>N</b>	Name	82
	Nat-Traversal	23, 51
	net	8, 41, 47

no Comp	36, 64
NULL	37, 38, 65, 66
<b>O</b> Oper Status	12
Oper status	15
Out	101
Own certificates	78
own/peer	9, 42, 48
<b>P</b> Packets in	97
pass	42
Password	74
peer	9, 42
Peer address	15
Peer certificates	78
Peer IDs	16
Peers blocked	96
Peers dormant	96
Peers up	96
Phase 1	
Authentication method	29, 57
Group	28, 56
Lifetime	54
Local certificate	31, 59
Local ID	31, 59
Mode	30, 58
NAT Traversal	31
Proposal	23, 52
Phase 2	
Lifetime	38, 66
Proposal	35, 63
Please enter certificate data	81
Port	6
Preshared key	16
Preshared keys	29, 57
Profile	41
Propagate PMTU	35, 63



Proposal	6, 33, 50, 61
protect	43
Proto	6
Protocol	7, 40, 46
Pto	100
<b>R</b>	
RA-Certificate (Encrypt)	78
RA-Certificate (Sign)	78
RADIUS authentication	87
range	9, 42, 48
Registration Authority Certificates	76
Remote	100
Type	8, 40, 46
Remote Address	12
Remote address	6
Remote ID	98
Remote IP	98
Request cert	71
RID	76
Rijndael	24, 37, 52, 65
RipeMD 160	25, 53
RPort	100
RSA encryption	29, 58
RSA Public Exponent	71
RSA signatures	29, 57
<b>S</b>	
SAs Phase 1	13
SAs phase 1	96
SAs Phase 2	13
SAs phase 2	97
Seconds	55
Serial no.	79
Server	75, 82
Setup Tool Wizard	3
SHA1	37, 65
SHA1 (Secure Hash Algorithm #1)	25, 53
Signing Algorithm to Use	75

skip	91
start (wizard)	91
State of last enrollment	75
Step 1 (NAT settings)	91
Step 2 (creation of proposals)	91
Step 3 (define authentication method)	91
Step 4 (request certificate)	92
Step 5 (own certificate)	92
Step 6 (CA certificate)	92
Step 7 (CRL server / peer certificate)	92
Step 8 (peer)	93
Step 9 (peer traffic / peer interface)	93
Subject Alternative Names	75
Subject Alternative Names – Type	75
Subject Alternative Names – Value	75
Subject Alternative Names (optional)	74
Subject name	74, 79
Sync SAs With Local Ifc	87
<b>T</b>	
TARSEH	98, 99
The IPsec Wizard step by step	91
Tiger 192	25, 53
Traffic List Settings	17
Trust ICMP Messages	86
Twofish	24, 37, 52, 65
Type	76
Type of certificate	80, 81
<b>U</b>	
URI	76
Use PFS	33, 38, 61, 66
Use Zero Cookies	87
<b>V</b>	
View proposals	25, 35, 54
Virtual interface	17
<b>W</b>	
What to do?	90





## Index: Security

### Numerics

3des	46
<b>A</b>	
Access restrictions	15
Action	13, 22, 33
Admin status	8, 29
Adminstatus	29
aes128	46
aes192	46
aes256	46
Alias	34, 36
arc4	46
<b>B</b>	
blowfish	46
<b>C</b>	
cast128	46
Category	11
Chain	16
Challenge response	45
Classification	7
ClientAliveCountMax	43
ClientAliveInterval	44
Compression	41
Connection state	19
<b>D</b>	
Day	12
Deny Silent	24
Description	18
Destination	32
Destination address	19
Destination mask	19
Destination port	20
Dynamic packet filtering	27

<b>E</b>	Expiring date	8
<b>F</b>	Filter	15, 16, 22
	Filter list	10
	Filtered interfaces	8
	First rule	24
	From	12
	Full filtering	30
<b>H</b>	History entries	9
<b>I</b>	ICMP type	34
	Index	18, 22
	Insert behind Rule	22
	Interface	16, 24, 37, 55
	IP access lists	28
	IP address	36, 55
	IP mask	37
	IP range	36
<b>L</b>	Local filter	29
	Logging level	30, 42
	Login Grace Time	43
<b>M</b>	Mask	55
	Max. # of Clients	40
	md5	47
	md5-96	47
	Mode	36
<b>N</b>	NAT	28
	Network access control	15
	Next rule	22
<b>O</b>	Orange filter ticket	8
	Order	22

	Other inactivity timeout	38
<b>P</b>	Password	45
	Port	35
	Port # used for Connections	40
	PPTP inactivity Timeout	38
	Print LastLog	41
	Print Motd	41
	Priority	13
	Protocol	18, 34
	Protocol version	45
	Public key	45
<b>R</b>	Range	35
	Reporting method	25
	ripemd160	47
	Rule chains	21
<b>S</b>	Safety feature	27
	Service	33, 54
	shal	47
	shal-96	47
	SIF	28
	Source	20, 32
	Source address	19
	Source mask	19
	Source port	19, 20
	Specify Port	19
<b>T</b>	TCP inactivity Timeout	38
	TCP Keepalives	43
	Ticket status	8
	To	13
	TOS mask	20
	Type	19
	Type of Service (TOS)	20

<b>U</b>	UDP inactivity Timeout	38
	URL-based content filtering service	7
<b>V</b>	Verify interface	55
	Verify IP address	54
	Verify reverse mapping	41

## Index: IP

<b>A</b>	Add Routing Entry	5
	ADDEXT	7
	Address	52, 55
	Administrative Status	45
	Alive Check (if inactive)	41
<b>B</b>	Bandwidth Management	21
	Bandwidth on Demand	21
	Block Time (seconds)	44
	BOD	21
<b>C</b>	Cache Hitrate (%)	58
	Cache Hits	58
	Client / Server	35
<b>D</b>	Default Domain	52
	Default Domains	53
	Default Interface	50
	Default Route distribution	68
	Description	22
	Destination IP Address	6
	Destination Port	9, 10
	DHCP Assignment	50
	Dialout	41
	Direction	73
	Distribution	73
	Distribution Fraction (in percent)	24
	Distribution Mode	23
	Distribution Policy	22, 24
	Distribution Ratio	23
	DNS	11, 47
	DNS Proxy	11
	DNS Requests	58
	Domain Name	11



Domain Name Server	11, 47
Dynamic Cache	51
DynDNS Registration	59
<b>E</b> Edit Routing Entry	5
Encryption (recommended)	43
Extended Routing	7
External Address	17
External Mask	17
External Port	18
<b>F</b> Flags	5
Forwarded Domains	51
Forwarded Requests	58
<b>G</b> Garbage Collection Timer	70
Gateway	32
Gateway IP Address	7
<b>H</b> Hold down timer	70
Host Name	60
HTTP TCP Port	12
<b>I</b> Ignore	7
Interface	31, 54, 60, 72
Interface 1 - 3	23
Interface Group ID	22
Internal Address	18
Internal Mask	18
Internal Port	19
Invalid DNS Packets	58
IP Address	29, 31, 38, 72
IP Address Pool LAN (DHCP)	31
IP Address Pool WAN (PPP)	29
IPCP Assignment	50
<b>L</b> LAN	7, 28



	Lease Time (Minutes)	32
	Load Balancing	21
	Local Nameservers	53
	Login Authentication/Authorization	44
<b>M</b>	MAC Address	32
	Maximum Number of DNS Records	56
	Maximum TTL for Neg Cache Entries	57
	Maximum TTL for Pos Cache Entries	57
	Metric	7
	Metric1 offset on interface dormant	74
	Metric1 offset on interface up	73
	Minimum Wait	63
	Mode	8, 9
	MX	61
<b>N</b>	Name	52, 53, 55, 62
	Name Resolution	47
	Negative Cache	49
	NetBT Node Type	32
	Netmask	6, 72
	Network	6
	Network Address Translation	14
	Number of Consecutive Addresses	29, 32
<b>O</b>	OSPF	65
	Overwrite Global Nameservers	50
<b>P</b>	Partner / Interface	7
	Password	38, 60
	Path	62
	Permission	61
	Poisoned Reverse	68
	Policy	39, 43
	Pool ID	29
	Port	39, 62
	Positive Cache	49

PPP Authentication	44
PPTP Passthrough	14
Primary BOOTP Relay Server	12
Primary Domain Name Server	11
Primary WINS	11
Priority	38, 42, 73
Protocol	9, 16, 38, 63
Provider	61

<b>R</b> RADIUS packets	36
Received DNS Packets	58
Ref	55
Refuse	7
Remote Address	17
Remote Mask	17
Remote Port	17
Remote TRACE Server TCP Port	12
Resp	55
Response	52
Retransmission timer	71
Retries	40
RFC 2091 variable timer	69
RFC 2453 variable timer	68
RIP	65
RIP UDP Port	12
Route Timeout	70
Route Type	6
Routing Protocols	65

<b>S</b> Secondary BOOTP Relay Server	12
Secondary Domain Name Server	11
Secondary WINS	11
Server	62
Server Failures	58
Server's IP Address or Hostname	42
Service	16
Silent Deny	14





	SNMP	33
	SNMP listen UDP port	33
	SNMP trap broadcasting	33
	SNMP trap community	34
	SNMP trap UDP port	33
	Source Interface	9
	Source IP Address	9
	Source Mask	9
	Source Port	9, 10
	State	40
	Static Hosts	50
	Successfully Answered Queries	58
<b>T</b>	TACACS+ Accounting	44
	TACACS+ Key (Secret)	43
	TACACS+ Single-Connection	45
	TCP Port	43
	Timeout (ms)	39
	Timeout (seconds)	44
	TOS Mask	9
	TTL	52, 54, 55
	Type of Service (TOS)	9
<b>U</b>	Unique Source IP Address	12
	Update Timer	70
	User	60
<b>V</b>	Validate	40
<b>W</b>	WAN with transit network	7, 28
	WAN without transit network	7, 28
	Wildcard	61
	WINS	11





## Index: PPP

<b>A</b>	Authentication Negotiation	3
	Authentication Protocol	4
<b>C</b>	Calling party number	3
	CHAP	4
	CLID	3
<b>L</b>	Link Quality Monitoring	4
<b>M</b>	MS-CHAP	4
<b>P</b>	PAP	4
	PPP Link Quality Monitoring	4
	PPPoE Ethernet Interface	4





## Index: CREDITS

<b>C</b>	Charges	3
	Credits Based Accounting System	3
<b>M</b>	Maximum Number of Outgoing Connections	6
	Maximum Time for Outgoing Connections (sec)	6
	Measure Time (sec)	5
<b>P</b>	PPPoE	5
<b>S</b>	Surveillance	5
	Syslog messages	3
<b>X</b>	xDSL	5





## Index: ATM

<b>A</b>	ATM Interface	5, 22, 29
	ATM Service Category	31
<b>B</b>	Back Route Verify	11
	Bridging	10
<b>C</b>	CC End-to-End	25
	CC Segment	26
	Client Type	16
<b>D</b>	Description	5
	DHCP Hostname	8
	DHCP MAC address	8
	Direction	26, 27
<b>E</b>	Encapsulation	6, 9, 13, 16, 18
<b>I</b>	IP accounting	11
	IP Configuration	19
	IP configuration	8, 13, 14
<b>L</b>	Local IP number	13
	Local IP-Number	19
	local IP-Number	8
	Local Netmask	19
	Local netmask	13
	local Netmask	8
	Loopback End-to-End	24
	Loopback Segment enable	24
<b>M</b>	MAC Address	13
	MAC address	9, 14
	Maximum Burst Size (MBS) in bytes	32
	Mode	9

<b>O</b>	OAM flow level	22
<b>P</b>	Peak Cell Rate (PCR) in bits per second	31
	Pending Requests (max)	24, 25
	Proxy ARP	11
<b>R</b>	RIP receive	11
	RIP send	10
<b>S</b>	Second local IP number	8, 13
	Second local netmask	8, 13
	Send Interval (sec)	24
	Sustained Cell Rate (SCR) in bits per second	32
<b>V</b>	VCI	23, 30
	Virtual channel connection (VCC)	22, 30
	Virtual channel identifier (VCI)	6
	Virtual path connection (VPC)	23
	Virtual path identifier (VPI)	6
	VLAN ID	9, 14
	VPI	23, 30



## Index: QoS

<b>A</b>	Action	11
<b>B</b>	Bound Transmit Rate (Shaping)	24
<b>C</b>	Class	23
	Class ID	12, 23
	Class Type	12
	Classification of IP Packets	9
	Congestion Avoidance Algorithm	25
	Connection State	7
<b>D</b>	Description	6
	Destination Address	7
	Destination Mask	7
	Destination Port	8
	Direction	10
	Dropping Algorithm	26
<b>F</b>	Filter	10
<b>I</b>	Index	6, 10
	Insert behind Rule	11
	Interface	18
	IP QoS Classification via	18
<b>L</b>	Lower Queue Threshold (Bytes)	26
<b>M</b>	Maximum Burst Size (Number of Bits)	14
	Maximum Burst Size (Number of Packets)	14
	Maximum Rate (Bits per Second)	14
	Maximum Rate (Packets per Second)	14
	Maximum Transmit Rate (Bits per Second)	22
	MLPPP Fragment Size	19



	MLPPP Interleave Mode	19
<b>N</b>	Next Rule	11
<b>P</b>	Priority	25
	Protocol	6
<b>Q</b>	Queuing and Scheduling Algorithm	20
<b>S</b>	Set Remark Type of Service (TOS) Field	15
	Set Type of Service (TOS) Field	13
	Shaping Algorithm	25
	Source Address	7
	Source Mask	7
	Source Port	7, 8
	Specify Port	7
	Specify ToS Set Exceed Action	14
	Specify ToS Set Rate Limitation	13
	Specify Traffic Shaping	21
<b>T</b>	TOS Mask	8
	Transmit Rate (Bits per Second)	24
	Transmit Rate Burst	24
	Type	7
	Type of Service (TOS)	8
<b>U</b>	Upper Queue Threshold (Bytes)	26
<b>W</b>	Weight	24

## Index: L2TP

<b>D</b>	Data Packets Sequence Numbers	10
<b>H</b>	Hello Interval	9
<b>L</b>	LAC	3
	Layer 2 Tunneling Protocol	3
	LNS	3
	Local Hostname	8
	Local IP Address	7
	Local UDP Port (LAC only)	8
<b>M</b>	Maximum Retry Count	10
	Maximum Time Between Retries	10
	Minimum Time Between Retries	10
<b>P</b>	Port usage for LNS mode	5
	Profile Name	7
<b>R</b>	Remote Hostname	9
	Remote IP Address (LAC only)	8
	Remote UDP Port (LAC only)	8
<b>T</b>	Tunnel Password	9
<b>U</b>	UDP port number for LNS mode	5



# Index: Configuration Management

<b>B</b>	boot	3
	Boot configuration file	3
<b>C</b>	Configuration information	3
<b>F</b>	Flash	3
	Flash EEPROM	3
<b>N</b>	Name in Flash	4
	New Name in Flash	4
<b>O</b>	Operation	4, 5
	Operations	3
<b>R</b>	RAM	3
<b>S</b>	Start Operation	5
	State of last operation	4
<b>T</b>	TFTP File Name	4
	TFTP Server	3
	TFTP Server IP Address	4
	Type of last operation	4
<b>U</b>	Unix	3
<b>W</b>	Windows	3

