

## Index: Licenses

<b>A</b>	Available subsystems	4
<b>D</b>	Description	6
<b>E</b>	Ex works state	4
<b>H</b>	Hardware serial number	3
<b>K</b>	Key	3, 6
<b>L</b>	License data	
	Activating extra licenses	5
	License serial number	3
	PIN	3
	Serial number	3
	Software license ID	3
	License serial number	3
<b>M</b>	Mask	6
<b>O</b>	Online licensing	3, 6
<b>P</b>	PIN	3
<b>S</b>	Serial Number	6
	Serial number	3, 6
	Software license ID	3



# Index: System

<b>Numerics</b>	1st Event index	28
<b>A</b>	Action	17
	Activity Monitor	7
<b>B</b>	Basic system data	3
<b>C</b>	Central server	13
	Change System Time	36
	CLID	13
	Client IP address	8
	Client UDP port	8
	Compare value	25
	Condition	24
	Contact	4
	Current System Time	36
<b>D</b>	Description	21, 28
	DownAction	15
<b>E</b>	End time	25
	End value	25
	Event protocol	9
	Eventlist condition	29
	Execute command	29
	External Activity Monitor	7
	External system logging	9
<b>F</b>	Facility	10
	FirstIfIndex	15, 18
<b>G</b>	Group	14

<b>H</b>	Hosts	13
<b>I</b>	Index	21, 28
	Index value	23, 30
	Index variable	23, 30
	Interface	17, 29
	Interfaces	13
	Interval	14
	IP address	14
<b>K</b>	Keepalive Monitoring	13
<b>L</b>	LAN	13
	Last change	31
	Level	10
	Local PPP ID (default)	3
	Location	4
	Log host	9, 10
<b>M</b>	Maximum Number of Acctlog Entries	5
	Maximum number of syslog entries	5
	Message level for the syslog table	5
	Method	11
	Mode	28
	Monitored event	22
<b>N</b>	Name/Address	36
	Next index	21
	Notify	31

<b>P</b>	Password settings	33
	Activity Monitor	33
	admin	33
	Ex works state	33
	HTTP server	33
	read	33
	write	33
	Protocol	37
<b>R</b>	Range	16, 18
<b>S</b>	Set value active	30
	Source IP	15
	Start time	25
	Status	26, 31
	Subsystems	9
	Syslog messages	9
	Syslog output on serial console	4
	System name	3
	System time	35
	Accounting	35
	Automatic	35
	Manual	35
	System Time Offset from GMT	36
<b>T</b>	Table	22, 30
	Time and date	35
	Time Update Interval	36
	Timestamp	10
	Trials	14
	Trigger	17
	Type	8, 10, 21
<b>U</b>	Update interval	8
	Update System Time from ISDN	36

<b>V</b>	Value inactive	30
	Variable	22, 30

## Index: External Systems

<b>A</b>	Access Points	3
	Admin. Password	11
	AP MAC Address	8
	Authentisierungsverhandlung	3
<b>C</b>	Calling Party Number	3
	CLID	3
<b>D</b>	Discovery	3
	discovery	7
<b>G</b>	Gateway Address	11
<b>I</b>	Interface	4, 6, 8
	IP Address	11
	IP Status	9
<b>L</b>	Last Change	10
	Last Run	5
<b>N</b>	Netmask	11
	Node Name	10
<b>O</b>	Operation	4, 7, 9
<b>R</b>	Result	5, 10





## Index: AUX

<b>A</b>	Access Point Name (APN)	7
	Active profile	5
	Additional Init Sequence	7
	Analog connections	3
	Analog/GSM interface	3
<b>G</b>	GSM modem	3
<b>I</b>	Incoming Dispatch Item	6
<b>L</b>	Line speed	5
<b>M</b>	Modem	3
	Modem Escape Character	7
<b>P</b>	Profile	5
	Profile configuration	5
<b>S</b>	Serial port	4
	SIM card uses PIN	6



## Index: ISDN

<b>B</b>	B-channel 1	6
	B-channel 2	6
	Bearer	11
<b>D</b>	D-channel	6
<b>I</b>	IPSec	12
	ISDN Login	9, 11
	ISDN switch type	5, 6
	Item	10
<b>L</b>	leased dte, dce	6
	Leased line	5
<b>M</b>	Mode	11
<b>N</b>	Number	11
<b>P</b>	Point to multipoint	5
	Point to point	5
	PPP (routing)	9, 11
	PPP 64k	11
	PPP DOVB	12
	PPP V.110 (1200...38400)	12
	PPP V.120	12
<b>R</b>	Result of autoconfiguration	4
<b>S</b>	Specify TEI Value	13
	SPID B-channel 1	7
	SPID B-channel 1+2	7
	SPID B-channel 2	7

<b>X</b>	X.31 TEI Service	14
	X.31 TEI Value	13

## Index: Ethernet

<b>A</b>	Advanced settings	8, 15
<b>B</b>	Back Route Verify	8, 9, 10
	Bridging	8
<b>D</b>	DHCP Hostname	7
	DHCP MAC address	7
<b>E</b>	Encapsulation	7, 13
	ETH interfaces	3
<b>F</b>	Fast Ethernet	3
<b>I</b>	IP accounting	8, 9, 10
	IP configuration	6, 13, 14
<b>L</b>	Local IP number	13
	local IP-Number	6
	Local netmask	13
	local Netmask	6
<b>M</b>	MAC address	7, 13, 14
<b>P</b>	Proxy ARP	8, 9, 10
<b>R</b>	RIP	8, 9, 11
	V1	11
	V2	11
	RIP receive	10
	RIP send	10
	Route	8
	Routing	9
	Routing table	8

<b>S</b>	Second local IP number	6, 13
	Second local netmask	7, 13
<b>V</b>	Virtual interfaces	12
	VLAN ID	8, 14
<b>W</b>	WAN partner	9

## Index: ADSL

<b>A</b>	ADSL Configured Mode	6
	ADSL Trained Mode	6
	Annex Type	7
<b>M</b>	Maximum threshold (kb/s)	7
<b>P</b>	Physical connection established	5
<b>T</b>	Transmit shaping	7





## Index: SHDSL

<b>A</b>	Actual Line Speed	5
	Additional Wire Pairs	8
<b>C</b>	Clock Rate Mode	8
<b>E</b>	Equipment Type	6
<b>M</b>	Maximum Rate (kbit/s)	10
	Minimum Rate (kbit/s)	9
<b>O</b>	Operating Mode	6
<b>P</b>	Physical Connection	5
<b>R</b>	Requested Rate (kbit/s)	9
<b>W</b>	Wire Mode	6



# Index: Wireless LAN

<b>Numerics</b>	802.11 b/g mixed	24
<b>A</b>	Accept Address	15
	Access Point	4
	ACL Filter	14
	Active Probing	7
	AdminStatus	10, 15, 21
<b>B</b>	Bridging enable	17
<b>C</b>	Channel	5
<b>D</b>	Default Key	11
<b>E</b>	Ena.	20
	Enter Preshared Key	13
<b>K</b>	Key	12
<b>L</b>	local communication	16
	Local IP	20
	Local IP-Address	22
	local IP-Number	16
	Local Netmask	22
	local Netmask	16
	Location	4
<b>M</b>	MAC Address	20
	Max. Clients	11
	Maximum Bitrate	24
	Mode	21
<b>N</b>	Name is visible	10

	Network Name	10
	Network/Mask	20
	NITRO Burst	25
<b>O</b>	Operation Mode	4
<b>P</b>	Partner IP-Address	22
	Proxy ARP	17
<b>R</b>	Radio band	4
	Remote IP	20
	Remote Netmask	22
	Remote Network	22
	Remote WDS MAC Address	21
<b>S</b>	Second Local IP-Number	16
	Second Local Netmask	16
	Security Mode	11
	SSID	10
<b>T</b>	Timeout (minutes)	25
	TX Power (dBm)	25
<b>U</b>	Usage area	5
<b>V</b>	vss	7
<b>W</b>	wds	19
	WEP	8
	Wireless Mode	24
	WPA	8
	WPA/WPA2 mixed mode	13
	WPA2 preauthentication	13

## Index: WAN Partner

<b>A</b>	Advanced settings	48
	Authentication	11
	Authentication negotiation	11
<b>B</b>	Back Route Verification	49
	Back Route Verify	50
	Bandwidth on Demand (BoD)	22
	Basic IP settings	37
	Bridge	55
	Bridging Mode	55
	<b>C</b>	Callback
Calling Line Identification		7
Channel bundling		16, 18
Closed User Group		36
Compression		6, 7
CUG index		36
<b>D</b>		D-channel queue length
	Default route	37, 40, 41
	Delay after connection failure	16
	Delay after connection failure (sec)	17
	Destination IP address	43, 46
	Destination port	47
	Direction	34
	Dynamic Name Server Negotiation	51, 53
	<b>E</b>	Enable NAT
Encapsulation		5, 6
Encryption		6
Encryption key negotiation		26
Extended interface settings		22
Extended IP routing		44
Extended routing		44

<b>F</b>	Flags	41
<b>G</b>	Gateway IP Address	41
	Gateway IP address	43
	Gear down threshold	25
	Gear up threshold	25
<b>I</b>	Idle for dynamic short hold (%)	17
	IP	37
	IP accounting	49, 50
	IP transit network	39
	ISDN ports to use	34
<b>K</b>	Keepalives	12
<b>L</b>	Layer 1 protocol	16, 17, 21
	Line utilization sample (sec)	24
	Line utilization weighting	24
	Link Quality Monitoring	12
	Local IP address	39
	Local PPP ID	11
	Local PPTP VPN IP Address	41
<b>M</b>	Maximum number of dialup channels	26
	Metric	44, 46
	Mode	24, 27, 46
	More routing	41
<b>N</b>	Netmask	43, 46
	Network	43, 44, 45
	Number	34
<b>P</b>	Partner / Interface	43, 46
	Partner IP address	39
	Partner name	3, 5
	Partner PPP ID	11

	PPP password	11
	PPPoE Ethernet Interface	27
	PPPoE Service Name	27
	PPTP VPN Partner's IP Address	40
	Pro	41
	Protocol	3, 46
	Proxy ARP	49, 51, 52
<b>R</b>	Remote IP address	40
	Remote netmask	40
	RIP	48
	RIP receive	50, 52
	RIP send	50, 52
	Route	37
	Route announce	49, 51
	Route type	43, 45
	Routing settings	37
	RX Key	26
<b>S</b>	Short hold	15
	Source interface	46
	Source IP address	46
	Source mask	46
	Source port	47
	Special interface types	19
	State	3
	Static short hold (sec)	17
<b>T</b>	TOS mask	46
	Total number of channels	18
	TX Key	26
	Type of Service (TOS)	46
<b>U</b>	Use Gateway	40
<b>V</b>	Van Jacobson Header Compression via IP Interface	51 40





## Index: Security

<b>Numerics</b>		
	3des	46
<b>A</b>	Access restrictions	15
	Action	13, 22, 33
	Admin status	8, 29
	Adminstatus	29
	aes128	46
	aes192	46
	aes256	46
	Alias	34, 36
	arc4	46
<b>B</b>	blowfish	46
<b>C</b>	cast128	46
	Category	11
	Chain	16
	Challenge response	45
	Classification	7
	ClientAliveCountMax	43
	ClientAliveInterval	44
	Compression	41
	Connection state	19
<b>D</b>	Day	12
	Deny Silent	24
	Description	18
	Destination	32
	Destination address	19
	Destination mask	19
	Destination port	20
	Dynamic packet filtering	27

<b>E</b>	Expiring date	8
<b>F</b>	Filter	15, 16, 22
	Filter list	9
	Filtered interfaces	8
	First rule	24
	From	12
	Full filtering	30
<b>H</b>	History entries	8
<b>I</b>	ICMP type	34
	Index	18, 22
	Insert behind Rule	22
	Interface	16, 24, 37, 56
	IP access lists	28
	IP address	36, 56
	IP mask	37
	IP range	36
<b>L</b>	Local filter	29
	Logging level	30, 42
	Login Grace Time	43
<b>M</b>	Mask	56
	Max. # of Clients	40
	md5	47
	md5-96	47
	Mode	36
<b>N</b>	NAT	28
	Network access control	15
	Next rule	22
<b>O</b>	Orange filter ticket	8
	Order	22

	Other inactivity timeout	38
<b>P</b>	Password	45
	Port	35
	Port # used for Connections	40
	PPTP inactivity Timeout	38
	Print LastLog	41
	Print Motd	41
	Priority	13
	Protocol	18, 34
	Protocol version	45
	Public key	45
<b>R</b>	Range	35
	Reporting method	25
	ripemd160	47
	Rule chains	21
<b>S</b>	Safety feature	27
	Service	33, 55
	shal	47
	shal-96	47
	SIF	28
	Source	20, 32
	Source address	19
	Source mask	19
	Source port	19, 20
	Specify Port	19
<b>T</b>	TCP inactivity Timeout	38
	TCP Keepalives	43
	Ticket status	8
	To	13
	TOS mask	20
	Type	19
	Type of Service (TOS)	20

<b>U</b>	UDP inactivity Timeout	38
	URL-based content filtering service	7
<b>V</b>	Verify interface	56
	Verify IP address	55
	Verify reverse mapping	41

## Index: PPTP

<b>B</b>	Back Route Verification	34
	Back Route Verify	35
<b>C</b>	Closed User Group	20
	CUG index	20
<b>D</b>	Default route	26
	Delay after connection failure	12
	Destination IP address	28, 30
	Destination port	31, 32
	Direction	18
	Dynamic Name Server Negotiation	36, 37
<b>E</b>	Enable NAT	26
<b>I</b>	IP accounting	34, 35
	ISDN ports to use	19
<b>M</b>	Metric	29, 31
	Mode	31, 32
<b>N</b>	Netmask	29, 30
	Network	28, 30
	Number	18
<b>P</b>	Partner / Interface	29, 31
	Protocol	31
	Proxy Arp	34, 35, 37
<b>R</b>	Remote IP address	26
	Remote netmask	26
	RIP	33
	RIP receive	35, 36
	RIP send	35, 36

	Route announce	34, 35
	Route type	28, 30
	Routing	33
	Routing protocol	33
	Routing table	33
<b>S</b>	Source interface	31
	Source IP address	31
	Source mask	31
	Source port	31, 32
<b>T</b>	TOS mask	31
	Type of Service (TOS)	31
<b>W</b>	WAN partner numbers	17

## Index: IPsec

### Numerics

1 (768-bit MODP)	37, 66
2 (1024-bit MODP)	37, 66
3DES	32, 45, 60, 75
5 (1536-bit MODP)	37, 66

### A

A	6
abort	103
ACTION	14
Action	8, 48, 50, 55
Admin Status	12
Admin status	15
aggressive	38, 67
aggressive-only	38, 68
AH (Authentication Header)	44, 74
Algorithm	80
Authentication method	58
auto/base64/binary	91
Autosave	83
Available encryption and message hash algorithms	32

### B

Block time	59
Blowfish	32, 45, 60, 75

### C

CA certificate	84
CA certificates	39, 59, 68
CA domain	84
CAST	32, 45, 60, 75
CEA	113
Certificate authority certificates	88
Certname	85
clear config	102
Combination of encryption and message hash algorithms for IKE phase 1	31
Cookies size	99
CRL	39, 68

	CRLs	94
<b>D</b>	default	38, 67
	DES	32, 45, 60, 75
	Description	7, 12, 15, 48, 54, 57, 80, 88, 89
	Description (Idx 0)	41
	Description (Idx 1)	71
	dhcp	9, 49, 56
	Direct ISDN call	18
	DN	86
	DNS	86
	Don't Send Cert Chains	98
	Don't Send Cert Req Payl.	98
	Don't Send CRLs	98
	Don't Send Initial Contact	98
	Don't Send Key Hash Payl.	98
	drop	50
	DSA signatures	37, 66
	dump messages	102
	DynDNS service	18
<b>E</b>	Email	86
	Enable IPsec	4
	ESP (Encapsulated Security Payload)	43, 73
<b>F</b>	Filename	85
	First active rule	6
	Flags	88
	force Comp	45, 75
<b>G</b>	Group	58
<b>H</b>	Heartbeats	42, 58, 72
	host	8, 49, 55
<b>I</b>	ID Protect Mode	21
	id_protect	38, 67



id-protect-only	38, 67
Ignore Cert Req Payloads	97
IKE (Phase 1) defaults	4
Import a certificate/CRL using	90
In	113
Incoming ISDN number	19
Interface IP Settings	17
Interoperability flags	97
IP	86
IP address transfer	21
IPComP	44, 74
IPsec (Phase 2) defaults	4
ISDN callback	19
<b>K</b> Key size (bits)	81
Key to enroll	82
<b>L</b> Lifetime	41
Lifetime Policy	35, 41, 58, 64, 71
Local	112
Type	7, 48, 54
Local Address	12
Local address	5
Local certificate	59
Local ID	59, 111
Local/Remote	
Type	48, 55
LPort	112
<b>M</b> M/R	6
Max. Symmetric Key Length	99
MD5	45, 75
MD5 (Message Digest #5)	32, 61
Messages	13
Method	83
Method of operation	21
Mode	58

	Modifying IKE and IPSec settings	26
	MODP	36
<b>N</b>	Name	91
	Nat-Traversal	31, 59
	net	8, 49, 55
	no Comp	44, 74
	NONE	86
	NULL	45, 46, 75, 76
<b>O</b>	Oper Status	12
	Out	113
	Outgoing ISDN number	19
	Own certificates	88
	own/peer	9, 49, 56
<b>P</b>	Packets in	109
	pass	50
	Password	83
	peer	9, 50
	Peer address	15
	Peer certificates	88
	Peer IDs	16
	Peers blocked	108
	Peers dormant	108
	Peers up	108
	Phase 1	
	Authentication method	37, 66
	Group	36, 65
	Lifetime Policy	62
	Local certificate	39, 68
	Local ID	39, 68
	Mode	38, 67
	NAT Traversal	39
	Proposal	31, 60

Phase 2	
Lifetime	46, 76
Proposal	43, 73
PKCS#12 support	91
Please enter certificate data	91
Port	6
Preshared key	16
Preshared keys	37, 66
Profile	48
Propagate PMTU	43, 73
Proposal	6, 58, 71
protect	51
Proto	6
Protocol	7, 48, 54
Pto	112
<b>R</b> RA-Certificate (Encrypt)	87
RA-Certificate (Sign)	87
RADIUS authentication	99
range	9, 49, 56
Registration Authority Certificates	86
Remote	112
Type	8, 48, 54
Remote Address	12
Remote address	6
Remote ID	110
Remote IP	110
Request cert	81
RID	86
Rijndael	32, 45, 60, 75
RipeMD 160	33, 61
RPort	112
RSA encryption	37, 67
RSA Public Exponent	81
RSA signatures	37, 66
<b>S</b> SAs Phase 1	13

SAs phase 1	108
SAs Phase 2	13
SAs phase 2	109
Serial no.	88
Server	85, 91
Setup Tool Wizard	3
SHA1	45, 75
SHA1 (Secure Hash Algorithm #1)	33, 61
Signing Algorithm to Use	85
skip	103
start (wizard)	103
Start of IKE phase 1 negotiation	21
State of last enrollment	84
Step 1 (NAT settings)	103
Step 2 (creation of proposals)	103
Step 3 (define authentication method)	103
Step 4 (request certificate)	104
Step 5 (own certificate)	104
Step 6 (CA certificate)	104
Step 7 (CRL server / peer certificate)	104
Step 8 (peer)	105
Step 9 (peer traffic / peer interface)	105
Subject Alternative Names	85
Subject Alternative Names – Type	85
Subject Alternative Names – Value	85
Subject Alternative Names (optional)	84
Subject name	84, 88
Sync SAs With Local Ifc	99
<b>T</b> TARSEH	110, 111
The IPsec Wizard step by step	103
Tiger 192	33, 61
Traffic List Settings	17
Trust ICMP Messages	98
Twofish	32, 45, 60, 75
Type	86
Type of certificate	89, 90

<b>U</b>	URI	86
	Use PFS	41, 46, 71, 76
	Use Zero Cookies	99
<b>V</b>	View proposals	33, 43, 62
	Virtual interface	17
<b>W</b>	What to do?	102



## Index: IP

<b>A</b>	Action	40
	Add Routing Entry	5
	ADDEXT	8
	Address	72, 75, 104
	Admin Status	100
	Administrative Status	64
	Advertise Matching	105
	Alias Name (Description)	27
	Alive Check (if inactive)	59
	Alive Test Period (seconds, 0=disabled)	47
	Area ID	100, 103
	Area Range	104
	Authentication Key	101
	Authentication Type	101
<b>B</b>	Bandwidth Management	21
	Bandwidth on Demand	21
	Block Time (seconds)	63
	BOD	21
<b>C</b>	Cache Hitrate (%)	78
	Cache Hits	78
	Chain	35
	Client / Server	53
	Client Identifier	46
	Connection State	37
	Control all TCP Services	26
<b>D</b>	Default Domain	72
	Default Domains	73
	Default Interface	70
	Default Route distribution	88
	Description	28, 36
	Destination Address	37

Destination IP Address	6
Destination Mask	37
Destination Port	9, 10, 38
DHCP Assignment	70
Dialout	59
Direction	40, 93
Distribution	93
Distribution Fraction (in percent)	30
Distribution Mode	29
Distribution Policy	29, 30
Distribution Ratio	29
DNS	11, 67
DNS Proxy	11
DNS Requests	78
Domain Name	11
Domain Name Server	11, 67
Dynamic Cache	71
DynDNS Registration	79
<b>E</b> Edit Routing Entry	5
Encryption (recommended)	63
Export indirect static routes	101
Extended Routing	8
External Address	17
External Mask	17
External Port	18
<b>F</b> Filter	35, 40
First Rule	42
Flags	5
Forwarded Domains	71
Forwarded Requests	78
<b>G</b> Garbage Collection Timer	90
Gateway	47
Gateway IP Address	7
Generate Default Route for the AS	97



<b>H</b>	Hold down timer	90
	Host Name	80
	HTTP TCP Port	12
<b>I</b>	Ignore	7
	Import external routes	103
	Index	36, 39
	Insert behind Rule	39
	Interface	24, 35, 42, 45, 74, 80, 92
	Interface 1 - 3	30
	Interface Group ID	29
	Internal Address	18
	Internal Mask	18
	Internal Port	19
	Invalid DNS Packets	78
	IP Address	43, 46, 56, 92
	IP Address Pool LAN (DHCP)	45
	IP Address Pool WAN (PPP)	43
	IPCP Assignment	70
<b>L</b>	LAN	7, 34
	Lease Time (Minutes)	46
	Load Balancing	21
	Local	8
	Local Nameservers	73
	Login Authentication/Authorization	64
<b>M</b>	MAC Address	46
	Mask	104
	Maximum Number of DNS Records	76
	Maximum TCP Download Rate (kbits/s)	25
	Maximum TTL for Neg Cache Entries	77
	Maximum TTL for Pos Cache Entries	77
	Metric	7, 101
	Metric Determination	100, 102
	Metric1 offset on interface dormant	94

	Metric1 offset on interface up	93
	Minimum Wait	83
	Mode	9, 10
	MX	81
<b>N</b>	Name	72, 73, 75, 82
	Name Resolution	67
	Negative Cache	69
	NetBT Node Type	47
	Netmask	6, 92
	Network	6
	Network Address Translation	14
	Next Rule	40
	Number of Channels	40
	Number of Consecutive Addresses	43, 46
<b>O</b>	Optimize Download Rate via TCP ACK prioritisation	24
	OSPF	85, 97
	Overwrite Global Nameservers	70
<b>P</b>	Partner / Interface	7
	Password	56, 80
	Path	82
	Permission	81
	Poisoned Reverse	88
	Policy	57, 62
	Pool ID	43
	Port	57, 82
	Positive Cache	69
	PPP Authentication	64
	PPTP Passthrough	14
	Primary BOOTP Relay Server	12
	Primary Domain Name Server	11
	Primary WINS	11
	Priority	56, 61, 93
	Propagate Routes on discard/refuse interfaces	98
	Protocol	9, 16, 36, 56, 83

Provider	81
<b>R</b> RADIUS packets	54
Received DNS Packets	78
Ref	75
Refuse	7
Remote Address	17
Remote CAPI Server TCP Port	12
Remote Mask	17
Remote Port	17
Remote TRACE Server TCP Port	12
Resp	75
Response	72
Retransmission timer	91
Retries	58
RFC 2091 variable timer	89
RFC 2453 variable timer	88
RIP	85
RIP UDP Port	12
Route Timeout	90
Route Type	6
Routing Protocols	85
Rule	35
<b>S</b> Secondary BOOTP Relay Server	12
Secondary Domain Name Server	11
Secondary WINS	11
Server	82
Server Failures	78
Server's IP Address or Hostname	61
Service	16
Silent Deny	14
SNMP	49
SNMP listen UDP port	50
SNMP trap broadcasting	51
SNMP trap community	51
SNMP trap UDP port	51

	SNMP versions	50
	Source Address	37
	Source Interface	9
	Source IP Address	9
	Source Mask	9, 37
	Source Port	9, 10, 37
	Specify Port	37
	State	58
	Static Hosts	70
	Status	27
	Successfully Answered Queries	78
<b>T</b>	TACACS+ Accounting	64
	TACACS+ Key (Secret)	62
	TACACS+ Single-Connection	65
	TCP Port	62
	TCP Service Port	27
	TDRC Mode	25
	Timeout (ms)	57
	Timeout (seconds)	63
	TOS Mask	9, 38
	TTL	72, 74, 75
	Type	37, 46
	Type of Service (TOS)	9, 38
<b>U</b>	Unique Source IP Address	12
	Update Timer	90
	User	80
<b>V</b>	Validate	58
<b>W</b>	WAN with transit network	7, 34
	WAN without transit network	7, 34
	Wildcard	81
	WINS	11

## Index: PPP

<b>A</b>	Authentication Negotiation	3
	Authentication Protocol	4
<b>C</b>	Calling party number	3
	CHAP	4
	CLID	3, 5
<b>L</b>	Link Quality Monitoring	5
<b>M</b>	MS-CHAP	4
<b>P</b>	PAP	4
	PPP Link Quality Monitoring	5
	PPPoE Ethernet Interface	6
<b>R</b>	RADIUS	5
	Radius Server Authentication	5



# Index: BRRP

<b>A</b>	Advertisement Interface	3
	Advertisement Interval	3
	Advertisement Interval Errors	3
	Advertisements Received	3
	Authentication Errors	3
	Authentication Key	5
	Authentication Type	5
	Authentication Type Mismatch	3
<b>B</b>	Backup	9
	Become Master	3
	BRRP states	7
<b>C</b>	Checksum Errors	3
<b>I</b>	Initialize	8
	Invalid Authentication Type	3
	Invalid Type Packets Received	3
	IP Address Owner	3
	IP TTL Errors	3
<b>M</b>	MAC address	4, 3
	Master	10
	Master Action	4
	Master Down Interval	4
	Master Interface	5
	Master Interface Protocol	3
	Master IP-Address	3
<b>P</b>	Packet Length Errors	3
	Pre-empt Mode	4
	Primary IP Address	3
	Priority	2

<b>R</b>	Redundant network environment	1
	RFC 2338	1
	Router redundancy procedure	1
<b>S</b>	Slave Admin Action	6
	Slave Interface	7
	Slave Interface Protocol	5
<b>T</b>	Task ID	2
<b>V</b>	Version Errors	3
	Virtual Interface	3
	Virtual Router	1, 3
	Virtual Router Backup	3
	Virtual Router ID	4, 7, 2
	Virtual Router Master	3
	Virtual Router State	2
	VRRP Advertisement	3
	VRRP Router	2
<b>W</b>	Watchdog Daemon	4, 1



## Index: CREDITS

<b>C</b>	Charges	3
	Credits Based Accounting System	3
<b>I</b>	ISDN Credits	5
	isdnlogin	5
<b>M</b>	Maximum Charge	7
	Maximum Number of Current Incoming Connections	8
	Maximum Number of Current Outgoing Connections	8
	Maximum Number of Incoming Connections	7
	Maximum Number of Outgoing Connections	7, 10
	Maximum Time for Incoming Connections (sec)	7
	Maximum Time for Outgoing Connections (sec)	7, 10
	Measure Time (sec)	6, 9
<b>P</b>	ppp	5
	PPPoE	9
<b>S</b>	Surveillance	6, 9
	Syslog messages	3
<b>X</b>	xDSL	9



## Index: CAPI

<b>C</b>	CAPI	4
<b>N</b>	Name	4
<b>P</b>	Password	4



## Index: ATM

<b>A</b>	ATM Interface	6, 17, 21, 26, 34
	ATM Service Category	35, 36
<b>B</b>	Back Route Verify	12
	Bridging	11
<b>C</b>	CC End-to-End	30
	CC Segment	31
	Client Type	18
<b>D</b>	Description	6, 17, 21
	DHCP Hostname	9, 23
	DHCP MAC address	9, 23
	Direction	30, 31
<b>E</b>	Encapsulation	7, 9, 15, 18, 22
<b>I</b>	IP accounting	12
	IP configuration	8, 14, 15, 23
<b>L</b>	Local IP number	14
	local IP-Number	8, 23
	Local netmask	14
	local Netmask	8, 23
	Loopback End-to-End	29
	Loopback Segment enable	29
<b>M</b>	MAC Address	14
	MAC address	10, 15
	Maximum Burst Size (MBS) in bytes	36
<b>O</b>	OAM flow level	26

<b>P</b>	Peak Cell Rate (PCR) in bits per second	36
	Pending Requests (max)	29, 30
	Proxy ARP	12
<b>R</b>	RIP receive	12
	RIP send	12
<b>S</b>	Second local IP number	9, 14
	Second local netmask	9, 14
	Send Interval (sec)	29
	Sustained Cell Rate (SCR) in bits per second	36
<b>V</b>	VCI	28, 34
	Virtual channel connection (VCC)	27, 34
	Virtual channel identifier (VCI)	6, 18, 22
	Virtual path connection (VPC)	28
	Virtual path identifier (VPI)	6, 18, 22
	VLAN ID	10, 15
	VPI	28, 34

## Index: QoS

<b>A</b>	Action	11
<b>B</b>	Bound Transmit Rate (Shaping)	24
<b>C</b>	Class	23
	Class ID	12, 23
	Class Type	12
	Classification of IP Packets	9
	Congestion Avoidance Algorithm	25
	Connection State	7
<b>D</b>	Description	6
	Destination Address	7
	Destination Mask	7
	Destination Port	8
	Direction	10
	Dropping Algorithm	26
<b>F</b>	Filter	10
<b>I</b>	Index	6, 10
	Insert behind Rule	11
	Interface	18
	IP QoS Classification via	18
<b>L</b>	Lower Queue Threshold (Bytes)	26
<b>M</b>	Maximum Burst Size (Number of Bits)	14
	Maximum Burst Size (Number of Packets)	14
	Maximum Rate (Bits per Second)	14
	Maximum Rate (Packets per Second)	14
	Maximum Transmit Rate (Bits per Second)	22
	MLPPP Fragment Size	19

	MLPPP Interleave Mode	19
<b>N</b>	Next Rule	11
<b>P</b>	Priority	25
	Protocol	6
<b>Q</b>	Queuing and Scheduling Algorithm	20
<b>S</b>	Set Remark Type of Service (TOS) Field	15
	Set Type of Service (TOS) Field	13
	Shaping Algorithm	25
	Source Address	7
	Source Mask	7
	Source Port	7, 8
	Specify Port	7
	Specify ToS Set Exceed Action	14
	Specify ToS Set Rate Limitation	13
	Specify Traffic Shaping	21
<b>T</b>	TOS Mask	8
	Transmit Rate (Bits per Second)	24
	Transmit Rate Burst	24
	Type	7
	Type of Service (TOS)	8
<b>U</b>	Upper Queue Threshold (Bytes)	26
<b>W</b>	Weight	24



## Index: GRE

<b>G</b>	Generic Routing Encapsulation	3
	GRE Local IP Address	4
	GRE Partner's IP Address	4
	GRE V.0	3
	GRE V.1	3
<b>K</b>	Key Used	5
<b>M</b>	Mtu	5
<b>N</b>	Name	4
<b>P</b>	Partner's LAN IP Address	4
	Partner's LAN IP Mask	4
<b>V</b>	Value	5
	Virtual Interface	3



## Index: L2TP

<b>D</b>	Data Packets Sequence Numbers	12
<b>H</b>	Hello Interval	12
<b>L</b>	LAC	3, 8
	Layer 2 Tunneling Protocol	3
	LNS	3, 5, 8
	Local Hostname	9
	Local IP Address	9
	Local UDP Port (LAC only)	9
<b>M</b>	Maximum Retry Count	13
	Maximum Time Between Retries	12
	Minimum Time Between Retries	12
<b>P</b>	Port usage for LNS mode	5
	PPP over L2TP (LAC mode)	3
	PPP over L2TP (LNS mode)	3
	Profile Name	8
<b>R</b>	Remote Hostname	11
	Remote IP Address - backup (LAC only)	10
	Remote IP Address (LAC only)	10
	Remote IP addresses through Radius (LAC only)	10
	Remote UDP Port (LAC only)	10
<b>S</b>	SCCRPs	9
	SCCRQs	9
<b>T</b>	Tunnel Password	11
	tunnel profiles	7
<b>U</b>	UDP port number for LNS mode	5



# Index: Configuration Management

<b>B</b>	boot	3
	Boot configuration file	3
<b>C</b>	Configuration information	3
<b>F</b>	Flash	3
	Flash EEPROM	3
<b>N</b>	Name in Flash	4
	New Name in Flash	4
<b>O</b>	Operation	4, 5
	Operations	3
<b>R</b>	RAM	3
<b>S</b>	Start Operation	5
	State of last operation	4
<b>T</b>	TFTP File Name	4
	TFTP Server	3
	TFTP Server IP Address	4
	Type of last operation	4
<b>U</b>	Unix	3
<b>W</b>	Windows	3



# Index: Monitoring and Debugging

<b>A</b>	Active Connections	14
	Admin Status	36
	Adminstatus	19
	ADSL	4
	Advertisement Interval Errors	3
	Advertisements Received	3
	Age	39
	Area	38
	ATM Interface	41
	ATM/OAM	4
	Authentication Errors	3
	Authentication Type Mismatch	3
<b>B</b>	Backup Designated Router (BDR)	36
	Become Master	3
	BRRP	4
<b>C</b>	CEA	33
	Charge	10
	Checksum Errors	3
	Class	8
	Compress	22
	Contents	21
	Corrected blocks	51
	CRC anomalies	55
	Current attenuation	50
	Current loop attenuation	55
	Current noise margin	50
	Current output power	50
	Current SNR margin	55
	Current status	50, 54, 55
<b>D</b>	Designated Router (DR)	36
	Dropped Octets	11

	Dropped Packets	11
	Duration	14
<b>E</b>	Email Alert	19
	End to end	45, 48
	Errored seconds (ES)	50, 55
	EXTENDED	14
<b>F</b>	Framing (LOF)	50
<b>I</b>	In	33
	InOctets	10
	InPkts	10
	Interface	35, 37, 5
	Interface Name	13
	Interfaces	3, 13, 35
	Invalid Authentication Type	3
	Invalid Type Packets Received	3
	IP QoS	4
	IP TTL Errors	3
	IPSec	4
	ISDN Credits	3, 9
	ISDN Monitor	3, 5
<b>L</b>	Last Error	20
	Level	21
	Link State ID	38
	Local	32
	Local ID	31
	Loss of sync word (LOSW) seconds	55
	LPort	32
	LSDB	38
<b>M</b>	max. Mails/min	20
	Maximum Transmit Rate	6
	Messages	3, 17, 22



<b>N</b>	Neighbor	37
	Nominal Transmit Rate	5
	Number of Current Connections	10
	Number of Current Incoming Connections	10
	Number of Current Outgoing Connections	10
	Number of Incoming Connections	9
	Number of Outgoing Connections	10, 11
<b>O</b>	OctetsDropped	10
	Octs	9
	Operation	14
	Operational Status	13, 41, 44, 47, 5
	Originator	20
	OSPF	35
	Out	33
	OutOctets	10
	OutPkts	10
<b>P</b>	Packet Length Errors	3
	Packets in	29
	Peers blocked	28
	Peers dormant	28
	Peers up	28
	Pkts	9
	PktsDropped	10
	Power (LRP)	50
	Pto	32
<b>Q</b>	Queued Octets	11
	Queued Packets	11
<b>R</b>	Received blocks	50, 55
	Received Errors	14, 42
	Received Octets	14, 41, 6
	Received Packets	13, 6
	Receiver	21

Remote	32
Remote ID	30
Remote IP	30
Retx Queue	37
Router ID	37, 39
RPort	32
RX Rate (Kb/s)	41
<b>S</b>	
SAs phase 1	28
SAs phase 2	29
Segment	45, 48
Select subsystems	22
Sequence	39
Severely errored seconds (SES)	55
SHDSL	4
SHDSL interface	53
Signal (LOS)	50
SMTP Server	20
SSHD	4
START OPERATION	14
State	36, 37, 38
<b>T</b>	
TARSEH	30, 31
TCP/IP	4, 25
Time for Outgoing Connections (sec)	11
Time of Incoming Connections	10
Time of Outgoing Connections	10
Time till end of measure interval (sec)	9, 11
Timeout	21
TOS	10
Transmit Discards	42
Transmit Errors	14, 42
Transmit Octets	14, 42, 6, 11
Transmit Packets	14, 6, 11
Transmitted blocks	50, 56
TX Rate (Kb/s)	42
Tx rate (Kb/s)	50

	Type	38
<b>U</b>	Unavailable seconds (UAS)	55
	Uncorrect blocks	51
<b>V</b>	Vendor ID	49
	Version Errors	3
	Version Number	49
	Virtual channel connection (VCC)	46
	Virtual path connection (VPC)	43
	Virtual Router ID	2
	Virtual Router State	2
<b>X</b>	xDSL Credits	3, 11

