

Index: Licenses

A	Available subsystems	4
D	Description	6
E	Ex works state	4
H	Hardware serial number	3
K	Key	3, 6
L	License data	
	Activating extra licenses	5
	License serial number	3
	PIN	3
	Serial number	3
	Software license ID	3
	License serial number	3
M	Mask	6
O	Online licensing	3, 6
P	PIN	3
S	Serial Number	6
	Serial number	3, 6
	Software license ID	3

Index: System

Numerics

1st Event index	28
A Action	17
Activity Monitor	7
B Basic system data	3
C Central server	13
Change System Time	36
CLID	13
Client IP address	8
Client UDP port	8
Compare value	25
Condition	24
Contact	4
Current System Time	36
D Description	21, 28
DownAction	15
E End time	25
End value	25
Event protocol	9
Eventlist condition	29
Execute command	29
External Activity Monitor	7
External system logging	9
F Facility	10
FirstIfIndex	15, 18
G Group	14

H	Hosts	13
I	Index	21, 28
	Index value	23, 30
	Index variable	23, 30
	Interface	17, 29
	Interfaces	13
	Interval	14
	IP address	14
K	Keepalive Monitoring	13
L	LAN	13
	Last change	31
	Level	10
	Local PPP ID (default)	3
	Location	4
	Log host	9, 10
M	Maximum Number of Acctlog Entries	5
	Maximum number of syslog entries	5
	Message level for the syslog table	5
	Method	11
	Mode	28
	Monitored event	22
N	Name/Address	36
	Next index	21
	Notify	31

P	Password settings	33
	Activity Monitor	33
	admin	33
	Ex works state	33
	HTTP server	33
	read	33
	write	33
	Protocol	37
R	Range	16, 18
S	Set value active	30
	Source IP	15
	Start time	25
	Status	26, 31
	Subsystems	9
	Syslog messages	9
	Syslog output on serial console	4
	System name	3
	System time	35
	Accounting	35
	Automatic	35
	Manual	35
	System Time Offset from GMT	36
T	Table	22, 30
	Time and date	35
	Time Update Interval	36
	Timestamp	10
	Trials	14
	Trigger	17
	Type	8, 10, 21
U	Update interval	8
	Update System Time from ISDN	36

V Value inactive
Variable

30
22, 30

Index: External Systems

A	Access Points	3
	Admin. Password	11
	AP MAC Address	8
	Authentisierungsverhandlung	3
C	Calling Party Number	3
	CLID	3
D	Discovery	3
	discovery	7
G	Gateway Address	11
I	Interface	4, 6, 8
	IP Address	10
	IP Status	9
L	Last Change	10
	Last Run	5
N	Netmask	11
	Node Name	10
O	Operation	4, 7, 9
R	Result	5, 10

Index: AUX

A	Access Point Name (APN)	7
	Active profile	5
	Additional Init Sequence	7
	Analog connections	3
	Analog/GSM interface	3
G	GSM modem	3
I	Incoming Dispatch Item	6
L	Line speed	5
M	Modem	3
	Modem Escape Character	7
P	Profile	5
	Profile configuration	5
S	Serial port	4
	SIM card uses PIN	6

Index: Ethernet

A	Advanced settings	8, 14
B	Back Route Verify	8, 9, 10
	Bridging	8
D	DHCP Hostname	7
	DHCP MAC address	7
E	Encapsulation	7, 13
	ETH interfaces	3
F	Fast Ethernet	3
I	IP accounting	8, 9, 10
	IP configuration	6, 12, 14
L	Local IP-Number	6, 12
	Local Netmask	6, 12
M	MAC address	7, 12, 13
P	Proxy ARP	8, 9, 10
R	RIP	8, 9, 11
	V1	11
	V2	11
	RIP receive	10
	RIP send	10
	Route	8
	Routing	9
	Routing table	8
S	Second local IP number	6, 12

	Second local netmask	7, 12
V	Virtual interfaces	11
	VLAN ID	8, 13
W	WAN partner	9

Index: ISDN

B	B-channel 1	6
	B-channel 2	6
	Bearer	11
D	D-channel	6
I	IPSec	12
	ISDN Login	9, 11
	ISDN switch type	5, 6
	Item	10
L	leased dte, dce	6
	Leased line	5
M	Mode	11
N	Number	11
P	Point to multipoint	5
	Point to point	5
	PPP (routing)	9, 11
	PPP 64k	11
	PPP DOVB	12
	PPP V.110 (1200...38400)	12
	PPP V.120	12
R	Result of autoconfiguration	4
S	Specify TEI Value	13
	SPID B-channel 1	7
	SPID B-channel 1+2	7
	SPID B-channel 2	7

X	X.31 TEI Service	14
	X.31 TEI Value	13

Index: ADSL

A	ADSL Configured Mode	4
	ADSL Trained Mode	4
	Annex Type	5
M	Maximum threshold (kb/s)	5
P	Physical connection established	3
T	Transmit shaping	5

Index: SHDSL

A	Actual Line Speed	6
	Additional Wire Pairs	9
C	Clock Rate Mode	9
E	Equipment Type	6
M	Maximum Rate (kbit/s)	10
	Minimum Rate (kbit/s)	10
O	Operating Mode	6
P	Physical Connection	5
R	Requested Rate (kbit/s)	11
W	Wire Mode	7

Index: Wireless LAN

Numerics	802.11 b/g mixed	24
A	Accept Address	15
	Access Point	4
	ACL Filter	14
	Active Probing	7
	AdminStatus	10, 15, 21
B	Bridging enable	17
C	Channel	5
D	Default Key	11
E	Ena.	20
	Enter Preshared Key	13
K	Key	12
L	local communication	16
	Local IP	20
	Local IP-Address	22
	local IP-Number	16
	Local Netmask	22
	local Netmask	16
	Location	4
M	MAC Address	20
	Max. Clients	11
	Maximum Bitrate	24
	Mode	21
N	Name is visible	10

	Network Name	10
	Network/Mask	20
	NITRO Burst	25
O	Operation Mode	4
P	Partner IP-Address	22
	Proxy ARP	17
R	Radio band	5
	Remote IP	20
	Remote Netmask	22
	Remote Network	22
	Remote WDS MAC Address	22
S	Second Local IP-Number	17
	Second Local Netmask	17
	Security Mode	11
	SSID	10
T	Timeout (minutes)	25
	TX Power (dBm)	25
U	Usage area	5
V	vss	7
W	wds	19
	WEP	8
	Wireless Mode	24
	WPA	8
	WPA/WPA2 mixed mode	13
	WPA2 preauthentication	13

Index: WAN Partner

A	Advanced settings	50
	Authentication	11
	Authentication negotiation	11
B	Back Route Verification	51
	Back Route Verify	52
	Bandwidth on Demand (BoD)	23
	Basic IP settings	39
	Bridge	57
	Bridging Mode	57
	C	Callback
Calling Line Identification		7
Channel bundling		16, 18
Closed User Group		38
Compression		6, 7
CUG index		38
D		D-channel queue length
	Default route	39, 42, 43
	Delay after connection failure	16
	Delay after connection failure (sec)	17
	Destination IP address	45, 48
	Destination port	49
	Direction	36
	Dynamic Name Server Negotiation	53, 55
	E	Enable NAT
Encapsulation		5, 6
Encryption		6
Encryption key negotiation		27
Extended interface settings		23
Extended IP routing		46
Extended routing		46

F	Flags	43
G	Gateway IP Address	43
	Gateway IP address	45
	Gear down threshold	26
	Gear up threshold	26
	GPRS/UMTS Interface	18
I	Idle for dynamic short hold (%)	17
	IP	39
	IP accounting	51, 52
	IP transit network	41
	ISDN ports to use	36
K	Keepalives	12
L	Layer 1 protocol	16, 17, 21
	Line utilization sample (sec)	25
	Line utilization weighting	25
	Link Quality Monitoring	12
	Local IP address	41
	Local PPP ID	11
	Local PPTP VPN IP Address	43
M	Maximum number of dialup channels	27
	Metric	46, 48
	Mode	25, 28, 48
	More routing	43
N	Netmask	45, 48
	Network	45, 46, 47
	Number	36
P	Partner / Interface	45, 48
	Partner IP address	41
	Partner name	3, 5

Partner PPP ID	11
PPP password	11
PPPoE Ethernet Interface	28
PPPoE Service Name	28
PPTP VPN Partner's IP Address	42
Pro	43
Protocol	3, 48
Proxy ARP	51, 53, 54
R Remote IP address	42
Remote netmask	42
RIP	50
RIP receive	52, 54
RIP send	52, 54
Route	39
Route announce	51, 53
Route type	45, 47
Routing settings	39
RX Key	27
S Short hold	15
Source interface	48
Source IP address	48
Source mask	48
Source port	49
Special interface types	19
State	3
Static short hold (sec)	17
T TOS mask	48
Total number of channels	18
TX Key	27
Type of Service (TOS)	48
U UMTS Interface	18
Use Gateway	42

V	Van Jacobson Header Compression via IP Interface	53 42
W	WAN partner numbers	35

Index: Security

Numerics

	3des	44
A	Access restrictions	13
	Action	11, 20, 31
	Admin status	6, 27
	Adminstatus	27
	aes128	44
	aes192	44
	aes256	44
	Alias	32, 34
	arc4	44
B	blowfish	44
C	cast128	44
	Category	9
	Chain	14
	Challenge response	43
	Classification	5
	ClientAliveCountMax	41
	ClientAliveInterval	42
	Compression	39
	Connection state	17
D	Day	10
	Deny Silent	22
	Description	16
	Destination	30
	Destination address	17
	Destination mask	17
	Destination port	18
	Dynamic packet filtering	25

E	Expiring date	6
F	Filter	13, 14, 20
	Filter list	8
	Filtered interfaces	6
	First rule	22
	From	10
	Full filtering	28
H	History entries	7
I	ICMP type	32
	Index	16, 20
	Insert behind Rule	20
	Interface	14, 22, 35, 52
	IP access lists	26
	IP address	34, 52
	IP mask	35
	IP range	34
L	Local filter	27
	Logging level	28, 40
	Login Grace Time	41
M	Mask	52
	Max. # of Clients	38
	md5	45
	md5-96	45
	Mode	34
N	NAT	26
	Network access control	13
	Next rule	20
O	Orange filter ticket	6
	Order	20

	Other inactivity timeout	36
P	Password	43
	Port	33
	Port # used for Connections	38
	PPTP inactivity Timeout	36
	Print LastLog	39
	Print Motd	39
	Priority	11
	Protocol	16, 32
	Protocol version	43
	Public key	43
R	Range	33
	Reporting method	23
	ripemd160	45
	Rule chains	19
S	Safety feature	25
	Service	31, 51
	shal	45
	shal-96	45
	SIF	26
	Source	18, 30
	Source address	17
	Source mask	17
	Source port	17, 18
	Specify Port	17
T	TCP inactivity Timeout	36
	TCP Keepalives	41
	Ticket status	6
	To	11
	TOS mask	18
	Type	17
	Type of Service (TOS)	18

U	UDP inactivity Timeout	36
	URL-based content filtering service	5
V	Verify interface	52
	Verify IP address	51
	Verify reverse mapping	39

Index: PPTP

B	Back Route Verification	34
	Back Route Verify	35
C	Closed User Group	20
	CUG index	20
D	Default route	26
	Delay after connection failure	12
	Destination IP address	28, 30
	Destination port	31, 32
	Direction	18
	Dynamic Name Server Negotiation	36, 37
E	Enable NAT	26
I	IP accounting	34, 35
	ISDN ports to use	19
M	Metric	29, 31
	Mode	31, 32
N	Netmask	29, 30
	Network	28, 30
	Number	18
P	Partner / Interface	29, 31
	Protocol	31
	Proxy Arp	34, 35, 37
R	Remote IP address	26
	Remote netmask	26
	RIP	33
	RIP receive	35, 36
	RIP send	35, 36

	Route announce	34, 35
	Route type	28, 30
	Routing	33
	Routing protocol	33
	Routing table	33
S	Source interface	31
	Source IP address	31
	Source mask	31
	Source port	31, 32
T	TOS mask	31
	Type of Service (TOS)	31
W	WAN partner numbers	17

Index: IPsec

Numerics

1 (768-bit MODP)	37, 66
2 (1024-bit MODP)	37, 66
3DES	32, 45, 60, 75
5 (1536-bit MODP)	37, 66

A

A	6
abort	103
ACTION	14
Action	8, 48, 50, 55
Admin Status	12
Admin status	15
aggressive	38, 67
aggressive-only	38, 68
AH (Authentication Header)	44, 74
Algorithm	80
Authentication method	58
auto/base64/binary	91
Autosave	83
Available encryption and message hash algorithms	32

B

Block time	59
Blowfish	32, 45, 60, 75

C

CA certificate	84
CA certificates	39, 59, 68
CA domain	84
CAST	32, 45, 60, 75
CEA	113
Certificate authority certificates	88
Certname	85
clear config	102
Combination of encryption and message hash algorithms for IKE phase 1	31
Cookies size	99
CRL	39, 68

	CRLs	94
D	default	38, 67
	DES	32, 45, 60, 75
	Description	7, 12, 15, 48, 54, 57, 80, 88, 89
	Description (Idx 0)	41
	Description (Idx 1)	71
	dhcp	9, 49, 56
	Direct ISDN call	18
	DN	86
	DNS	86
	Don't Send Cert Chains	98
	Don't Send Cert Req Payl.	98
	Don't Send CRLs	98
	Don't Send Initial Contact	98
	Don't Send Key Hash Payl.	98
	drop	50
	DSA signatures	37, 66
	dump messages	102
	DynDNS service	18
E	Email	86
	Enable IPsec	4
	ESP (Encapsulated Security Payload)	43, 73
F	Filename	85
	First active rule	6
	Flags	88
	force Comp	45, 75
G	Group	58
H	Heartbeats	42, 58, 72
	host	8, 49, 55
I	ID Protect Mode	21
	id_protect	38, 67

id-protect-only	38, 67
Ignore Cert Req Payloads	97
IKE (Phase 1) defaults	4
Import a certificate/CRL using	90
In	113
Incoming ISDN number	19
Interface IP Settings	17
Interoperability flags	97
IP	86
IP address transfer	21
IPComP	44, 74
IPsec (Phase 2) defaults	4
ISDN callback	19
K Key size (bits)	81
Key to enroll	82
L Lifetime	41
Lifetime Policy	35, 41, 58, 64, 71
Local	112
Type	7, 48, 54
Local Address	12
Local address	5
Local certificate	59
Local ID	59, 111
Local/Remote	
Type	48, 55
LPort	112
M M/R	6
Max. Symmetric Key Length	99
MD5	45, 75
MD5 (Message Digest #5)	32, 61
Messages	13
Method	83
Method of operation	21
Mode	58

	Modifying IKE and IPSec settings	26
	MODP	36
N	Name	91
	Nat-Traversal	31, 59
	net	8, 49, 55
	no Comp	44, 74
	NONE	86
	NULL	45, 46, 75, 76
O	Oper Status	12
	Out	113
	Outgoing ISDN number	19
	Own certificates	88
	own/peer	9, 49, 56
P	Packets in	109
	pass	50
	Password	83
	peer	9, 50
	Peer address	15
	Peer certificates	88
	Peer IDs	16
	Peers blocked	108
	Peers dormant	108
	Peers up	108
	Phase 1	
	Authentication method	37, 66
	Group	36, 65
	Lifetime Policy	62
	Local certificate	39, 68
	Local ID	39, 68
	Mode	38, 67
	NAT Traversal	39
	Proposal	31, 60

Phase 2	
Lifetime	46, 76
Proposal	43, 73
PKCS#12 support	91
Please enter certificate data	91
Port	6
Preshared key	16
Preshared keys	37, 66
Profile	48
Propagate PMTU	43, 73
Proposal	6, 58, 71
protect	51
Proto	6
Protocol	7, 48, 54
Pto	112
R RA-Certificate (Encrypt)	87
RA-Certificate (Sign)	87
RADIUS authentication	99
range	9, 49, 56
Registration Authority Certificates	86
Remote	112
Type	8, 48, 54
Remote Address	12
Remote address	6
Remote ID	110
Remote IP	110
Request cert	81
RID	86
Rijndael	32, 45, 60, 75
RipeMD 160	33, 61
RPort	112
RSA encryption	37, 67
RSA Public Exponent	81
RSA signatures	37, 66
S SAs Phase 1	13

SAs phase 1	108
SAs Phase 2	13
SAs phase 2	109
Serial no.	88
Server	85, 91
Setup Tool Wizard	3
SHA1	45, 75
SHA1 (Secure Hash Algorithm #1)	33, 61
Signing Algorithm to Use	85
skip	103
start (wizard)	103
Start of IKE phase 1 negotiation	21
State of last enrollment	84
Step 1 (NAT settings)	103
Step 2 (creation of proposals)	103
Step 3 (define authentication method)	103
Step 4 (request certificate)	104
Step 5 (own certificate)	104
Step 6 (CA certificate)	104
Step 7 (CRL server / peer certificate)	104
Step 8 (peer)	105
Step 9 (peer traffic / peer interface)	105
Subject Alternative Names	85
Subject Alternative Names – Type	85
Subject Alternative Names – Value	85
Subject Alternative Names (optional)	84
Subject name	84, 88
Sync SAs With Local Ifc	99
T TARSEH	110, 111
The IPsec Wizard step by step	103
Tiger 192	33, 61
Traffic List Settings	17
Trust ICMP Messages	98
Twofish	32, 45, 60, 75
Type	86
Type of certificate	89, 90

U	URI	86
	Use PFS	41, 46, 71, 76
	Use Zero Cookies	99
V	View proposals	33, 43, 62
	Virtual interface	17
W	What to do?	102

Index: IP

A	Action	40
	Add Routing Entry	5
	ADDEXT	8
	Address	72, 75, 104
	Admin Status	100
	Administrative Status	64
	Advertise Matching	105
	Alias Name (Description)	27
	Alive Check (if inactive)	59
	Alive Test Period (seconds, 0=disabled)	47
	Area ID	100, 103
	Area Range	104
	Authentication Key	101
	Authentication Type	101
B	Bandwidth Management	21
	Bandwidth on Demand	21
	Block Time (seconds)	63
	BOD	21
C	Cache Hitrate (%)	78
	Cache Hits	78
	Chain	35
	Client / Server	53
	Client Identifier	46
	Connection State	37
	Control all TCP Services	26
D	Default Domain	72
	Default Domains	73
	Default Interface	70
	Default Route distribution	88
	Description	28, 36
	Destination Address	37, 38

Destination IP Address	6
Destination Mask	38
Destination Port	9, 10, 38
DHCP Assignment	70
Dialout	59
Direction	40, 93
Distribution	93
Distribution Fraction (in percent)	30
Distribution Mode	29
Distribution Policy	29, 30
Distribution Ratio	29
DNS	11, 67
DNS Proxy	11
DNS Requests	78
Domain Name	11
Domain Name Server	11, 67
Dynamic Cache	71
DynDNS Registration	79
E Edit Routing Entry	5
Encryption (recommended)	63
Export indirect static routes	101
Extended Routing	8
External Address	17
External Mask	17
External Port	18
F Filter	35, 40
First Rule	42
Flags	5
Forwarded Domains	71
Forwarded Requests	78
G Garbage Collection Timer	90
Gateway	47
Gateway IP Address	7
Generate Default Route for the AS	97

H	Hold down timer	90
	Host Name	80
	HTTP TCP Port	12
I	Ignore	7
	Import external routes	103
	Index	36, 39
	Insert behind Rule	39
	Interface	24, 35, 42, 45, 74, 80, 92
	Interface 1 - 3	30
	Interface Group ID	29
	Internal Address	18
	Internal Mask	18
	Internal Port	19
	Invalid DNS Packets	78
	IP Address	43, 46, 56, 92
	IP Address Pool LAN (DHCP)	45
	IP Address Pool WAN (PPP)	43
	IPCP Assignment	70
L	LAN	7, 34
	Lease Time (Minutes)	46
	Load Balancing	21
	Local	8
	Local Nameservers	73
	Login Authentication/Authorization	64
M	MAC Address	46
	Mask	104
	Maximum Number of DNS Records	76
	Maximum TCP Download Rate (kbits/s)	25
	Maximum TTL for Neg Cache Entries	77
	Maximum TTL for Pos Cache Entries	77
	Metric	7, 101
	Metric Determination	100, 102
	Metric1 offset on interface dormant	94

	Metric1 offset on interface up	93
	Minimum Wait	83
	Mode	9, 10
	MX	81
N	Name	72, 73, 75, 82
	Name Resolution	67
	Negative Cache	69
	NetBT Node Type	47
	Netmask	6, 92
	Network	6
	Network Address Translation	14
	Next Rule	40
	Number of Channels	40
	Number of Consecutive Addresses	43, 46
O	Optimize Download Rate via TCP ACK prioritisation	24
	OSPF	85, 97
	Overwrite Global Nameservers	70
P	Partner / Interface	7
	Password	56, 80
	Path	82
	Permission	81
	Poisoned Reverse	88
	Policy	57, 62
	Pool ID	43
	Port	57, 82
	Positive Cache	69
	PPP Authentication	64
	PPTP Passthrough	14
	Primary BOOTP Relay Server	12
	Primary Domain Name Server	11
	Primary WINS	11
	Priority	56, 61, 93
	Propagate Routes on discard/refuse interfaces	98
	Protocol	9, 16, 36, 56, 83

Provider	81
R RADIUS packets	54
Received DNS Packets	78
Ref	75
Refuse	7
Remote Address	17
Remote CAPI Server TCP Port	12
Remote Mask	17
Remote Port	17
Remote TRACE Server TCP Port	12
Resp	75
Response	72
Retransmission timer	91
Retries	58
RFC 2091 variable timer	89
RFC 2453 variable timer	88
RIP	85
RIP UDP Port	12
Route Timeout	90
Route Type	6
Routing Protocols	85
Rule	35
S Secondary BOOTP Relay Server	12
Secondary Domain Name Server	11
Secondary WINS	11
Server	82
Server Failures	78
Server's IP Address or Hostname	61
Service	16
Silent Deny	14
SNMP	49
SNMP listen UDP port	50
SNMP trap broadcasting	51
SNMP trap community	51
SNMP trap UDP port	51

	SNMP versions	50
	Source Address	37
	Source Interface	9
	Source IP Address	9
	Source Mask	9, 37
	Source Port	9, 10, 37
	Specify Port	37
	State	58
	Static Hosts	70
	Status	27
	Successfully Answered Queries	78
T	TACACS+ Accounting	64
	TACACS+ Key (Secret)	62
	TACACS+ Single-Connection	65
	TCP Port	62
	TCP Service Port	27
	TDRC Mode	25
	Timeout (ms)	57
	Timeout (seconds)	63
	TOS Mask	9, 38
	TTL	72, 74, 75
	Type	37, 46
	Type of Service (TOS)	9, 38
U	Unique Source IP Address	12
	Update Timer	90
	User	80
V	Validate	58
W	WAN with transit network	7, 34
	WAN without transit network	7, 34
	Wildcard	81
	WINS	11

Index: PPP

A	Authentication Negotiation	3
	Authentication Protocol	4
C	Calling party number	3
	CHAP	4
	CLID	3, 5
L	Link Quality Monitoring	5
M	MS-CHAP	4
P	PAP	4
	PPP Link Quality Monitoring	5
	PPPoE Ethernet Interface	6
R	RADIUS	5
	Radius Server Authentication	5

Index: X.25

A	Allow Incoming XOT Calls	44
B	Back Route Verification	38
	Back Route Verify	39
C	Call Setup	4
	Closed User Group	76
	Connection-Oriented	3
	CUG index	76
D	Data Link	5
	Default route	30
	Delay after connection failure	27
	Delay after connection failure (sec)	27
	Destination IP address	32, 35
	Destination Link	21
	Destination Link Address (LLC)	21
	Destination Port	45
	Destination port	36
	Destination X.25 Address	21
	Direction	74
	Disconnect Timeout	16
E	Enable NAT	29
	Extended IP routing	33
	Extended routing	33
G	Gateway IP address	32
H	Highest Two-Way-Channel (HTC)	16
I	Incoming Partner Source IP Address	45
	Interface Name	44

	IP accounting	38, 39
	IP transit network	29
	ISDN ports to use	74
L	L2 Window Size	16
	L3 Mode	14
	L3 Packet Size	14
	L3 Window Size	14
	Layer 2 Behaviour	16
	Link	14
	Local IP address	29
	Local X.25 Address	11
	Logical Channel Number 0	15
	Lowest Two-Way-Channel (LTC)	16
M	Mask	45
	Max Number of XOT Links	45
	Metric	21, 33, 35
	Mode	35
	MTU	45
N	Netmask	32, 35
	Network	32, 33, 34
	NSAP Addresses	9
	Number	74
O	Outgoing Partner Destination IP Address	45
P	Packet Switched	4
	Partner / Interface	32, 35
	Partner IP address	29
	Point-to-Multipoint Interface	6
	Point-to-Point Interface	6
	Protocol	35
	Proxy ARP	38, 40, 41

Index: Frame Relay

A	Advanced settings	27
B	Back Route Verification	28
	Back Route Verify	29
	Basic IP settings	18
D	Default route	20
	Destination IP address	22, 25
	Destination port	26
E	Enable NAT	20
	Extended IP routing	23
	Extended routing	23
F	Flags	20
G	Gateway IP address	22
I	IP accounting	28, 29
	IP transit network	19
L	Local IP address	19
M	Metric	23, 25
	Mode	25
	More routing	20
N	Netmask	22, 25
	Network	22, 23, 24
P	Partner / Interface	22, 25
	Partner IP address	19
	Pro	20

	Protocol	25
	Proxy ARP	28, 30, 31
R	Remote IP address	20
	Remote netmask	20
	RIP	27
	RIP receive	29, 30
	RIP send	29, 30
	Route	18
	Route announce	28, 30
	Route type	22, 24
S	Source interface	25
	Source IP address	25
	Source mask	25
	Source port	26
T	TOS mask	25
	Type of Service (TOS)	25
V	Van Jacobson Header Compression	30

Index: BRRP

A	Advertisement Interface	23
	Advertisement Interval	24
	Advertisement Interval Errors	29
	Advertisements Received	29
	Authentication Errors	29
	Authentication Key	25
	Authentication Type	25
	Authentication Type Mismatch	29
B	Backup	17
	Become Master	29
	BRRP states	15
C	Checksum Errors	29
I	Initialize	16
	Invalid Authentication Type	29
	Invalid Type Packets Received	29
	IP Address Owner	5
	IP TTL Errors	29
M	MAC address	6, 23
	Master	18
	Master Action	12
	Master Down Interval	24
	Master Interface	13
	Master Interface Protocol	11
	Master IP-Address	23
P	Packet Length Errors	29
	Pre-empt Mode	25
	Primary IP Address	5
	Priority	23

R	Redundant network environment	3
	RFC 2338	3
	Router redundancy procedure	3
S	Slave Admin Action	14
	Slave Interface	15
	Slave Interface Protocol	13
T	Task ID	10
V	Version Errors	29
	Virtual Interface	23
	Virtual Router	3, 5
	Virtual Router Backup	5
	Virtual Router ID	12, 15, 22, 28
	Virtual Router Master	5
	Virtual Router State	22, 28
	VRRP Advertisement	5
	VRRP Router	4
W	Watchdog Daemon	6, 9

Index: CREDITS

C	Charges	3
	Credits Based Accounting System	3
I	ISDN Credits	5
	isdnlogin	5
M	Maximum Charge	7
	Maximum Number of Current Incoming Connections	8
	Maximum Number of Current Outgoing Connections	8
	Maximum Number of Incoming Connections	7
	Maximum Number of Outgoing Connections	7, 10
	Maximum Time for Incoming Connections (sec)	7
	Maximum Time for Outgoing Connections (sec)	7, 10
	Measure Time (sec)	6, 9
P	ppp	5
	PPPoE	9
S	Surveillance	6, 9
	Syslog messages	3
X	xDSL	9

Index: CAPI

C	CAPI	4
N	Name	4
P	Password	4

Index: ATM

A	ATM Interface	6, 17, 21, 26, 34
	ATM Service Category	35, 36
B	Back Route Verify	12
	Bridging	11
C	CC End-to-End	30
	CC Segment	31
	Client Type	18
D	Description	6, 17, 21
	DHCP Hostname	9, 23
	DHCP MAC address	9, 23
	Direction	30, 31
E	Encapsulation	7, 9, 15, 18, 22
I	IP accounting	12
	IP configuration	8, 14, 15, 23
L	Local IP number	14
	local IP-Number	8, 23
	Local netmask	14
	local Netmask	8, 23
	Loopback End-to-End	29
	Loopback Segment enable	29
M	MAC Address	14
	MAC address	10, 15
	Maximum Burst Size (MBS) in bytes	36
O	OAM flow level	26

P	Peak Cell Rate (PCR) in bits per second	36
	Pending Requests (max)	29, 30
	Proxy ARP	12
R	RIP receive	12
	RIP send	12
S	Second local IP number	9, 14
	Second local netmask	9, 14
	Send Interval (sec)	29
	Sustained Cell Rate (SCR) in bits per second	36
V	VCI	28, 34
	Virtual channel connection (VCC)	27, 34
	Virtual channel identifier (VCI)	6, 18, 22
	Virtual path connection (VPC)	28
	Virtual path identifier (VPI)	6, 18, 22
	VLAN ID	10, 15
	VPI	28, 34

Index: QoS

A	Action	11
B	Bound Transmit Rate (Shaping)	24
C	Class	23
	Class ID	12, 23
	Class Type	12
	Classification of IP Packets	9
	Congestion Avoidance Algorithm	25
	Connection State	7
D	Description	6
	Destination Address	7
	Destination Mask	7
	Destination Port	8
	Direction	10
	Dropping Algorithm	26
F	Filter	10
I	Index	6, 10
	Insert behind Rule	11
	Interface	18
	IP QoS Classification via	18
L	Lower Queue Threshold (Bytes)	26
M	Maximum Burst Size (Number of Bits)	14
	Maximum Burst Size (Number of Packets)	14
	Maximum Rate (Bits per Second)	14
	Maximum Rate (Packets per Second)	14
	Maximum Transmit Rate (Bits per Second)	22
	MLPPP Fragment Size	19

	MLPPP Interleave Mode	19
N	Next Rule	11
P	Priority	25
	Protocol	6
Q	Queuing and Scheduling Algorithm	20
S	Set Remark Type of Service (TOS) Field	15
	Set Type of Service (TOS) Field	13
	Shaping Algorithm	25
	Source Address	7
	Source Mask	7
	Source Port	7, 8
	Specify Port	7
	Specify ToS Set Exceed Action	14
	Specify ToS Set Rate Limitation	13
	Specify Traffic Shaping	21
T	TOS Mask	8
	Transmit Rate (Bits per Second)	24
	Transmit Rate Burst	24
	Type	7
	Type of Service (TOS)	8
U	Upper Queue Threshold (Bytes)	26
W	Weight	24

Index: VoIP

A	Adminstatus	6
D	Destination Port	7
H	H.323 standard	3
L	Low Latency Transmission	7
P	Protocol	7
	Proxy Settings	6
	Proxy Type	6
R	Real-time behavior	3
V	Voice and video transmission	3

Index: GRE

G	Generic Routing Encapsulation	3
	GRE Local IP Address	4
	GRE Partner's IP Address	4
	GRE V.0	3
	GRE V.1	3
K	Key Used	5
M	Mtu	5
N	Name	4
P	Partner's LAN IP Address	4
	Partner's LAN IP Mask	4
V	Value	5
	Virtual Interface	3

Index: L2TP

D	Data Packets Sequence Numbers	12
H	Hello Interval	12
L	LAC	3, 8
	Layer 2 Tunneling Protocol	3
	LNS	3, 5, 8
	Local Hostname	9
	Local IP Address	9
	Local UDP Port (LAC only)	9
M	Maximum Retry Count	13
	Maximum Time Between Retries	12
	Minimum Time Between Retries	12
P	Port usage for LNS mode	5
	PPP over L2TP (LAC mode)	3
	PPP over L2TP (LNS mode)	3
	Profile Name	8
R	Remote Hostname	11
	Remote IP Address - backup (LAC only)	10
	Remote IP Address (LAC only)	10
	Remote IP addresses through Radius (LAC only)	10
	Remote UDP Port (LAC only)	10
S	SCCRPs	9
	SCCRQs	9
T	Tunnel Password	11
	tunnel profiles	7
U	UDP port number for LNS mode	5

Index: Configuration Management

B	boot	3
	Boot configuration file	3
C	Configuration information	3
F	Flash	3
	Flash EEPROM	3
N	Name in Flash	4
	New Name in Flash	4
O	Operation	4, 5
	Operations	3
R	RAM	3
S	Start Operation	5
	State of last operation	4
T	TFTP File Name	4
	TFTP Server	3
	TFTP Server IP Address	4
	Type of last operation	4
U	Unix	3
W	Windows	3

Index: Monitoring and Debugging

A	Active Connections	18
	Admin Status	40
	Adminstatus	23
	ADSL	4
	Advertisement Interval Errors	63
	Advertisements Received	63
	Age	43
	Area	42
	ATM Interface	45
	ATM/OAM	4
	Authentication Errors	63
	Authentication Type Mismatch	63
B	Backup Designated Router (BDR)	40
	Become Master	63
	BRRP	4
C	CEA	37
	Charge	10
	Checksum Errors	63
	Class	68
	Compress	26
	Contents	25
	Corrected blocks	55
	CRC anomalies	59
	Current attenuation	54
	Current loop attenuation	59
	Current noise margin	54
	Current output power	54
	Current SNR margin	59
	Current status	54, 58, 59
D	Designated Router (DR)	40
	Dropped Octets	71

	Dropped Packets	71
	Duration	18
E	Email Alert	23
	End to end	49, 52
	Errored seconds (ES)	54, 59
	EXTENDED	18
F	Framing (LOF)	54
I	In	37
	InOctets	70
	InPkts	70
	Interface	39, 41, 65
	Interface Name	17
	Interfaces	3, 17, 39
	Invalid Authentication Type	63
	Invalid Type Packets Received	63
	IP QoS	4
	IP TTL Errors	63
	IPSec	4
	ISDN Credits	3, 9
	ISDN Monitor	3, 5
L	Last Error	24
	Level	25
	Link State ID	42
	Local	36
	Local ID	35
	Loss of sync word (LOSW) seconds	59
	LPort	36
	LSDB	42
M	max. Mails/min	24
	Maximum Transmit Rate	66
	Messages	4, 21, 26

N	Neighbor	41
	Nominal Transmit Rate	65
	Number of Current Connections	10
	Number of Current Incoming Connections	10
	Number of Current Outgoing Connections	10
	Number of Incoming Connections	9
	Number of Outgoing Connections	10, 11
O	OctetsDropped	70
	Octs	69
	Operation	18
	Operational Status	17, 45, 48, 51, 65
	Originator	24
	OSPF	4, 39
	Out	37
	OutOctets	70
	OutPkts	70
P	Packet Length Errors	63
	Packets in	33
	Peers blocked	32
	Peers dormant	32
	Peers up	32
	Pkts	69
	PktsDropped	70
	Power (LRP)	54
	Pto	36
Q	Queued Octets	71
	Queued Packets	71
R	Received blocks	54, 59
	Received Errors	18, 46
	Received Octets	18, 45, 66
	Received Packets	17, 66
	Receiver	25

Remote	36
Remote ID	34
Remote IP	34
Retx Queue	41
Router ID	41, 43
RPort	36
RX Rate (Kb/s)	45
S	
SAs phase 1	32
SAs phase 2	33
Segment	49, 52
Select subsystems	26
Sequence	43
Severely errored seconds (SES)	59
SHDSL	4
Signal (LOS)	54
SMTP Server	24
SSHD	4
START OPERATION	18
State	40, 41, 42
T	
TARSEH	34, 35
TCP/IP	4, 29
Time for Outgoing Connections (sec)	11
Time of Incoming Connections	10
Time of Outgoing Connections	10
Time till end of measure interval (sec)	9, 11
Timeout	25
TOS	70
Transmit Discards	46
Transmit Errors	18, 46
Transmit Octets	18, 46, 66, 71
Transmit Packets	18, 66, 71
Transmitted blocks	54, 60
TX Rate (Kb/s)	46
Tx rate (Kb/s)	54
Type	42

U	Unavailable seconds (UAS)	59
	Uncorrect blocks	55
V	Vendor ID	53
	Version Errors	63
	Version Number	53
	Virtual channel connection (VCC)	50
	Virtual path connection (VPC)	47
	Virtual Router ID	62
	Virtual Router State	62
X	X.25 Monitor	3
	xDSL Credits	3, 11

