



## Index: Licenses

|          |                                 |      |
|----------|---------------------------------|------|
| <b>A</b> | Auslieferungszustand            | 4    |
| <b>D</b> | Description                     | 5    |
| <b>H</b> | Hardware-Seriennummer           | 3    |
| <b>K</b> | Key                             | 3, 5 |
| <b>L</b> | LicenseSerialNumber             | 3    |
|          | Lizenzdaten                     |      |
|          | Freischalten von Zusatzlizenzen | 4    |
|          | LicenseSerialNumber             | 3    |
|          | PIN                             | 3    |
|          | Serialnumber                    | 3    |
|          | Software License ID             | 3    |
| <b>M</b> | Mask                            | 5    |
| <b>O</b> | Online-Lizenzierung             | 3, 5 |
| <b>P</b> | PIN                             | 3    |
| <b>S</b> | Serialnumber                    | 3, 5 |
|          | Software License ID             | 3    |
| <b>V</b> | Verfügbare Subsysteme           | 4    |



# Index: System

## Numerics

|                             |        |
|-----------------------------|--------|
| 1. Event Index              | 28     |
| <b>A</b> Action             | 17     |
| Activity Monitor            | 7      |
| <b>C</b> Change System Time | 36     |
| CLID                        | 13     |
| Client IP Address           | 8      |
| Client UDP Port             | 8      |
| Compare value               | 25     |
| Condition                   | 24     |
| Contact                     | 4      |
| Current System Time         | 36     |
| <b>D</b> Description        | 21, 28 |
| DownAction                  | 15     |
| <b>E</b> End time           | 25     |
| End value                   | 25     |
| Eventlist Condition         | 29     |
| Execute command             | 29     |
| External Activity Monitor   | 7      |
| External System Logging     | 9      |
| <b>F</b> Facility           | 10     |
| FirstIfIndex                | 16, 17 |
| <b>G</b> Group              | 14     |
| Grundlegenden Systemdaten   | 3      |
| <b>H</b> Hosts              | 13     |
| <b>I</b> Index              | 21, 28 |



|  |        |
|--|--------|
| Index value                                | 23, 30 |
| Index variable                             | 23, 30 |
| Interface                                  | 17, 29 |
| Interfaces                                 | 13     |
| Interval                                   | 14     |
| IPAddress                                  | 14     |
| <b>K</b> Keepalive Monitoring              | 13     |
| <b>L</b> LAN                               | 13     |
| Last Change                                | 31     |
| Level                                      | 10     |
| Local PPP ID (default)                     | 3      |
| Location                                   | 4      |
| Log Host                                   | 9, 10  |
| <b>M</b> Maximum Number of Acctlog Entries | 5      |
| Maximum Number of Syslog Entries           | 5      |
| Message level for the syslog table         | 5      |
| Method                                     | 11     |
| Mode                                       | 28     |
| Monitored event                            | 22     |
| <b>N</b> Name/Address                      | 37     |
| Next Index                                 | 21     |
| Notify                                     | 31     |
| <b>P</b> Password settings                 | 33     |
| Activity Monitor                           | 33     |
| admin                                      | 33     |
| Auslieferungszustand                       | 33     |
| HTTP Server                                | 33     |
| read                                       | 33     |
| write                                      | 33     |
| Protocol                                   | 37     |
| Protokoll der Ereignisse                   | 9      |



|          |                                 |           |
|----------|---------------------------------|-----------|
| <b>R</b> | Range                           | 16, 18    |
| <b>S</b> | Set value active                | 30        |
|          | Source IP                       | 15        |
|          | Start time                      | 25        |
|          | Status                          | 26, 31    |
|          | Subsysteme                      | 9         |
|          | Syslog Messages                 | 9         |
|          | Syslog output on serial console | 4         |
|          | System Name                     | 3         |
|          | System Time Offset from GMT     | 36        |
|          | Systemzeit                      | 35        |
|          | Accounting                      | 35        |
|          | automatisch                     | 35        |
|          | manuell                         | 35        |
| <b>T</b> | Table                           | 22, 30    |
|          | Time and Date                   | 35        |
|          | Time Update Interval            | 36        |
|          | Timestamp                       | 11        |
|          | Trials                          | 15        |
|          | Trigger                         | 17        |
|          | Type                            | 8, 10, 21 |
| <b>U</b> | Update Interval (sec)           | 8         |
|          | Update System Time from ISDN    | 36        |
| <b>V</b> | value inactive                  | 30        |
|          | Variable                        | 22, 30    |
| <b>Z</b> | Zentraler Server                | 13        |



## Index: External Systems

|          |                             |         |
|----------|-----------------------------|---------|
| <b>A</b> | Access Points               | 3       |
|          | Admin. Password             | 11      |
|          | AP MAC Address              | 8       |
|          | Authentisierungsverhandlung | 3       |
| <b>C</b> | Calling Party Number        | 3       |
|          | CLID                        | 3       |
| <b>D</b> | Discovery                   | 3       |
|          | discovery                   | 7       |
| <b>G</b> | Gateway Address             | 11      |
| <b>I</b> | Interface                   | 4, 6, 8 |
|          | IP Address                  | 11      |
|          | IP Status                   | 9       |
| <b>L</b> | Last Change                 | 11      |
|          | Last Run                    | 5       |
| <b>N</b> | Netmask                     | 11      |
|          | Node Name                   | 11      |
| <b>O</b> | Operation                   | 4, 7, 9 |
| <b>R</b> | Result                      | 5, 10   |





## Index: Ethernet

|          |                        |            |
|----------|------------------------|------------|
| <b>A</b> | Advanced Settings      | 14, 20     |
| <b>B</b> | Back Route Verify      | 14, 15, 17 |
|          | Bridging               | 14         |
| <b>D</b> | DHCP Hostname          | 13         |
|          | DHCP MAC Address       | 12         |
| <b>E</b> | Encapsulation          | 13, 19     |
|          | Ethernet Unit (1 - 3)  | 3          |
|          | ETH-Schnittstellen     | 3          |
| <b>I</b> | IP Accounting          | 14, 15, 16 |
|          | IP Configuration       | 12, 18, 20 |
| <b>L</b> | Local IP-Number        | 12, 18     |
|          | Local Netmask          | 12, 18     |
| <b>M</b> | MAC Address            | 13, 18, 19 |
|          | Mode                   | 13         |
| <b>P</b> | Proxy ARP              | 14, 16     |
| <b>R</b> | RIP                    | 14, 15, 17 |
|          | V1                     | 17         |
|          | V2                     | 17         |
|          | RIP Receive            | 16         |
|          | RIP Send               | 16         |
|          | Route                  | 14         |
|          | Routing                | 15         |
|          | Routing-Tabelle        | 14         |
| <b>S</b> | Second Local IP-Number | 12, 19     |



|          |                      |        |
|----------|----------------------|--------|
|          | Second Local Netmask | 12, 19 |
| <b>V</b> | Virtual Interfaces   | 18     |
|          | VLAN ID              | 13, 20 |
| <b>W</b> | WAN Partner          | 15     |

## Index: ISDN

|          |  |         |
|----------|--|---------|
| <b>A</b> | Anlagenanschluß (Point to Point)         | 5       |
| <b>B</b> | Basic Rate Interface (BRI)               | 3       |
|          | B-Channel 1                              | 6       |
|          | B-Channel 2                              | 7       |
|          | Bearer                                   | 11      |
| <b>D</b> | data                                     | 11      |
|          | D-Channel                                | 6       |
|          | DOVB                                     | 12      |
| <b>F</b> | Festverbindung (Leased line)             | 5       |
| <b>I</b> | Incoming Call Answering                  | 9       |
|          | IPSec                                    | 12      |
|          | ISDN Login                               | 10, 12  |
|          | ISDN S0                                  | 3       |
|          | ISDN Switch Type                         | 3, 5, 6 |
|          | Item                                     | 11      |
| <b>L</b> | Leased dte, dce                          | 6, 7    |
|          | Leased line (Festverbindung)             | 5       |
| <b>M</b> | Mehrgeräteanschluß (Point to multipoint) | 5       |
|          | Mode                                     | 11      |
| <b>N</b> | Number                                   | 11      |
| <b>P</b> | Point to multipoint (Mehrgeräteanschluß) | 5       |
|          | Point to Point (Anlagenanschluß)         | 5       |
|          | PPP (routing)                            | 12      |
| <b>R</b> | Result of autoconfiguration              | 4       |



|          |                    |    |
|----------|--------------------|----|
| <b>S</b> | SPID B-Channel 1   | 7  |
|          | SPID B-Channel 1+2 | 7  |
|          | SPID B-Channel 2   | 7  |
| <b>V</b> | voice              | 11 |



## Index: Wireless LAN

|                 |                     |       |
|-----------------|---------------------|-------|
| <b>Numerics</b> | 802.11 b/g mixed    | 18    |
| <b>A</b>        | Accept Address      | 13    |
|                 | Access Point        | 4     |
|                 | Active Probing      | 5     |
|                 | AdminStatus         | 9, 13 |
| <b>C</b>        | Channel             | 4     |
| <b>D</b>        | Default Key         | 10    |
| <b>F</b>        | FOUR-X Burst        | 19    |
| <b>K</b>        | Key                 | 11    |
| <b>L</b>        | local communication | 15    |
|                 | local IP-Number     | 15    |
|                 | local Netmask       | 15    |
|                 | Location            | 4     |
| <b>M</b>        | MAC Filter          | 12    |
|                 | Maximum Bitrate     | 18    |
|                 | Mode                | 14    |
| <b>N</b>        | Name is visible     | 9     |
|                 | Network Name        | 9     |
| <b>O</b>        | Operation Mode      | 4     |
| <b>P</b>        | Preshared Key       | 12    |
| <b>R</b>        | Routing             | 14    |



|          |                        |      |
|----------|------------------------|------|
| <b>S</b> | Second Local IP-Number | 15   |
|          | Second Local Netmask   | 15   |
|          | Security Mode          | 10   |
|          | SSID                   | 7, 9 |
| <b>T</b> | TX Power (dBm)         | 19   |
| <b>V</b> | vss                    | 5    |
| <b>W</b> | WEP                    | 6    |
|          | Wireless Mode          | 18   |
|          | WPA                    | 6    |



## Index: ADSL

|          |                                 |   |
|----------|---------------------------------|---|
| <b>M</b> | Maximum threshold (kb/s)        | 4 |
| <b>P</b> | Physical connection established | 3 |
| <b>T</b> | Transmit shaping                | 3 |





## Index: WAN Partner

|          |                                      |            |
|----------|--------------------------------------|------------|
| <b>A</b> | Advanced Settings                    | 48         |
|          | Authentication                       | 11         |
|          | Authentisierungsverhandlung          | 11         |
| <b>B</b> | Back Route Verification              | 50         |
|          | Back Route Verify                    | 51         |
|          | Bandwidth On Demand (=BOD)           | 23         |
|          | Basic IP-Settings                    | 37         |
|          | Bridge                               | 55         |
|          | Bridging-Modus                       | 55         |
| <b>C</b> | Callback                             | 15, 17, 20 |
|          | Calling Line Identification          | 7          |
|          | Channel-Bundling                     | 16, 18     |
|          | Closed User Group                    | 36         |
|          | Compression                          | 6, 7       |
|          | CUG-Index                            | 36         |
| <b>D</b> | D-Channel Queue Length               | 26         |
|          | Default Route                        | 37, 40, 41 |
|          | Delay after Connection Failure       | 16         |
|          | Delay after Connection Failure (sec) | 18         |
|          | Destination IP-Address               | 43, 46     |
|          | Destination Port                     | 47, 48     |
|          | Direction                            | 34         |
|          | Dynamic Name Server Negotiation      | 52, 54     |
| <b>E</b> | Enable NAT                           | 39, 41     |
|          | Encapsulation                        | 5, 6       |
|          | Encryption                           | 6          |
|          | Erweitertes IP-Routing               | 44         |
|          | Extended Interface Settings          | 23         |
|          | Extended Routing                     | 44         |



|          |                                   |                |
|----------|-----------------------------------|----------------|
| <b>F</b> | Flags                             | 42             |
| <b>G</b> | Gateway IP Address                | 41             |
|          | Gateway IP-Address                | 44             |
|          | Gear Down Threshold               | 25             |
|          | Gear Up Threshold                 | 25             |
|          | Geschlossene Benutzergruppe       | 36             |
| <b>I</b> | Idle for Dynamic Short Hold (%)   | 17             |
|          | IP                                | 37             |
|          | IP Accounting                     | 50, 51         |
|          | IP Transit Network                | 39             |
| <b>K</b> | Keepalives                        | 12             |
| <b>L</b> | Layer 1 Protocol                  | 16, 18, 21     |
|          | Line Utilization Sample (sec)     | 25             |
|          | Line Utilization Weighting        | 24             |
|          | Link Quality Monitoring           | 12             |
|          | Local IP Address                  | 39             |
|          | Local PPP ID                      | 11             |
|          | Local PPTP VPN IP Address         | 41             |
| <b>M</b> | Maximum Number of Dialup Channels | 26             |
|          | Metric                            | 44, 47         |
|          | Mode                              | 24, 26, 46, 47 |
|          | More Routing                      | 42             |
| <b>N</b> | Netmask                           | 44, 46         |
|          | Network                           | 43, 44, 46     |
|          | Number                            | 33             |
| <b>P</b> | Partner / Interface               | 44, 46         |
|          | Partner IP Address                | 39             |
|          | Partner Name                      | 5              |
|          | Partner PPP ID                    | 11             |



|  |            |
|--|------------|
| Partnername  | 3          |
| PPP Password   | 11         |
| PPTP VPN Partner's IP Address                                | 40         |
| Pro  | 42         |
| Protocol   | 3, 47      |
| Proxy Arp  | 50, 52, 53 |
| <b>R</b> Remote IP Address                                   | 40         |
| Remote Netmask   | 40         |
| Remote X.25 Address  | 19         |
| RIP  | 49         |
| RIP Receive  | 51, 52     |
| RIP Send   | 51, 52     |
| Route  | 37         |
| Route Announce   | 50, 51     |
| Route Type   | 43, 46     |
| Routing-Einstellungen  | 37         |
| Rufnummern des WAN Partners                                  | 33         |
| <b>S</b> Shorthold   | 15         |
| Source Interface   | 47         |
| Source IP-Address  | 47         |
| Source Mask  | 47         |
| Source Port  | 47, 48     |
| Special Interface Types                                      | 19         |
| State  | 3          |
| Static Short Hold (sec)                                      | 17         |
| <b>T</b> TOS Mask  | 47         |
| Total Number of Channels                                     | 19         |
| Type of Service (TOS)  | 47         |
| <b>U</b> Use Gateway   | 41         |
| <b>V</b> Van Jacobson Header Compression<br>via IP Interface | 52<br>40   |



## Index: Security

### Numerics

|          |                           |            |
|----------|---------------------------|------------|
|          | 3des                      | 49         |
| <b>A</b> | Action                    | 13, 23, 35 |
|          | Admin Status              | 8          |
|          | Adminstatus               | 29         |
|          | aes128                    | 49         |
|          | aes192                    | 49         |
|          | aes256                    | 49         |
|          | Alias                     | 36, 38     |
|          | arc4                      | 49         |
| <b>B</b> | blowfish                  | 49         |
| <b>C</b> | cast128                   | 49         |
|          | Category                  | 11         |
|          | Challenge Response        | 48         |
|          | ClientAliveCountMax       | 46         |
|          | ClientAliveInterval       | 46         |
|          | Compression               | 43         |
|          | Connection State          | 19         |
| <b>D</b> | Day                       | 12         |
|          | Deny Silent               | 25         |
|          | Description               | 18         |
|          | Destination               | 34         |
|          | Destination Address       | 20         |
|          | Destination Mask          | 20         |
|          | Destination Port          | 20         |
|          | Dynamische Paketfilterung | 27         |
| <b>E</b> | Expiring Date             | 8          |
| <b>F</b> | Filter                    | 15, 16, 23 |

|          |                          |            |
|----------|--------------------------|------------|
|          | Filtered Interfaces      | 8          |
|          | Filterliste              | 10         |
|          | First Rule               | 25         |
|          | From                     | 12         |
|          | Full Filtering           | 30         |
| <b>H</b> | History Entries          | 9          |
| <b>I</b> | ICMP Type                | 36         |
|          | Index                    | 18, 22     |
|          | Insert behind Rule       | 22         |
|          | Interface                | 25, 38, 58 |
|          | IP Access Lists          | 28         |
|          | IP Address               | 38, 58     |
|          | IP-Mask                  | 38         |
|          | IP-Range                 | 38         |
| <b>K</b> | Kategorisierung          | 7          |
|          | Kette                    | 16         |
| <b>L</b> | Local Filter             | 30         |
|          | Logging Level            | 31, 44     |
|          | Login Grace Time         | 45         |
| <b>M</b> | Mask                     | 58         |
|          | Max. # of Clients        | 43         |
|          | md5                      | 50         |
|          | md5-96                   | 50         |
|          | Mode                     | 38         |
| <b>N</b> | NAT                      | 28         |
|          | Netzwerkzugangskontrolle | 15         |
|          | Next Rule                | 23         |
| <b>O</b> | Orange Filter Ticket     | 8          |
|          | Other inactivity Timeout | 40         |

|          |                             |        |
|----------|-----------------------------|--------|
| <b>P</b> | Password                    | 48     |
|          | Port                        | 36     |
|          | Port # used for Connections | 43     |
|          | PPTP inactivity Timeout     | 40     |
|          | Print LastLog               | 44     |
|          | Print Motd                  | 43     |
|          | Priority                    | 13     |
|          | Protocol                    | 19, 36 |
|          | Protocol Version            | 47     |
|          | Public Key                  | 47     |
| <b>R</b> | Range                       | 37     |
|          | Regel                       | 16     |
|          | Regelketten                 | 21     |
|          | Reihenfolge                 | 23     |
|          | Reporting Method            | 25     |
|          | ripemd160                   | 50     |
| <b>S</b> | Schnittstelle               | 17     |
|          | Service                     | 34, 57 |
|          | shal                        | 50     |
|          | shal-96                     | 50     |
|          | Sicherheitsfunktion         | 27     |
|          | SIF                         | 28     |
|          | Source                      | 20, 33 |
|          | Source Address              | 19     |
|          | Source Mask                 | 19     |
|          | Source Port                 | 20     |
|          | Specify Port                | 20     |
| <b>T</b> | TCP inactivity Timeout      | 39     |
|          | TCP Keepalives              | 45     |
|          | Ticket Status               | 8      |
|          | To                          | 13     |
|          | TOS Mask                    | 20     |
|          | Type                        | 19     |

|          |  |    |
|----------|--|----|
|          | Type of Service (TOS)                  | 20 |
| <b>U</b> | UDP inactivity Timeout                 | 39 |
|          | URL-basierter Content Filtering Dienst | 7  |
| <b>V</b> | Verify Interface                       | 58 |
|          | Verify IP Address                      | 57 |
|          | Verify Reverse Mapping                 | 43 |
| <b>Z</b> | Zugangsbeschränkungen                  | 15 |



## Index: IPSec

### Numerics

|                   |                |
|-------------------|----------------|
| 1 (768 bit MODP)  | 37, 68         |
| 2 (1024 bit MODP) | 37, 68         |
| 3DES              | 32, 46, 63, 77 |
| 5 (1536 bit MODP) | 37, 68         |

### A

|  |               |
|--|---------------|
| A  | 6             |
| abort  | 107           |
| ACTION   | 14            |
| Action   | 8, 50, 52, 55 |
| Admin Status                                   | 12, 15        |
| aggressive                                     | 38, 69        |
| aggressive-only                                | 39, 70        |
| AH (Authentication Header)                     | 45, 76        |
| Algorithm                                      | 82            |
| Anpassung der IKE- und IPSec-Einstellungen     | 26            |
| Authentication Method                          | 29, 60        |
| auto/base64/binary                             | 95            |
| autodetect best possible mode (D channel only) | 24            |
| autodetect best possible mode (D or B channel) | 24            |
| Autosave                                       | 85            |

### B

|                                    |                |
|------------------------------------|----------------|
| Beginn der IKE-Phase-1-Aushandlung | 22             |
| Block Time                         | 31, 62         |
| Blowfish                           | 32, 46, 63, 77 |

### C

|                                    |                |
|------------------------------------|----------------|
| CA Certificates                    | 31, 40, 62, 71 |
| CA-Certificate                     | 86             |
| CA-Domain                          | 86             |
| CAST                               | 32, 46, 63, 77 |
| CEA                                | 117            |
| Certificate Authority Certificates | 91             |
| Certname                           | 88             |
| clear config                       | 106            |
| Cookies Size                       | 103            |

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| CRL                                   | 40, 71                            |
| CRLs                                  | 98                                |
| <b>D</b>                              |                                   |
| D-Channel Mode                        | 25                                |
| default                               | 38, 69                            |
| Der IPSec- Wizard Schritt für Schritt | 107                               |
| DES                                   | 32, 46, 63, 77                    |
| Description                           | 7, 12, 15, 49, 54, 59, 82, 92, 93 |
| Description (Idx 0)                   | 29, 42, 73                        |
| dhcp                                  | 9, 51, 56                         |
| DN                                    | 88                                |
| DNS                                   | 88                                |
| Dont Send Cert Chains                 | 102                               |
| Dont send Cert Req Payl.              | 102                               |
| Dont send CRLs                        | 102                               |
| Dont Send Initial Contact             | 103                               |
| Dont send Key Hash Payl.              | 102                               |
| drop                                  | 52                                |
| DSA Signatures                        | 37, 69                            |
| dump messages                         | 106                               |
| <b>E</b>                              |                                   |
| Edit Lifetimes                        | 35                                |
| Email                                 | 88                                |
| Enable IPSec                          | 4                                 |
| Erste aktive Regel                    | 6                                 |
| ESP (Encapsulated Security Payload)   | 44, 76                            |
| <b>F</b>                              |                                   |
| Filename                              | 88                                |
| Flags                                 | 92                                |
| force Comp                            | 46, 77                            |
| Force trusted                         | 95                                |
| Funktionsweise                        | 21                                |
| <b>G</b>                              |                                   |
| Group                                 | 29, 60                            |
| <b>H</b>                              |                                   |
| Heartbeats                            | 30, 43, 61, 74                    |
| host                                  | 8, 50, 55                         |



|          |  |                |
|----------|--|----------------|
| <b>I</b> | id_protect   | 38, 69         |
|          | ID-Protect-Modus   | 21             |
|          | id-protect-only  | 39, 70         |
|          | Ignore Cert Req Payloads   | 101            |
|          | IKE (Phase 1) Defaults   | 4              |
|          | Import a Certificate/CRL using   | 94             |
|          | In   | 117            |
|          | Incoming ISDN Number   | 19             |
|          | Interface IP Settings  | 17             |
|          | Interoperabilitäts-Flags   | 101            |
|          | IP   | 88             |
|          | IPComP   | 45, 76         |
|          | IPsec (Phase 2) Defaults   | 4              |
|          | ISDN Callback  | 19             |
| <b>K</b> | Kb   | 36, 67         |
|          | Key Size (Bits)  | 83             |
|          | Key to enroll  | 84             |
|          | Kombination aus Verschlüsselungs- und Message Hash-Algorithmen für IKE Phase 1 | 31             |
| <b>L</b> | Lifetime   | 29, 42, 60, 74 |
|          | Lifetime Restriction Based On  | 35, 66         |
|          | LLC  | 25             |
|          | LLC-and-SUBADDR  | 25             |
|          | Local  | 116            |
|          | Type   | 8, 49, 55      |
|          | Local Address  | 5, 12          |
|          | Local Certificate  | 31, 62         |
|          | Local ID   | 31, 62, 115    |
|          | Local/Remote   |                |
|          | Type   | 50, 55         |
|          | LPort  | 116            |
| <b>M</b> | M/R  | 6              |
|          | Matching Policy  | 36, 67         |



|                           |            |
|---------------------------|------------|
| Max. Symmetric Key Length | 103        |
| MD5                       | 47, 78     |
| MD5 (Message Digest #5)   | 33, 63     |
| Messages                  | 13         |
| Method                    | 85         |
| Mode                      | 24, 29, 60 |
| MODP                      | 36         |

|                |                |
|----------------|----------------|
| <b>N</b> Name  | 95             |
| NAT Traversal  | 40, 71         |
| Nat-Traversal  | 31             |
| Nat-Traversals | 62             |
| net            | 9, 51, 56      |
| no Comp        | 46, 77         |
| NONE           | 89             |
| NULL           | 46, 47, 77, 78 |

|                      |           |
|----------------------|-----------|
| <b>O</b> Oper Status | 12        |
| Out                  | 117       |
| Outgoing ISDN Number | 19        |
| Own Certificates     | 91        |
| own/peer             | 9, 51, 57 |

|                     |     |
|---------------------|-----|
| <b>P</b> Packets In | 113 |
| pass                | 52  |
| Password            | 86  |
| Peer Address        | 15  |
| Peer Certificates   | 91  |
| Peer IDs            | 16  |
| Peers Blocked       | 112 |
| Peers Dormant       | 112 |
| Peers Up            | 112 |



|  |                   |
|--|-------------------|
| Phase 1                                    |                   |
| Authentication Method                      | 37, 68            |
| Group                                      | 36, 67            |
| Lifetime                                   | 65                |
| Local Certificate                          | 39, 70            |
| Local ID                                   | 39, 70            |
| Mode                                       | 38, 69            |
| Proposal                                   | 31, 62            |
| Phase 2                                    |                   |
| Lifetime                                   | 48, 79            |
| Proposal                                   | 44, 75            |
| PKCS#12-Unterstützung                      | 95                |
| Please enter certificate data              | 94                |
| Port                                       | 6                 |
| Pre Shared Key                             | 16                |
| Pre Shared Keys                            | 37, 68            |
| Profile                                    | 50                |
| Propagate PMTU                             | 44, 75            |
| Proposal                                   | 6, 29, 42, 60, 74 |
| protect                                    | 52                |
| Proto                                      | 6                 |
| Protocol                                   | 7, 49, 54         |
| Pto  | 116               |
| <b>R</b>                                   |                   |
| RA-Certificate (Encrypt)                   | 91                |
| RA-Certificate (Sign)                      | 90                |
| RADIUS Authentication                      | 103               |
| range                                      | 9, 51, 56         |
| Registration-Authority-Zertifikate im SCEP | 89                |
| Remote                                     | 116               |
| Type                                       | 8, 50, 55         |
| Remote Address                             | 6, 12             |
| Remote ID                                  | 114               |
| Remote IP                                  | 114               |
| Request Cert                               | 83                |
| RID  | 88                |
| Rijndael                                   | 32, 46, 63, 77    |

|   |         |
|---|---------|
| RipeMD 160                                | 33, 64  |
| RPort                                     | 117     |
| RSA Encryption                            | 38, 69  |
| RSA Public Exponent                       | 83      |
| RSA Signatures                            | 38, 69  |
| <b>S</b> SAs Phase 1                      | 13, 112 |
| SAs Phase 2                               | 13, 113 |
| Schritt 1 (NAT-Einstellungen)             | 107     |
| Schritt 2 (Erstellung der Proposals)      | 107     |
| Schritt 3 (Authentisierungsart festlegen) | 108     |
| Schritt 4 (Zertifikat beantragen)         | 108     |
| Schritt 5 (Eigenes Zertifikat)            | 108     |
| Schritt 6 (CA-Zertifikat)                 | 108     |
| Schritt 7 (CRL Server / Peer Certificate) | 109     |
| Schritt 8 (Peer)                          | 109     |
| Schritt 9 (Peer Traffic / Peer Interface) | 109     |
| Seconds                                   | 35, 66  |
| Serial No                                 | 92      |
| Server                                    | 87, 95  |
| Setup Tool Wizard                         | 3       |
| SHA1                                      | 47, 78  |
| SHA1 (Secure Hash Algorithm #1)           | 33, 64  |
| Signing algorithm to use                  | 87      |
| skip                                      | 107     |
| start (wizard)                            | 107     |
| Start Wizard                              | 105     |
| State of Last Enrollment                  | 87      |
| SUBADDR                                   | 25      |
| Subject Alternative Names                 | 88      |
| Subject Alternative Names – Type          | 88      |
| Subject Alternative Names – Value         | 88      |
| Subject Alternative Names (optional)      | 87      |
| Subject Name                              | 86      |
| Subject Names                             | 92      |
| Sync SAs With Local Ifc                   | 103     |



|          |  |                |
|----------|--|----------------|
| <b>T</b> | TARSEH   | 114, 115       |
|          | Tiger 192  | 33, 64         |
|          | Traffic List Settings                                      | 17             |
|          | Transfer own IP Address over ISDN                          | 23             |
|          | Trust ICMP Messages  | 102            |
|          | try specific D channel mode, fall back on B                | 24             |
|          | Twofish  | 32, 46, 63, 77 |
|          | Type   | 88             |
|          | Type of Certificate  | 93, 94         |
| <b>U</b> | Übertragung der IP-Adresse                                 | 22             |
|          | URI  | 88             |
|          | use B channel  | 24             |
|          | Use PFS  | 42, 48, 74, 79 |
|          | use specific D channel mode                                | 24             |
|          | Use Zero Cookies   | 103            |
| <b>V</b> | Verfügbaren Verschlüsselungs- und Message Hash-Algorithmen | 32             |
|          | View Proposals   | 34, 44, 65     |
|          | Virtual Interface  | 17             |
| <b>W</b> | What to do?  | 106            |





## Index: IP

|          |   |           |
|----------|---|-----------|
| <b>A</b> | Action                                  | 42        |
|          | ADDEXT                                  | 8         |
|          | Address                                 | 75, 78    |
|          | Administrative Status                   | 67        |
|          | Alias Name (Description)                | 28        |
|          | Alive Check (if inactive)               | 61        |
|          | Alive Test Period (seconds, 0=disabled) | 48        |
| <b>B</b> | Bandwidth Management                    | 23        |
|          | Bandwidth on Demand                     | 23        |
|          | Block Time (seconds)                    | 66        |
|          | BOD                                     | 23        |
| <b>C</b> | Cache Hitrate (%)                       | 82        |
|          | Cache Hits                              | 81        |
|          | Client / Server                         | 55        |
|          | Connection State                        | 38        |
|          | Control all TCP Services                | 27        |
| <b>D</b> | Default Domain                          | 74        |
|          | Default Domains                         | 76        |
|          | Default Interface                       | 72        |
|          | Default Route distribution              | 92        |
|          | Description                             | 30, 37    |
|          | Destination Address                     | 39        |
|          | Destination IP-Address                  | 6, 34     |
|          | Destination Mask                        | 34, 39    |
|          | Destination Port                        | 9, 10, 39 |
|          | DHCP Assignment                         | 73        |
|          | Dialout                                 | 61        |
|          | Direction                               | 42, 97    |
|          | Distribution                            | 98        |
|          | Distribution Fraction (in percent)      | 31        |
|          | Distribution Mode                       | 30        |



|          |                          |                                |
|----------|--------------------------|--------------------------------|
|          | Distribution Policy      | 30, 32                         |
|          | Distribution Ratio       | 31                             |
|          | DNS                      | 11, 69                         |
|          | DNS Requests             | 81                             |
|          | DNS-Proxy                | 11                             |
|          | Domain Name              | 11                             |
|          | Domain Name Server       | 11, 69                         |
|          | Dynamic Cache            | 73                             |
|          | DynDNS Registrierung     | 83                             |
| <b>E</b> | Encryption (recommended) | 65                             |
|          | Extended Routing         | 8                              |
|          | External Address         | 17                             |
|          | External Mask            | 17                             |
|          | External Port            | 18                             |
| <b>F</b> | Filter                   | 36, 42                         |
|          | First Rule               | 44                             |
|          | Flags                    | 5                              |
|          | Forwarded Domains        | 73                             |
|          | Forwarded Requests       | 81                             |
| <b>G</b> | Garbage Collection Timer | 94                             |
|          | Gateway                  | 48                             |
|          | Gateway IP-Address       | 7, 34                          |
| <b>H</b> | Hold down timer          | 94                             |
|          | Host Name                | 85                             |
|          | HTTP TCP port            | 12                             |
| <b>I</b> | Ignore                   | 7                              |
|          | Index                    | 37, 41                         |
|          | Insert behind Rule       | 41                             |
|          | Interface                | 25, 33, 36, 44, 47, 77, 85, 96 |
|          | Interface 1 - 3          | 31                             |
|          | Interface Group ID       | 30                             |
|          | Internal Address         | 18                             |



|          |                                     |                |
|----------|-------------------------------------|----------------|
|          | Internal Mask                       | 18             |
|          | Internal Port                       | 19             |
|          | Invalid DNS Packets                 | 81             |
|          | IP Address                          | 45, 47, 58     |
|          | IP address pool LAN (DHCP)          | 47             |
|          | IP address pool WAN (PPP)           | 45             |
|          | IP-Address                          | 97             |
|          | IPCP Assignment                     | 73             |
| <b>K</b> | Kette                               | 36             |
| <b>L</b> | LAN                                 | 7, 35          |
|          | Lease Time (Minutes)                | 48             |
|          | Load Balancing                      | 23             |
|          | Local Nameservers                   | 76             |
|          | Login Authentication/Authorization  | 67             |
| <b>M</b> | MAC Address                         | 48             |
|          | Maximum Number of DNS Records       | 80             |
|          | Maximum TCP Download Rate (kbits/s) | 26             |
|          | Maximum TTL for Neg Cache Entries   | 80             |
|          | Maximum TTL for Pos Cache entries   | 80             |
|          | Metric                              | 7              |
|          | Metric1 offset on interface dormant | 98             |
|          | Metric1 offset on interface up      | 98             |
|          | Minimum Wait                        | 88             |
|          | Mode                                | 9, 10          |
|          | MX                                  | 85             |
| <b>N</b> | Name                                | 75, 76, 78, 86 |
|          | Namensauflösung                     | 69             |
|          | Negative Cache                      | 72             |
|          | NetBT Mode Type                     | 49             |
|          | Netmask                             | 6, 97          |
|          | Network                             | 6, 34          |
|          | Network Address Translation         | 14             |
|          | Next Rule                           | 42             |

|  |                       |
|--|-----------------------|
| Number of Channels   | 42                    |
| Number of consecutive addresses                            | 45, 48                |
| <b>O</b> Optimize Download Rate via TCP ACK prioritisation | 25                    |
| OSPF   | 89                    |
| Overwrite Global Nameservers                               | 72                    |
| <b>P</b> Partner / Interface                               | 7                     |
| Password   | 58, 85                |
| Path   | 87                    |
| Permission   | 86                    |
| Poisoned Reverse   | 92                    |
| Policy   | 59, 65                |
| Pool ID  | 45                    |
| Port   | 35, 59, 87            |
| Positive Cache   | 71                    |
| PPP Authentication   | 66                    |
| PPTP Passthrough   | 14                    |
| Primary BOOTP Relay Server                                 | 12                    |
| Primary Domain Name Server                                 | 11                    |
| Primary WINS   | 11                    |
| Priority   | 59, 64, 97            |
| Protocol   | 9, 16, 34, 38, 58, 87 |
| Provider   | 85                    |
| <b>R</b> RADIUS Pakete                                     | 56                    |
| Radius Server  | 55                    |
| Received DNS Packets                                       | 81                    |
| Ref  | 78                    |
| Refuse   | 7                     |
| Regel  | 36                    |
| Remote Address   | 17                    |
| Remote CAPI Server TCP port                                | 12                    |
| Remote Mask  | 17                    |
| Remote Port  | 17                    |
| Remote TRACE Server TCP port                               | 12                    |
| Resp   | 78                    |



|                            |    |
|----------------------------|----|
| Response                   | 75 |
| Retransmission timer       | 95 |
| Retries                    | 60 |
| RFC 2091 variable timer    | 93 |
| RFC 2453 variable timer    | 92 |
| RIP                        | 89 |
| RIP UDP port               | 12 |
| Route Timeout              | 94 |
| Route Type                 | 6  |
| Routing protocols          | 89 |
| Routing-Eintrag ändern     | 5  |
| Routing-Eintrag hinzufügen | 5  |

|                                       |           |
|---------------------------------------|-----------|
| <b>S</b> Secondary BOOTP Relay Server | 12        |
| Secondary Domain Name Server          | 11        |
| Secondary WINS                        | 11        |
| Server                                | 86        |
| Server Failures                       | 82        |
| Server's IP Address or Hostname       | 63        |
| Service                               | 16, 35    |
| Silent Deny                           | 14        |
| SNMP                                  | 51        |
| SNMP listen UDP port                  | 52        |
| SNMP trap broadcasting                | 53        |
| SNMP trap community                   | 53        |
| SNMP trap UDP port                    | 53        |
| SNMP versions                         | 52        |
| Source Address                        | 38        |
| Source Interface                      | 9         |
| Source IP-Address                     | 9, 34     |
| Source Mask                           | 9, 34, 38 |
| Source Port                           | 9, 10, 39 |
| Specify Port                          | 39        |
| State                                 | 60        |
| Static Hosts                          | 73        |
| Status                                | 28        |
| Successfully Answered Queries         | 82        |



|          |                             |            |
|----------|-----------------------------|------------|
| <b>T</b> | TACACS+ Accounting          | 67         |
|          | TACACS+ Key (Secret)        | 64         |
|          | TACACS+ Single-Connection   | 68         |
|          | TCP Port                    | 64         |
|          | TCP port number for UPnP    | 22         |
|          | TCP Service Port            | 28         |
|          | TDRC Mode                   | 26         |
|          | Timeout (ms)                | 60         |
|          | Timeout (seconds)           | 66         |
|          | TOS Mask                    | 9, 39      |
|          | TTL                         | 75, 77, 78 |
|          | Type                        | 34, 38     |
|          | Type of Service (TOS)       | 9, 39      |
| <b>U</b> | Unique Source IP Address    | 12         |
|          | Update Timer                | 94         |
|          | UPnP status                 | 21         |
|          | User                        | 85         |
| <b>V</b> | Validate                    | 61         |
| <b>W</b> | WAN with transit network    | 7, 35      |
|          | WAN without transit network | 7, 35      |
|          | Wildcard                    | 85         |
|          | WINS                        | 11         |



## Index: PPP

|          |                              |      |
|----------|------------------------------|------|
| <b>A</b> | Authenticaton Protocol       | 4    |
|          | Authentisierungsverhandlung  | 3    |
| <b>C</b> | Calling Party Number         | 3    |
|          | CHAP                         | 4    |
|          | CLID                         | 3, 5 |
| <b>L</b> | Link Quality Monitoring      | 6    |
| <b>M</b> | MS-CHAP                      | 4    |
| <b>P</b> | PAP                          | 4    |
|          | PPP Link Quality Monitoring  | 6    |
|          | PPPoE Ethernet Interface     | 6    |
| <b>R</b> | RADIUS                       | 5    |
|          | Radius Server Authentication | 5    |





## Index: Credits

|          |  |       |
|----------|--|-------|
| <b>G</b> | Gebühren                                       | 3     |
| <b>I</b> | ISDN Credits                                   | 5     |
|          | isdnlogin                                      | 5     |
| <b>M</b> | Maximum Charge                                 | 7     |
|          | Maximum Number of Current Incoming Connections | 8     |
|          | Maximum Number of Current Outgoing Connections | 8     |
|          | Maximum Number of Incoming Connections         | 7     |
|          | Maximum Number of Outgoing Connections         | 7, 10 |
|          | Maximum Time for Incoming Connections (sec)    | 7     |
|          | Maximum Time for Outgoing Connections (sec)    | 8, 10 |
|          | Measure Time (sec)                             | 6, 9  |
| <b>P</b> | ppp  | 5     |
|          | PPPoE  | 9     |
| <b>S</b> | Surveillance                                   | 6, 9  |
|          | Syslog-Messages                                | 3     |
| <b>T</b> | Taschengeldkonto                               | 3     |
| <b>X</b> | xDSL   | 9     |





## Index: CAPI

|          |          |   |
|----------|----------|---|
| <b>C</b> | CAPI     | 4 |
| <b>N</b> | Name     | 4 |
| <b>P</b> | Password | 4 |



## Index: ATM

|          |                        |           |
|----------|------------------------|-----------|
| <b>B</b> | Back Route Verify      | 11        |
|          | Bridging               | 10        |
| <b>D</b> | DHCP Hostname          | 9, 21     |
|          | DHCP MAC Address       | 8, 21     |
| <b>E</b> | Encapsulation          | 9, 14     |
|          | Ethernet Unit (1 - 3)  | 3         |
|          | ETH-Schnittstellen     | 3         |
| <b>I</b> | IP Accounting          | 11        |
|          | IP Configuration       | 8, 13, 21 |
| <b>L</b> | Local IP-Number        | 8, 13, 21 |
|          | Local Netmask          | 8, 13, 21 |
| <b>M</b> | MAC Address            | 9, 13, 14 |
| <b>P</b> | Proxy ARP              | 11        |
| <b>R</b> | RIP                    | 12        |
|          | V1                     | 12        |
|          | V2                     | 12        |
|          | RIP Receive            | 11        |
|          | RIP Send               | 11        |
| <b>S</b> | Second Local IP-Number | 8, 13     |
|          | Second Local Netmask   | 8, 13     |
| <b>V</b> | VLAN ID                | 9, 14     |



## Index: QoS

|          |   |        |
|----------|---|--------|
| <b>A</b> | Action                                  | 11     |
| <b>B</b> | Bound Transmit Rate (Shaping)           | 25     |
| <b>C</b> | Class                                   | 24     |
|          | Class ID                                | 12, 24 |
|          | Class Type                              | 12     |
|          | Congestion Avoidance Algorithm          | 26     |
|          | Connection State                        | 7      |
| <b>D</b> | Description                             | 6      |
|          | Destination Address                     | 7      |
|          | Destination Mask                        | 8      |
|          | Destination Port                        | 8      |
|          | Direction                               | 10     |
|          | Dropping Algorithm                      | 27     |
| <b>F</b> | Filter                                  | 10     |
| <b>I</b> | Index                                   | 6, 10  |
|          | Insert behind Rule                      | 11     |
|          | Interface                               | 18     |
|          | IP QoS Classification via               | 18     |
| <b>K</b> | Klassifizierung der IP-Pakete           | 9      |
| <b>L</b> | Lower Queue Threshold (Bytes)           | 27     |
| <b>M</b> | Maximum Burst Size (Number of Bits)     | 14     |
|          | Maximum Burst Size (Number of Packets)  | 14     |
|          | Maximum Rate (Bits per Second)          | 14     |
|          | Maximum Rate (Packets per Second)       | 14     |
|          | Maximum Transmit Rate (Bits per Second) | 22     |



|          |  |      |
|----------|--|------|
|          | MLPPP Fragment Size                    | 19   |
|          | MLPPP Interleave Mode                  | 19   |
| <b>N</b> | Next Rule                              | 11   |
| <b>P</b> | Priority                               | 26   |
|          | Protocol                               | 6    |
| <b>Q</b> | Queueing and Scheduling Algorithm      | 20   |
| <b>S</b> | Set Remark Type of Service (TOS) Field | 15   |
|          | Set Type of Service (TOS) Field        | 13   |
|          | Shaping Algorithm                      | 26   |
|          | Source Address                         | 7    |
|          | Source Mask                            | 7    |
|          | Source Port                            | 7, 8 |
|          | Specify Port                           | 7    |
|          | Specify ToS Set Exceed Action          | 14   |
|          | Specify ToS Set Rate Limitation        | 13   |
|          | Specify Traffic Shaping                | 22   |
| <b>T</b> | TOS Mask                               | 8    |
|          | Transmit Rate (Bits per Second)        | 24   |
|          | Transmit Rate Burst                    | 25   |
|          | Type                                   | 7    |
|          | Type of Service (TOS)                  | 8    |
| <b>U</b> | Upper Queue Threshold (Bytes)          | 27   |
| <b>W</b> | Weight                                 | 25   |



## Index: L2TP

|          |   |         |
|----------|---|---------|
| <b>D</b> | Data Packets Sequence Numbers                 | 12      |
| <b>H</b> | Hello Interval                                | 12      |
| <b>L</b> | L2TP-Tunnelprofile                            | 7       |
|          | LAC   | 3, 8    |
|          | LNS   | 3, 5, 8 |
|          | Local Hostname                                | 9       |
|          | Local IP Address                              | 9       |
|          | Local UDP Port (LAC only)                     | 9       |
| <b>M</b> | Maximum Retry Count                           | 13      |
|          | Maximum Time Between Retries                  | 12      |
|          | Minimum Time Between Retries                  | 12      |
| <b>P</b> | Port usage for LNS mode                       | 5       |
|          | PPP over L2TP (LAC mode)                      | 3       |
|          | PPP over L2TP (LNS mode)                      | 3       |
|          | Profile Name                                  | 8       |
| <b>R</b> | Remote Hostname                               | 11      |
|          | Remote IP Address - backup (LAC only)         | 10      |
|          | Remote IP Address (LAC only)                  | 10      |
|          | Remote IP addresses through Radius (LAC only) | 10      |
|          | Remote UDP Port (LAC only)                    | 10      |
| <b>S</b> | SCCRPs  | 9       |
|          | SCCRQs  | 9       |
|          | Schicht-2-Tunnelprotokoll                     | 3       |
| <b>T</b> | Tunnel Password                               | 11      |
| <b>U</b> | UDP port number for LNS mode                  | 5       |



# Index: Configuration Management

|          |                             |      |
|----------|-----------------------------|------|
| <b>A</b> | Aktionen                    | 3    |
|          | Arbeitsspeicher             | 3    |
| <b>B</b> | boot                        | 3    |
|          | Boot-Konfigurationsdatei    | 3    |
| <b>F</b> | Flash                       | 3    |
|          | Flash EEPROM                | 3    |
| <b>K</b> | Konfigurationsinformationen | 3    |
| <b>N</b> | Name in Flash               | 4    |
|          | New Name in Flash           | 4    |
| <b>O</b> | Operation                   | 4, 5 |
| <b>R</b> | RAM                         | 3    |
| <b>S</b> | Start Operation             | 5    |
|          | State of last operation     | 4    |
| <b>T</b> | TFTP File Name              | 4    |
|          | TFTP Server IP Address      | 4    |
|          | TFTP-Server                 | 3    |
|          | Type of last operation      | 4    |
| <b>U</b> | Unix                        | 3    |
| <b>W</b> | Windows                     | 3    |



# Index: Monitoring and Debugging

|          |                      |        |
|----------|----------------------|--------|
| <b>A</b> | Active Connections   | 16     |
|          | ADSL                 | 6      |
|          | ATM Interface        | 31     |
|          | ATM/OAM              | 6      |
| <b>C</b> | CEA                  | 29     |
|          | Charge               | 12     |
|          | Class                | 46     |
|          | Corrected blocks     | 41     |
|          | Current attenuation  | 40     |
|          | Current noise margin | 40     |
|          | Current output power | 40     |
|          | Current status       | 40     |
| <b>D</b> | Dropped Octets       | 49     |
|          | Dropped Packets      | 49     |
|          | Duration             | 16     |
| <b>E</b> | End to End           | 35, 38 |
|          | Errored seconds (ES) | 40     |
|          | EXTENDED             | 16     |
| <b>F</b> | Framing (LOF)        | 40     |
| <b>I</b> | In                   | 29     |
|          | InOctets             | 48     |
|          | InPkts               | 48     |
|          | Interface            | 43     |
|          | Interface Name       | 15     |
|          | Interfaces           | 5      |
|          | IP QoS               | 6      |
|          | IPSec                | 6, 23  |
|          | ISDN Credits         | 5      |
|          | ISDN Monitor         | 5      |

|          |  |                    |
|----------|--|--------------------|
| <b>L</b> | Local                                  | 28                 |
|          | Local ID                               | 27                 |
|          | LPort                                  | 28                 |
| <b>M</b> | Maximum Transmit Rate                  | 44                 |
|          | Messages                               | 6                  |
| <b>N</b> | Nominal Transmit Rate                  | 43                 |
|          | Number of Current Connections          | 12                 |
|          | Number of Current Incoming Connections | 12                 |
|          | Number of Current Outgoing Connections | 12                 |
|          | Number of Incoming Connections         | 11                 |
|          | Number of Outgoing Connections         | 12, 13             |
| <b>O</b> | OctetsDropped                          | 48                 |
|          | Octs                                   | 47                 |
|          | Operation                              | 16                 |
|          | Operational Status                     | 15, 31, 34, 37, 43 |
|          | Out                                    | 29                 |
|          | OutOctets                              | 48                 |
|          | OutPkts                                | 48                 |
| <b>P</b> | Packets In                             | 25                 |
|          | Peers Blocked                          | 24                 |
|          | Peers Dormant                          | 24                 |
|          | Peers Up                               | 24                 |
|          | Pkts                                   | 47                 |
|          | PktsDropped                            | 48                 |
|          | Power (LRP)                            | 40                 |
|          | Pto                                    | 28                 |
| <b>Q</b> | Queued Octets                          | 49                 |
|          | Queued Packets                         | 49                 |
| <b>R</b> | Received blocks                        | 40                 |
|          | Received Errors                        | 16, 32             |



|          |   |                |
|----------|---|----------------|
|          | Received Octets                         | 16, 31, 44     |
|          | Received Packets                        | 15, 44         |
|          | Remote                                  | 28             |
|          | Remote ID                               | 26             |
|          | Remote IP                               | 26             |
|          | RPort                                   | 29             |
|          | RX Rate (Kb/s)                          | 31             |
| <b>S</b> | SAs Phase 1                             | 24             |
|          | SAs Phase 2                             | 25             |
|          | Segment                                 | 35, 38         |
|          | Signal (LOS)                            | 40             |
|          | SSHD                                    | 6              |
|          | START OPERATION                         | 16             |
| <b>T</b> | TARSEH                                  | 26, 27         |
|          | TCP/IP                                  | 6              |
|          | Time for Incoming Connections           | 12             |
|          | Time for Outgoing Connections           | 12             |
|          | Time for Outgoing Connections (sec)     | 13             |
|          | Time till end of measure interval (sec) | 11, 13         |
|          | TOS                                     | 47             |
|          | Transmit Discards                       | 32             |
|          | Transmit Errors                         | 16, 32         |
|          | Transmit Octets                         | 16, 32, 44, 49 |
|          | Transmit Packets                        | 16, 44, 49     |
|          | Transmitted blocks                      | 41             |
|          | TX Rate (Kb/s)                          | 32             |
|          | Tx rate (Kb/s)                          | 40             |
| <b>U</b> | Uncorrect blocks                        | 41             |
| <b>V</b> | Vendor ID                               | 39             |
|          | Version Number                          | 39             |
|          | Virtual channel connection (VCC)        | 36             |
|          | Virtual path connection (VPC)           | 33             |



**X** xDSL Credits

5