



**User's Guide**  
**bintec R230a / R230aw / R232b / R232bw**  
**Ethernet**

Copyright © April 24, 2006 Funkwerk Enterprise Communications GmbH  
Version 2.0

<b>Purpose</b>	This document is part of the user's guide to the installation and configuration of bintec gateways running software release 7.2.10 or later. For up-to-the-minute information and instructions concerning the latest software release, you should always read our <b>Release Notes</b> , especially when carrying out a software update to a later release level. The latest <b>Release Notes</b> can be found at <a href="http://www.funkwerk-ec.com">www.funkwerk-ec.com</a> .		
<b>Liability</b>	While every effort has been made to ensure the accuracy of all information in this manual, Funkwerk Enterprise Communications GmbH cannot assume liability to any party for any loss or damage caused by errors or omissions or by statements of any kind in this document and is only liable within the scope of its terms of sale and delivery.  The information in this manual is subject to change without notice. Additional information, changes and <b>Release Notes</b> for bintec gateways can be found at <a href="http://www.funkwerk-ec.com">www.funkwerk-ec.com</a> .		
	As multiprotocol gateways, bintec gateways set up WAN connections in accordance with the system configuration. To prevent unintentional charges accumulating, the operation of the product should be carefully monitored. Funkwerk Enterprise Communications GmbH accepts no liability for loss of data, unintentional connection costs and damages resulting from unsupervised operation of the product.		
<b>Trademarks</b>	bintec and the bintec logo are registered trademarks of Funkwerk Enterprise Communications GmbH.  Other product names and trademarks mentioned are usually the property of the respective companies and manufacturers.		
<b>Copyright</b>	All rights are reserved. No part of this publication may be reproduced or transmitted in any form or by any means – graphic, electronic, or mechanical – including photocopying, recording in any medium, taping, or storage in information retrieval systems, without the prior written permission of Funkwerk Enterprise Communications GmbH. Adaptation and especially translation of the document is inadmissible without the prior consent of Funkwerk Enterprise Communications GmbH.		
<b>Guidelines and standards</b>	bintec gateways comply with the following guidelines and standards:  R&TTE Directive 1999/5/EG  CE marking for all EU countries and Switzerland  You will find detailed information in the Declarations of Conformity at <a href="http://www.funkwerk-ec.com">www.funkwerk-ec.com</a> .		
<b>How to reach Funkwerk Enterprise Communications GmbH</b>	<table border="1"> <tr> <td>Funkwerk Enterprise Communications GmbH Suedwestpark 94 D-90449 Nuremberg Germany  Telephone: +49 180 300 9191 0 Fax: +49 180 300 9193 0 Internet: <a href="http://www.funkwerk-ec.com">www.funkwerk-ec.com</a></td><td>Bintec France 6/8 Avenue de la Grande Lande F-33174 Gradignan France  Telephone: +33 5 57 35 63 00 Fax: +33 5 56 89 14 05 Internet: <a href="http://www.bintec.fr">www.bintec.fr</a></td></tr> </table>	Funkwerk Enterprise Communications GmbH Suedwestpark 94 D-90449 Nuremberg Germany  Telephone: +49 180 300 9191 0 Fax: +49 180 300 9193 0 Internet: <a href="http://www.funkwerk-ec.com">www.funkwerk-ec.com</a>	Bintec France 6/8 Avenue de la Grande Lande F-33174 Gradignan France  Telephone: +33 5 57 35 63 00 Fax: +33 5 56 89 14 05 Internet: <a href="http://www.bintec.fr">www.bintec.fr</a>
Funkwerk Enterprise Communications GmbH Suedwestpark 94 D-90449 Nuremberg Germany  Telephone: +49 180 300 9191 0 Fax: +49 180 300 9193 0 Internet: <a href="http://www.funkwerk-ec.com">www.funkwerk-ec.com</a>	Bintec France 6/8 Avenue de la Grande Lande F-33174 Gradignan France  Telephone: +33 5 57 35 63 00 Fax: +33 5 56 89 14 05 Internet: <a href="http://www.bintec.fr">www.bintec.fr</a>		

<b>1</b>	<b>Ethernet Menu</b>	<b>3</b>
<b>2</b>	<b>XEY-100SW, Fast Ethernet menu</b>	<b>5</b>
2.1	Fast Ethernet/en1-x Menu	5
2.2	Switch Configuration Menu	6
<b>3</b>	<b>XEY-100BT, Fast Ethernet menu</b>	<b>11</b>
3.1	Submenu Advanced Settings	15
3.2	Submenu Virtual Interfaces	18
	<b>Index: Ethernet</b>	<b>23</b>



# 1      Ethernet Menu

The fields of the **ETHERNET** menus are described below.

These menus offer different configuration options depending on the type of device for configuring the interfaces of a switch (**XEY-100SW, FAST ETHERNET**) or for configuring a separate Ethernet interface (**XEY-100BT, FAST ETHERNET**).

You will find a detailed description of your gateway's available interfaces in the User's Guide chapter **Technical Data**.



## 2 XEY-100SW, Fast Ethernet menu

The fields of the **XEY-100SW, FAST ETHERNET** menu for the Ethernet interface with integrated switch are described below.

R232bw Setup Tool	Funkwerk Enterprise Communications GmbH
[SWITCH] : Fast Ethernet Configuration	MyGateway
Fast Ethernet/en1-0>	
Switch Configuration >	
EXIT	

Your gateway offers the possibility to have the four switch ports operate as one interface (Single Interface Mode) or to operate with a logical separation and individual configuration of the four switch ports (Splitted Ports Mode).

Per default the switch is in single interface mode, i.e. there is just one configuration for all switch ports.

Configuration of the individual ports is carried out in the **FAST ETHERNET/EN1-X** submenu. Configuration of the switch (select Single Interface or Splitted Ports Mode) is carried out in the **SWITCH CONFIGURATION** submenu.

### 2.1 Fast Ethernet/en1-x Menu

The fields of the **ETHERNET/EN1-X** menu are described below.

R232bw Setup Tool		Funkwerk Enterprise Communications GmbH
[SWITCH] [SLOT 1 UNIT 0 ETH]: Configure Ethernet Interface		MyGateway
IP-Configuration	Manual	
local IP-Number	192.168.0.254	
local Netmask	255.255.255.0	
Second Local IP-Number		
Second Local Netmask		
Encapsulation	Ethernet II	
MAC Address		
Bridging		disabled
Advanced Settings >		
Virtual Interfaces >		
SAVE		CANCEL

When separating the switch ports one **FAST ETHERNET/EN1-x** menu is displayed for each splitted port which allows a completely independent configuration of the resulting interfaces. All configuration options are identical to those available for the configuration of a single Ethernet interface (see “[XEY-100BT, Fast Ethernet menu](#)” on page 11).



The Ethernet interface **en1-0** is preconfigured with **LOCAL IP-NUMBER** 192.168.0.254 and **LOCAL NETMASK** 255.255.255.0.

**Note**

## 2.2 Switch Configuration Menu

**The fields of the SWITCH CONFIGURATION menu are described below.**

In this menu you configure, whether to use the Ethernet switch of the gateway in Single Interface Mode (default) or in Splitted Ports Mode.

You can change the switch configuration in the menu **SWITCH CONFIGURATION**:

R232bw Setup Tool		Funkwerk Enterprise Communications GmbH
[SWITCH] [ASSIGN] : Switch Interface Assignment		
Switch Port	Assigned Interface	Switch Port Mode
Port 1	en1-0	full autonegotiation
Port 2	en1-0	full autonegotiation
Port 3	en1-0	full autonegotiation
Port 4	en1-0	full autonegotiation
		MyGateway
SAVE		CANCEL

The menu contains the following fields:

Field	Description
Switch Port	Here the switch port numbers are displayed. The numbering corresponds to the numbering of the ports on the rear of your gateway.
Assigned Interface	Here you can assign an ethernet interface to the switch port. Four interfaces are available: <i>en1-0</i> to <i>en1-3</i> . The default configuration assigns <i>en1-0</i> to all four switch ports.

Field	Description
Switch Port Mode	<p>Here you choose the mode the interface is to be operated in.</p> <p>Available values are:</p> <ul style="list-style-type: none"> <li>■ <i>full autonegotiation</i> (default)</li> <li>■ <i>auto 100 mbps only</i></li> <li>■ <i>auto 10 mbps only</i></li> <li>■ <i>auto 100 mbps/full duplex</i></li> <li>■ <i>auto 100 mbps/half duplex</i></li> <li>■ <i>auto 10 mbps/full duplex</i></li> <li>■ <i>auto 10 mbps/half duplex</i></li> <li>■ <i>fixed 100 mbps/full duplex</i></li> <li>■ <i>fixed 100 mbps/half duplex</i></li> <li>■ <i>fixed 10 mbps/full duplex</i></li> <li>■ <i>fixed 10 mbps/half duplex</i></li> <li>■ <i>suspend</i> - The interface is deactivated and disconnected from the power supply.</li> <li>■ <i>disabled</i> - The interface is created but remains inactive.</li> </ul>

Table 2-1: **XEY-100SW, FAST ETHERNET ➔ SWITCH CONFIGURATION**

After switch configuration, the menu **XEY-100SW, FAST ETHERNET** changes and displays the Ethernet interfaces assigned to the switch ports. You can now configure the interfaces individually. The menu offers the same options as for “[XEY-100BT, Fast Ethernet menu](#)” on page 11.

Please note: The separation of the switch ports into Ethernet interfaces is a logical one, i.e. the maximum overall bandwidth available across all switch ports or Ethernet interfaces remains unchanged (100 Mbit/s Full Duplex). If you, e.g.,

separate all switch ports, each of the resulting interfaces can use only part of the overall bandwidth.

If you collect several switch ports into a single interface, the bandwidth available between these ports is a full 100 Mbit/s Full Duplex.



### 3 XEY-100BT, Fast Ethernet menu

The fields of the **XEY-100BT, FAST ETHERNET** menu for the separate Ethernet interface is described below.

R232bw Setup Tool	Funkwerk Entreprise Communication GmbH
[SLOT 5 ETH]: Configure Ethernet Interface	MyGateway
IP-Configuration local IP-Number local Netmask	Manual
Encapsulation Mode MAC Address	none Auto
Bridging	disabled
Virtual Interfaces >	
SAVE	CANCEL

This chapter contains the settings for the separate Ethernet interface of your gateway. The Ethernet interface is a physical interface for the connection to the local network or to external networks. You give your gateway the IP address at which it is reached in the LAN resp. WAN in the **ETHERNET** menu. As long as these parameters are not entered in your gateway, it cannot be addressed by other hosts in the network.



#### Note

Please note that only the gateways **R232b** and **R232bw** are equipped with a separate Ethernet interface.

If your gateway is connected to an IP network that consists of two subnets, you should enter a **SECOND LOCAL IP NUMBER** and a **SECOND LOCAL NETMASK** for the second subnet.



The Ethernet interface *en1-0* is preconfigured with **LOCAL IP-NUMBER** 192.168.0.254 and **LOCAL NETMASK** 255.255.255.0.

**Note**

The **ETHERNET** menu consists of the following fields:

Field	Description
IP-Configuration	Possible values: <ul style="list-style-type: none"> <li>■ <b>Manual</b>: Default value. IP address and netmask must be entered (default value).</li> <li>■ <b>VLAN</b>: Allows the assignment of the Ethernet interface to a ➤➤ <b>VLAN</b>.</li> <li>■ <b>DHCP</b>: Your gateway obtains, among other values, IP address and netmask from a DHCP server.</li> </ul>
local IP-Number	IP address of your gateway in the network at the interface.
local Netmask	Netmask of the network in which your gateway with <b>LOCAL IP NUMBER</b> is located.
Second Local IP Number	Only for <b>IP CONFIGURATION Manual</b> or <b>VLAN</b> and after entering a <b>LOCAL IP-NUMBER</b> . Second IP address of your gateway in the network.
Second Local Netmask	Only for <b>IP CONFIGURATION Manual</b> or <b>VLAN</b> . Netmask of the network in which your gateway with <b>SECOND LOCAL IP NUMBER</b> is located.

Field	Description
DHCP MAC Address	<p>Only for <b>IP CONFIGURATION DHCP</b>.</p> <p>MAC address of the corresponding Ethernet interface, e.g. <i>00e1f906bf03</i>.</p> <p>Some providers use hardware-independent MAC addresses to assign their clients IP addresses dynamically. If your provider has assigned you a MAC address, enter this here.</p>
DHCP Hostname	<p>Only for <b>IP CONFIGURATION DHCP</b>.</p> <p>In this field you can enter the host name required by the provider. The maximum length of the entry is 45 characters.</p>
Encapsulation	<p>Defines the kind of header added to the IP packets that run over this interface. Possible values:</p> <ul style="list-style-type: none"> <li>■ <i>Ethernet II</i> (conforms to IEEE 802.3)</li> <li>■ <i>Ethernet SNAP</i></li> <li>■ <i>none</i> (default value)</li> </ul> <p>You can generally retain the default value <i>Ethernet II</i>. The interface is called e.g. en0-1 for <i>Ethernet II</i> and en0-1-snap for <i>Ethernet SNAP</i>.</p>
Mode	<p>Defines the mode in which the interface is operated. Possible values:</p> <ul style="list-style-type: none"> <li>■ <i>100 Mbps Full Duplex</i></li> <li>■ <i>Auto</i> (default value)</li> <li>■ <i>10 Mbps Half Duplex</i></li> <li>■ <i>10 Mbps Full Duplex</i></li> <li>■ <i>100 Mbps Half Duplex</i></li> </ul>

Field	Description
MAC Address	Only for <b>IP CONFIGURATION Manual</b> or <b>VLAN</b> . Here you can assign the interface another MAC address. This is only required for configurations that are more complex than the basic configuration, e.g. <i>00a0f906bf03</i> .
VLAN ID	Only for <b>IP CONFIGURATION VLAN</b> . Here you can assign the Ethernet interface to a VLAN by entering the relevant VLAN ID.

Field	Description
Bridging	Here you can activate <b>BRIDGING</b> for this interface. This function is only necessary for special configurations. Possible values: <i>disabled</i> (default value), <i>enabled</i> .

Table 3-1: **ETHERNET** menu fields

The menu **ETHERNET** leads to further submenus:

- **ADVANCED SETTINGS**
- **VIRTUAL INTERFACES.**

### 3.1 Submenu Advanced Settings

The fields of the **ADVANCED SETTINGS** submenu are described below.

R232bw Setup Tool	Funkwerk Entreprise Communication GmbH
[SLOT 5 ETH] [ADVANCED] : Advanced Settings	MyGateway
RIP Send	none
RIP Receive	none
IP Accounting	off
Proxy ARP	off
Back Route Verify	off
SAVE	CANCEL

The **ETHERNET → ADVANCED SETTINGS** menu contains settings for the Routing Information Protocol (RIP), IP Accounting, Proxy ARP and "Back Route Verify". The menu is only displayed if a **LOCAL IP-NUMBER** has been configured.

### Brief description of routing

The ►► **gateway** receives ►► **data packets**, each of which contains the destination host IP address. On the basis of the entries in the routing table **IP → Routing**, the gateway decides which route to use to forward the data packet to ensure that it arrives at its destination as quickly and cheaply as possible (with the fewest possible intermediate stations). The entries in the routing table can be defined statically or the routing table can be updated constantly by a dynamic exchange of routing information between several gateways. This exchange is controlled by a so-called Routing Protocol, e.g. RIP (Routing Information Protocol).

**RIP (Routing Information Protocol)** Gateways use ►► **RIP** to exchange information stored in routing tables by communicating with each other at regular intervals to mutually supplement and replace their routing entries. The **R Series** gateways support both version 1 and version 2 of RIP, either individually or together.

Gateways can be defined as active or passive gateways: active gateways store routing entries sent by other gateways and offer their routing entries to the others via ►► **broadcasts**. Passive gateways accept the information from the active gateways and store it, but do not pass on their own routing entries. The **R Series** gateways provide both variants.

**IP accounting** This option is for activating or deactivating IP accounting messages for this interface. If IP accounting is activated, accounting messages are generated (and entered in the **biboAdmSyslogTable**), which contain detailed information about the IP-connections of this interface.

**Back Route Verification** This term conceals a simple but very powerful function of the **R Series** gateways. If Backroute Verification is activated for an interface, incoming data packets are only accepted over it if outgoing answering packets would be routed over the same interface. You can therefore prevent packets with fake IP addresses being accepted – even without filters.

**Proxy ARP** The ►► **Proxy ARP** function enables the gateway to answer ►► **ARP** requests from its own LAN acting for a defined WAN partner. If a host in the LAN wants to set up a connection to another host in the LAN or to a WAN partner but doesn't know its hardware address (MAC address), it sends a so-called ARP request into the network as a ►► **broadcast**. If Proxy ARP is activated on the gateway and the desired target host can be reached e.g. over a host route, the

gateway answers the ARP request with its own hardware address. This is sufficient for establishing the connection: The **>> data packets** are sent to the gateway, which then forwards them to the desired host.

Ensure that Proxy ARP is also activated at the defined WAN partner.



#### Note

The configuration is set in the **ETHERNET UNIT → ADVANCED SETTINGS** menus:

Field	Description
RIP Send	Enables RIP packets to be sent via the Ethernet interface. Possible values: see <a href="#">table “Selection options for RIP SEND and RIP RECEIVE,” on page 18</a> , default value is <i>none</i> .
RIP Receive	For receiving RIP packets via the Ethernet interface. Possible values: see <a href="#">table “Selection options for RIP SEND and RIP RECEIVE,” on page 18</a> , default value is <i>none</i> .
IP Accounting	For generating accounting messages for e.g. <b>&gt;&gt; TCP-</b> , <b>&gt;&gt; UDP</b> and ICMP sessions. Possible values: <i>on</i> , <i>off</i> (default value).
Proxy ARP	Enables the gateway to answer ARP requests from its own LAN acting for a defined WAN partner. Possible values: <i>on</i> , <i>off</i> (default value).
Back Route Verify	Activates Backroute Verification for the Ethernet interface. Possible values: <i>on</i> , <i>off</i> (default value).

Table 3-2: **ADVANCED SETTINGS** menu fields

**RIP SEND** and **RIP RECEIVE** contain the following selection options:

Description	Meaning
none	Not activated.

Description	Meaning
RIP V2 multicast	Only for <b>RIP SEND</b> For sending RIP V2 messages over the multi-cast address 224.0.0.9.
RIP V1 triggered	RIP V1 messages are sent rsp. received and processed as per RFC 2091. (Triggered <b>&gt;&gt; RIP</b> ).
RIP V2 triggered	RIP V2 messages are sent rsp. received and processed as per RFC 2091. (Triggered <b>&gt;&gt; RIP</b> ).
RIP V1	For sending and receiving RIP packets of version 1.
RIP V2	For sending and receiving RIP packets of version 2.
RIP V1 + V2	For sending and receiving RIP packets of both version 1 and 2.

Table 3-3: Selection options for **RIP SEND** and **RIP RECEIVE**

## 3.2 Submenu Virtual Interfaces

The fields of the **VIRTUAL INTERFACES** submenu are described below.

R232bw Setup Tool	Funkwerk Entreprise Communication GmbH
[SLOT 5 ETH] [VIRTUAL] [ADD]:	Configure Virtual MyGateway LAN Interface # 1
IP Configuration	Manual
Local IP Number	
Local Netmask	
Encapsulation	none
MAC Address	00a0f9
Advanced Settings >	
SAVE	CANCEL

The virtual interfaces are shown in the **ETHERNET → VIRTUAL INTERFACES** menu.  
 In the **ETHERNET → VIRTUAL INTERFACES → ADD/EDIT** menu you configure virtual Ethernet interfaces for e.g. redundant networks.

The **VIRTUAL INTERFACES → ADD/EDIT** menu consists of the following fields:

Field	Description
IP-Configuration	Here you select one of four different configuration modes. Possible values: see table “Selection options in IP CONFIGURATION,” on page 21.
Local IP Number	Here you assign an IP address to the virtual interface.
Local Netmask	Enter the netmask for the <b>LOCAL IP-NUMBER</b> .
Second Local IP Number	Only for <b>IP CONFIGURATION Manual</b> or <b>VLAN</b> and after entering a <b>LOCAL IP-NUMBER</b> .  Second IP address of your gateway in the network.
Second Local Netmask	Only for <b>IP CONFIGURATION Manual</b> or <b>VLAN</b> .  Netmask of the network in which your gateway with <b>SECOND LOCAL IP NUMBER</b> is located.

Field	Description
Encapsulation	<p>Defines the kind of header added to the IP packets that run over this interface. Possible values:</p> <ul style="list-style-type: none"> <li>■ <i>Ethernet II</i> (conforms to IEEE 802.3, default value)</li> <li>■ <i>Ethernet SNAP</i></li> <li>■ <i>none</i></li> </ul> <p>You can generally retain the default value <i>Ethernet II</i>. The interface is called e.g. en0-1 for <i>Ethernet II</i> and en0-1-snap for <i>Ethernet SNAP</i>.</p>
MAC Address	<p>Enter the MAC address associated with the virtual interface. You can use the MAC address of the physical interface under which the virtual interface was created, but this is not necessary. You can also assign a virtual MAC address.</p> <p>In <i>VLAN</i> and <i>Manual</i> mode, the first six 6 characters of the MAC address (in <i>BRRP</i> and <i>BRRP over LAN</i> mode the first ten characters) are set as default, but can be changed.</p>
VLAN ID	<p>Is only shown if <b>IP CONFIGURATION</b> is set to <i>VLAN</i> or <i>BRRP over VLAN</i>.</p> <p>Here you assign the virtual interface to a VLAN by assigning the VLAN ID of the respective VLAN.</p> <p>Possible values are 1 (default value) to 4094.</p>

Table 3-4: **VIRTUAL INTERFACES** submenu fields

**IP CONFIGURATION** contains the following selection options:

Description	Meaning
Manual (default value)	This mode permits simple manual IP configuration.

Description	Meaning
VLAN	The assignment to a VLAN is made via the VLAN ID, which is configured in this mode. A MAC address must be defined in this mode.

Table 3-5: Selection options in **IP CONFIGURATION**

### 3.2.1 Submenu Advanced Settings

The submenu contains the same option as the **ETHERNET → ADVANCED SETTINGS** menu.

Description see “Submenu Advanced Settings” on page 15.



# Index: Ethernet

<b>A</b>	Advanced settings	15, 21
<b>B</b>	Back Route Verify	15, 16, 17
	Bridging	15
<b>D</b>	DHCP Hostname	13
	DHCP MAC address	13
<b>E</b>	Encapsulation	13, 20
	ETH interfaces	3
	Ethernet unit	3
<b>I</b>	IP accounting	15, 16, 17
	IP configuration	12, 19, 20
<b>L</b>	Local IP number	19
	local IP-Number	12
	Local netmask	19
	local Netmask	12
<b>M</b>	MAC address	14, 19, 20
	Mode	13
<b>P</b>	Proxy ARP	15, 16, 17
<b>R</b>	RIP	15, 16, 17
	V1	17
	V2	17
	RIP receive	17
	RIP send	17
	Route	15
	Routing	16
	Routing table	15

<b>S</b>	Second local IP number	12, 19
	Second local netmask	12, 19
<b>V</b>	Virtual interfaces	18
	VLAN ID	14, 20
<b>W</b>	WAN partner	16