

Index: Licenses

| | | |
|----------|---------------------------------|------|
| A | Auslieferungszustand | 4 |
| D | Description | 6 |
| H | Hardware-Seriennummer | 3 |
| K | Key | 3, 6 |
| L | LicenseSerialNumber | 3 |
| | Lizenzdaten | |
| | Freischalten von Zusatzlizenzen | 5 |
| | LicenseSerialNumber | 3 |
| | PIN | 3 |
| | Serialnumber | 3 |
| | Software License ID | 3 |
| M | Mask | 6 |
| O | Online-Lizenzierung | 3, 6 |
| P | PIN | 3 |
| S | Serialnumber | 3, 6 |
| | Software License ID | 3 |
| V | Verfügbare Subsysteme | 4 |

Index: System

Numerics

| | |
|-----------------------------|--------|
| 1. Event Index | 28 |
| A Action | 17 |
| Activity Monitor | 7 |
| C Change System Time | 36 |
| CLID | 13 |
| Client IP Address | 8 |
| Client UDP Port | 8 |
| Compare value | 25 |
| Condition | 24 |
| Contact | 4 |
| Current System Time | 36 |
| D Description | 21, 28 |
| DownAction | 15 |
| E End time | 25 |
| End value | 25 |
| Eventlist Condition | 29 |
| Execute command | 29 |
| External Activity Monitor | 7 |
| External System Logging | 9 |
| F Facility | 10 |
| FirstIfIndex | 16, 17 |
| G Group | 14 |
| Grundlegenden Systemdaten | 3 |
| H Hosts | 13 |
| I Index | 21, 28 |

| | | |
|----------|------------------------------------|--------|
| | Index value | 23, 30 |
| | Index variable | 23, 30 |
| | Interface | 17, 29 |
| | Interfaces | 13 |
| | Interval | 14 |
| | IPAddress | 14 |
| K | Keepalive Monitoring | 13 |
| L | LAN | 13 |
| | Last Change | 31 |
| | Level | 10 |
| | Local PPP ID (default) | 3 |
| | Location | 4 |
| | Log Host | 9, 10 |
| M | Maximum Number of Acctlog Entries | 5 |
| | Maximum Number of Syslog Entries | 5 |
| | Message level for the syslog table | 5 |
| | Method | 11 |
| | Mode | 28 |
| | Monitored event | 22 |
| N | Name/Address | 37 |
| | Next Index | 21 |
| | Notify | 31 |
| P | Password settings | 33 |
| | Activity Monitor | 33 |
| | admin | 33 |
| | Auslieferungszustand | 33 |
| | HTTP Server | 33 |
| | read | 33 |
| | write | 33 |
| | Protocol | 37 |
| | Protokoll der Ereignisse | 9 |

| | | |
|----------|---------------------------------|-----------|
| R | Range | 16, 18 |
| S | Set value active | 30 |
| | Source IP | 15 |
| | Start time | 25 |
| | Status | 26, 31 |
| | Subsysteme | 9 |
| | Syslog Messages | 9 |
| | Syslog output on serial console | 4 |
| | System Name | 3 |
| | System Time Offset from GMT | 37 |
| | Systemzeit | 35 |
| | Accounting | 35 |
| | automatisch | 35 |
| | manuell | 35 |
| T | Table | 22, 30 |
| | Time and Date | 35 |
| | Time Update Interval | 36 |
| | Timestamp | 11 |
| | Trials | 15 |
| | Trigger | 17 |
| | Type | 8, 10, 21 |
| U | Update Interval (sec) | 8 |
| | Update System Time from ISDN | 36 |
| V | value inactive | 30 |
| | Variable | 22, 30 |
| Z | Zentraler Server | 13 |

Index: External Systems

| | | |
|----------|-----------------------------|---------|
| A | Access Points | 3 |
| | Admin. Password | 11 |
| | AP MAC Address | 8 |
| | Authentisierungsverhandlung | 3 |
| C | Calling Party Number | 3 |
| | CLID | 3 |
| D | Discovery | 3 |
| | discovery | 7 |
| G | Gateway Address | 11 |
| I | Interface | 4, 6, 8 |
| | IP Address | 11 |
| | IP Status | 9 |
| L | Last Change | 11 |
| | Last Run | 5 |
| N | Netmask | 11 |
| | Node Name | 11 |
| O | Operation | 4, 7, 9 |
| R | Result | 5, 10 |

Index: Auxiliary

| | | |
|----------|--------------------------|---|
| A | Access Point Name (APN) | 7 |
| | Active Profile | 5 |
| | Additional Init Sequence | 7 |
| | Analog-/GSM-Interface | 3 |
| | Analoge Anschlüsse | 3 |
| G | GSM Modem | 3 |
| I | Incoming Dispatch Item | 6 |
| L | Line speed | 5 |
| M | Modem | 3 |
| | Modem Escape Character | 7 |
| P | Profile 1 bis 4 | 5 |
| | Profilkonfiguration | 5 |
| S | Serial Port | 4 |
| | SIM card uses PIN | 6 |

Index: ISDN

| | | |
|----------|--|---------|
| A | Anlagenanschluß (Point to Point) | 5 |
| B | Basic Rate Interface (BRI) | 3 |
| | B-Channel 1 | 6 |
| | B-Channel 2 | 7 |
| | Bearer | 11 |
| D | data | 11 |
| | D-Channel | 6 |
| | DOVB | 12 |
| F | Festverbindung (Leased line) | 5 |
| I | Incoming Call Answering | 9, 13 |
| | IPSec | 12 |
| | ISDN Login | 10, 12 |
| | ISDN S0 | 3 |
| | ISDN Switch Type | 3, 5, 6 |
| | Item | 11 |
| L | Leased dte, dce | 6, 7 |
| | Leased line (Festverbindung) | 5 |
| M | Mehrgeräteanschluß (Point to multipoint) | 5 |
| | Mode | 11 |
| N | Number | 11 |
| P | Point to multipoint (Mehrgeräteanschluß) | 5 |
| | Point to Point (Anlagenanschluß) | 5 |
| | PPP (routing) | 12 |
| | PPP 64k | 12 |
| | PPP V.110 (1200...38400) | 12 |

| | | |
|----------|-----------------------------|----|
| | PPP V.120 | 12 |
| R | Result of autoconfiguration | 4 |
| S | SPID B-Channel 1 | 7 |
| | SPID B-Channel 1+2 | 7 |
| | SPID B-Channel 2 | 7 |
| V | voice | 11 |

Index: Ethernet

| | | |
|----------|------------------------|-----------|
| A | Advanced Settings | 8, 15 |
| B | Back Route Verify | 8, 9, 11 |
| | Bridging | 8 |
| D | DHCP Hostname | 7 |
| | DHCP MAC Address | 7 |
| E | Encapsulation | 7, 13 |
| | Ethernet Unit (1 - 3) | 3 |
| | ETH-Schnittstellen | 3 |
| I | IP Accounting | 8, 9, 10 |
| | IP Configuration | 6, 12, 14 |
| L | Local IP-Number | 6, 12 |
| | Local Netmask | 6, 12 |
| M | MAC Address | 7, 12, 13 |
| P | Proxy ARP | 8, 10, 11 |
| R | RIP | 8, 9, 11 |
| | V1 | 11 |
| | V2 | 11 |
| | RIP Receive | 10 |
| | RIP Send | 10 |
| | Route | 8 |
| | Routing | 9 |
| | Routing-Tabelle | 8 |
| S | Second Local IP-Number | 6, 13 |
| | Second Local Netmask | 7, 13 |

| | | |
|----------|--------------------|-------|
| V | Virtual Interfaces | 12 |
| | VLAN ID | 8, 14 |
| W | WAN Partner | 9 |

Index: ADSL

| | | |
|----------|---------------------------------|---|
| A | ADSL Configured Mode | 5 |
| | ADSL Trained Mode | 4 |
| | Annex Type | 5 |
| M | Maximum threshold (kb/s) | 6 |
| P | Physical connection established | 3 |
| T | Transmit shaping | 5 |

Index: SHDSL

| | | |
|----------|-------------------------|----|
| A | Actual Line Speed | 5 |
| | Additional Wire Pairs | 8 |
| C | Clock Rate Mode | 8 |
| E | Equipment Type | 6 |
| M | Maximum Rate (kbit/s) | 10 |
| | Minimum Rate (kbit/s) | 9 |
| O | Operating Mode | 6 |
| P | Physical Connection | 5 |
| R | Requested Rate (kbit/s) | 9 |
| W | Wire Mode | 6 |

Index: Wireless LAN

| | | |
|-----------------|---------------------|------------|
| Numerics | 802.11 b/g mixed | 24 |
| A | Accept Address | 16 |
| | Access Point | 4 |
| | ACL Filter | 15 |
| | Active Probing | 7 |
| | AdminStatus | 11, 16, 21 |
| B | Bridging enable | 18 |
| C | Channel | 5 |
| D | Default Key | 12 |
| E | Ena. | 20 |
| | Enter Preshared Key | 13 |
| K | Key | 13 |
| L | local communication | 17 |
| | Local IP | 20 |
| | Local IP-Address | 22 |
| | local IP-Number | 17 |
| | Local Netmask | 22 |
| | local Netmask | 17 |
| | Location | 4 |
| M | MAC Address | 20 |
| | Max. Clients | 11 |
| | Maximum Bitrate | 24 |
| | Mode | 21 |
| N | Name is visible | 11 |

| | | |
|----------|------------------------|-------|
| | Network Name | 11 |
| | Network/Mask | 20 |
| | NITRO Burst | 25 |
| O | Operation Mode | 4 |
| P | Partner IP-Address | 22 |
| | Proxy ARP | 18 |
| R | Radio band | 5 |
| | Remote IP | 20 |
| | Remote Netmask | 22 |
| | Remote Network | 22 |
| | Remote WDS MAC Address | 22 |
| S | Second Local IP-Number | 17 |
| | Second Local Netmask | 17 |
| | Security Mode | 12 |
| | SSID | 8, 11 |
| T | Timeout (minutes) | 26 |
| | TX Power (dBm) | 25 |
| U | Usage area | 5 |
| V | vss | 7 |
| W | wds | 20 |
| | WEP | 8 |
| | Wireless Mode | 24 |
| | WPA | 8 |
| | WPA/WPA2 mixed mode | 14 |
| | WPA2 preauthentication | 14 |

Index: WAN Partner

| | | |
|----------|--------------------------------------|------------|
| A | Advanced Settings | 50 |
| | Authentication | 11 |
| | Authentisierungsverhandlung | 11 |
| B | Back Route Verification | 52 |
| | Back Route Verify | 53 |
| | Bandwidth On Demand (=BOD) | 23 |
| | Basic IP-Settings | 39 |
| | Bridge | 57 |
| | Bridging-Modus | 57 |
| C | Callback | 15, 17, 19 |
| | Calling Line Identification | 7 |
| | Channel-Bundling | 16, 18 |
| | Closed User Group | 38 |
| | Compression | 6, 7 |
| | CUG-Index | 38 |
| D | D-Channel Queue Length | 27 |
| | Default Route | 39, 42, 43 |
| | Delay after Connection Failure | 16 |
| | Delay after Connection Failure (sec) | 18 |
| | Destination IP-Address | 45, 48 |
| | Destination Port | 49, 50 |
| | Direction | 36 |
| | Dynamic Name Server Negotiation | 54, 56 |
| E | Enable NAT | 41, 43 |
| | Encapsulation | 5, 6 |
| | Encryption | 6 |
| | Encryption Key Negotiation | 28 |
| | Erweitertes IP-Routing | 46 |
| | Extended Interface Settings | 23 |
| | Extended Routing | 46 |

| | | |
|----------|-----------------------------------|----------------|
| F | Flags | 44 |
| G | Gateway IP Address | 43 |
| | Gateway IP-Address | 46 |
| | Gear Down Threshold | 26 |
| | Gear Up Threshold | 26 |
| | Geschlossene Benutzergruppe | 38 |
| I | Idle for Dynamic Short Hold (%) | 17 |
| | IP | 39 |
| | IP Accounting | 52, 53 |
| | IP Transit Network | 41 |
| | ISDN Ports to use | 36 |
| K | Keepalives | 12 |
| L | Layer 1 Protocol | 16, 18, 21 |
| | Line Utilization Sample (sec) | 26 |
| | Line Utilization Weighting | 25 |
| | Link Quality Monitoring | 12 |
| | Local IP Address | 41 |
| | Local PPP ID | 11 |
| | Local PPTP VPN IP Address | 43 |
| M | Maximum Number of Dialup Channels | 27 |
| | Metric | 46, 49 |
| | Mode | 25, 29, 48, 49 |
| | More Routing | 44 |
| N | Netmask | 46, 48 |
| | Network | 45, 46, 48 |
| | Number | 36 |
| P | Partner / Interface | 46, 48 |
| | Partner IP Address | 41 |
| | Partner Name | 5 |

| | |
|-------------------------------|------------|
| Partner PPP ID | 11 |
| Partnername | 3 |
| PPP Password | 11 |
| PPPoE Ethernet Interface | 28 |
| PPPoE Service Name | 28 |
| PPTP VPN Partner's IP Address | 42 |
| Pro | 44 |
| Protocol | 3, 49 |
| Proxy Arp | 52, 54, 55 |
| R Remote IP Address | 42 |
| Remote Netmask | 42 |
| RIP | 51 |
| RIP Receive | 53, 54 |
| RIP Send | 53, 54 |
| Route | 39 |
| Route Announce | 52, 53 |
| Route Type | 45, 48 |
| Routing-Einstellungen | 39 |
| Rufnummern des WAN Partners | 35 |
| RX Key | 28 |
| S Shorthold | 15 |
| Source Interface | 49 |
| Source IP-Address | 49 |
| Source Mask | 49 |
| Source Port | 49, 50 |
| Special Interface Types | 19 |
| State | 3 |
| Static Short Hold (sec) | 17 |
| T TOS Mask | 49 |
| Total Number of Channels | 19 |
| TX Key | 28 |
| Type of Service (TOS) | 49 |
| U Use Gateway | 43 |

V Van Jacobson Header Compression
via IP Interface

54
42

Index: Security

Numerics

| | | |
|----------|---------------------------|------------|
| | 3des | 49 |
| A | Action | 13, 23, 35 |
| | Admin Status | 8 |
| | Adminstatus | 29 |
| | aes128 | 49 |
| | aes192 | 49 |
| | aes256 | 49 |
| | Alias | 36, 38 |
| | arc4 | 49 |
| B | blowfish | 49 |
| C | cast128 | 49 |
| | Category | 11 |
| | Challenge Response | 48 |
| | ClientAliveCountMax | 46 |
| | ClientAliveInterval | 46 |
| | Compression | 43 |
| | Connection State | 19 |
| D | Day | 12 |
| | Deny Silent | 25 |
| | Description | 18 |
| | Destination | 34 |
| | Destination Address | 20 |
| | Destination Mask | 20 |
| | Destination Port | 20 |
| | Dynamische Paketfilterung | 27 |
| E | Expiring Date | 8 |
| F | Filter | 15, 16, 23 |

| | | |
|----------|--------------------------|------------|
| | Filtered Interfaces | 8 |
| | Filterliste | 10 |
| | First Rule | 25 |
| | From | 12 |
| | Full Filtering | 30 |
| H | History Entries | 9 |
| I | ICMP Type | 36 |
| | Index | 18, 22 |
| | Insert behind Rule | 22 |
| | Interface | 25, 38, 58 |
| | IP Access Lists | 28 |
| | IP Address | 38, 58 |
| | IP-Mask | 38 |
| | IP-Range | 38 |
| K | Kategorisierung | 7 |
| | Kette | 16 |
| L | Local Filter | 30 |
| | Logging Level | 31, 44 |
| | Login Grace Time | 45 |
| M | Mask | 58 |
| | Max. # of Clients | 43 |
| | md5 | 50 |
| | md5-96 | 50 |
| | Mode | 38 |
| N | NAT | 28 |
| | Netzwerkzugangskontrolle | 15 |
| | Next Rule | 23 |
| O | Orange Filter Ticket | 8 |
| | Other inactivity Timeout | 40 |

| | | |
|----------|-----------------------------|--------|
| P | Password | 48 |
| | Port | 36 |
| | Port # used for Connections | 43 |
| | PPTP inactivity Timeout | 40 |
| | Print LastLog | 44 |
| | Print Motd | 43 |
| | Priority | 13 |
| | Protocol | 19, 36 |
| | Protocol Version | 47 |
| | Public Key | 47 |
| R | Range | 37 |
| | Regel | 16 |
| | Regelketten | 21 |
| | Reihenfolge | 23 |
| | Reporting Method | 25 |
| | ripemd160 | 50 |
| S | Schnittstelle | 17 |
| | Service | 34, 57 |
| | shal | 50 |
| | shal-96 | 50 |
| | Sicherheitsfunktion | 27 |
| | SIF | 28 |
| | Source | 20, 33 |
| | Source Address | 19 |
| | Source Mask | 19 |
| | Source Port | 20 |
| | Specify Port | 20 |
| T | TCP inactivity Timeout | 39 |
| | TCP Keepalives | 45 |
| | Ticket Status | 8 |
| | To | 13 |
| | TOS Mask | 20 |
| | Type | 19 |

| | | |
|----------|--|----|
| | Type of Service (TOS) | 20 |
| U | UDP inactivity Timeout | 39 |
| | URL-basierter Content Filtering Dienst | 7 |
| V | Verify Interface | 58 |
| | Verify IP Address | 57 |
| | Verify Reverse Mapping | 43 |
| Z | Zugangsbeschränkungen | 15 |

Index: PPTP

| | | |
|----------|---------------------------------|------------|
| B | Back Route Verification | 35 |
| C | Closed User Group | 22 |
| | CUG-Index | 22 |
| D | Default Route | 26 |
| | Delay after Connection Failure | 12 |
| | Destination IP-Address | 29, 31 |
| | Destination Port | 32, 33 |
| | Direction | 19 |
| | Dynamic Name Server Negotiation | 36, 38 |
| E | Enable NAT | 26 |
| G | Geschlossene Benutzergruppe | 22 |
| I | IP Accounting | 35, 36 |
| | IP Address Negotiation | 26 |
| | ISDN Ports to use | 20 |
| M | Metric | 29, 31 |
| | Mode | 31, 32 |
| N | Netmask | 29, 31 |
| | Network | 29, 31 |
| | Number | 18 |
| P | Partner / Interface | 31 |
| | Protocol | 32 |
| | Proxy Arp | 35, 36, 37 |
| R | Remote IP Address | 27 |
| | Remote Netmask | 27 |

| | |
|-----------------------------|--------|
| RIP | 34 |
| RIP Receive | 36, 37 |
| RIP Send | 36, 37 |
| Route Announce | 35 |
| Route Type | 29, 31 |
| Routing | 34 |
| Routing-Protokoll | 34 |
| Routing-Tabelle | 34 |
| Rufnummern des WAN Partners | 17 |
| S Source Interface | 32 |
| Source IP-Address | 32 |
| Source Mask | 32 |
| Source Port | 32, 33 |
| T TOS Mask | 32 |
| Type of Service (TOS) | 32 |

Index: IPSec

Numerics

| | |
|-------------------|----------------|
| 1 (768 bit MODP) | 38, 70 |
| 2 (1024 bit MODP) | 39, 71 |
| 3DES | 32, 48, 65, 81 |
| 5 (1536 bit MODP) | 39, 71 |

A

| | |
|--|---------------|
| A | 6 |
| abort | 111 |
| ACTION | 14 |
| Action | 8, 52, 54, 57 |
| Admin Status | 12, 15 |
| aggressive | 40, 72 |
| aggressive-only | 41, 73 |
| AH (Authentication Header) | 47, 80 |
| Algorithm | 86 |
| Anpassung der IKE- und IPSec-Einstellungen | 26 |
| Authentication Method | 29, 62 |
| auto/base64/binary | 99 |
| autodetect best possible mode (D channel only) | 24 |
| autodetect best possible mode (D or B channel) | 24 |
| Autosave | 89 |

B

| | |
|------------------------------------|----------------|
| Beginn der IKE-Phase-1-Aushandlung | 22 |
| Block Time | 31, 64 |
| Blowfish | 32, 48, 65, 81 |

C

| | |
|------------------------------------|----------------|
| CA Certificates | 31, 41, 64, 73 |
| CA-Certificate | 90 |
| CA-Domain | 90 |
| CAST | 32, 48, 65, 81 |
| CEA | 121 |
| Certificate Authority Certificates | 95 |
| Certname | 92 |
| clear config | 110 |
| Cookies Size | 107 |

| | |
|---------------------------------------|-----------------------------------|
| CRL | 41, 73 |
| CRLs | 102 |
| D | |
| D-Channel Mode | 25 |
| default | 40, 72 |
| Der IPSec- Wizard Schritt für Schritt | 111 |
| DES | 32, 48, 65, 81 |
| Description | 7, 12, 15, 51, 56, 61, 86, 96, 97 |
| Description (Idx 0) | 29, 44, 77 |
| dhcp | 9, 53, 58 |
| DN | 92 |
| DNS | 92 |
| Dont Send Cert Chains | 106 |
| Dont send Cert Req Payl. | 106 |
| Dont send CRLs | 106 |
| Dont Send Initial Contact | 107 |
| Dont send Key Hash Payl. | 106 |
| drop | 54 |
| DSA Signatures | 39, 71 |
| dump messages | 110 |
| E | |
| Edit Lifetimes | 35, 68 |
| Email | 92 |
| Enable IPSec | 4 |
| Erste aktive Regel | 6 |
| ESP (Encapsulated Security Payload) | 46, 80 |
| F | |
| Filename | 92 |
| Flags | 96 |
| force Comp | 48, 81 |
| Funktionsweise | 21 |
| G | |
| Group | 29, 62 |
| H | |
| Heartbeats | 30, 45, 63, 78 |
| host | 8, 52, 57 |

| | | |
|----------|--|------------------------|
| I | id_protect | 40, 72 |
| | ID-Protect-Modus | 21 |
| | id-protect-only | 40, 72 |
| | Ignore Cert Req Payloads | 105 |
| | IKE (Phase 1) Defaults | 4 |
| | Import a Certificate/CRL using | 98 |
| | In | 121 |
| | Incoming ISDN Number | 19 |
| | Interface IP Settings | 17 |
| | Interoperabilitäts-Flags | 105 |
| | IP | 92 |
| | IPComP | 47, 80 |
| | IPsec (Phase 2) Defaults | 4 |
| | ISDN Callback | 19, 20 |
| K | Kb | 38, 70 |
| | Key Size (Bits) | 87 |
| | Key to enroll | 88 |
| | Kombination aus Verschlüsselungs- und Message Hash-Algorithmen für IKE Phase 1 | 31 |
| L | Lifetime Policy | 29, 36, 44, 62, 68, 78 |
| | LLC | 25 |
| | LLC-and-SUBADDR | 25 |
| | Local | 120 |
| | Type | 8, 51, 57 |
| | Local Address | 5, 12 |
| | Local Certificate | 31, 64 |
| | Local ID | 31, 64, 119 |
| | Local/Remote | |
| | Type | 52, 57 |
| | LPort | 120 |
| M | M/R | 6 |
| | Max. Symmetric Key Length | 107 |
| | MD5 | 49, 82 |

| | | |
|----------|-------------------------|----------------|
| | MD5 (Message Digest #5) | 33, 65 |
| | Messages | 13 |
| | Method | 89 |
| | Mode | 24, 29, 62 |
| | MODP | 38 |
| N | Name | 99 |
| | NAT Traversal | 42, 74 |
| | Nat-Traversal | 31 |
| | Nat-Traversals | 64 |
| | net | 9, 53, 58 |
| | no Comp | 48, 81 |
| | NONE | 93 |
| | NULL | 48, 49, 81, 82 |
| O | Oper Status | 12 |
| | Out | 121 |
| | Outgoing ISDN Number | 19 |
| | Own Certificates | 95 |
| | own/peer | 9, 53, 59 |
| P | Packets In | 117 |
| | pass | 54 |
| | Password | 90 |
| | Peer Address | 15 |
| | Peer Certificates | 95 |
| | Peer IDs | 16 |
| | Peers Blocked | 116 |
| | Peers Dormant | 116 |
| | Peers Up | 116 |

| | |
|--|-------------------|
| Phase 1 | |
| Authentication Method | 39, 71 |
| Group | 38, 70 |
| Lifetime Policy | 67 |
| Local Certificate | 41, 73 |
| Local ID | 41, 73 |
| Mode | 40, 72 |
| Proposal | 31, 64 |
| Phase 2 | |
| Lifetime | 50, 83 |
| Proposal | 46, 79 |
| PKCS#12-Unterstützung | 99 |
| Please enter certificate data | 98 |
| Port | 6 |
| Pre Shared Key | 16 |
| Pre Shared Keys | 39, 71 |
| Profile | 52 |
| Propagate PMTU | 46, 79 |
| Proposal | 6, 29, 44, 62, 78 |
| protect | 54 |
| Proto | 6 |
| Protocol | 7, 51, 56 |
| Pto | 120 |
| R | |
| RA-Certificate (Encrypt) | 95 |
| RA-Certificate (Sign) | 94 |
| RADIUS Authentication | 107 |
| range | 9, 53, 58 |
| Registration-Authority-Zertifikate im SCEP | 93 |
| Remote | 120 |
| Type | 8, 52, 57 |
| Remote Address | 6, 12 |
| Remote ID | 118 |
| Remote IP | 118 |
| Request Cert | 87 |
| RID | 92 |
| Rijndael | 32, 48, 65, 81 |

| | |
|---------------------|--------|
| RipeMD 160 | 33, 66 |
| RPort | 121 |
| RSA Encryption | 40, 72 |
| RSA Public Exponent | 87 |
| RSA Signatures | 39, 71 |

| | |
|---|---------|
| S SAs Phase 1 | 13, 116 |
| SAs Phase 2 | 13, 117 |
| Schritt 1 (NAT-Einstellungen) | 111 |
| Schritt 2 (Erstellung der Proposals) | 111 |
| Schritt 3 (Authentisierungsart festlegen) | 112 |
| Schritt 4 (Zertifikat beantragen) | 112 |
| Schritt 5 (Eigenes Zertifikat) | 112 |
| Schritt 6 (CA-Zertifikat) | 112 |
| Schritt 7 (CRL Server / Peer Certificate) | 113 |
| Schritt 8 (Peer) | 113 |
| Schritt 9 (Peer Traffic / Peer Interface) | 113 |
| Seconds | 38, 70 |
| Serial No | 96 |
| Server | 91, 99 |
| Setup Tool Wizard | 3 |
| SHA1 | 49, 82 |
| SHA1 (Secure Hash Algorithm #1) | 33, 66 |
| Signing algorithm to use | 91 |
| skip | 111 |
| start (wizard) | 111 |
| Start Wizard | 109 |
| State of Last Enrollment | 91 |
| SUBADDR | 25 |
| Subject Alternative Names | 92 |
| Subject Alternative Names – Type | 92 |
| Subject Alternative Names – Value | 92 |
| Subject Alternative Names (optional) | 91 |
| Subject Name | 90 |
| Subject Names | 96 |
| Sync SAs With Local Ifc | 107 |

| | | |
|----------|--|----------------|
| T | TARSEH | 118, 119 |
| | Tiger 192 | 33, 66 |
| | Traffic List Settings | 17 |
| | Transfer own IP Address over ISDN | 23 |
| | Trust ICMP Messages | 106 |
| | try specific D channel mode, fall back on B | 24 |
| | Twofish | 32, 48, 65, 81 |
| | Type | 92 |
| | Type of Certificate | 97, 98 |
| U | Übertragung der IP-Adresse | 22 |
| | URI | 92 |
| | use B channel | 24 |
| | Use PFS | 44, 50, 78, 83 |
| | use specific D channel mode | 24 |
| | Use Zero Cookies | 107 |
| V | Verfügbaren Verschlüsselungs- und Message Hash-Algorithmen | 32 |
| | View Proposals | 34, 46, 67 |
| | Virtual Interface | 17 |
| W | What to do? | 110 |

Index: IP

| | | |
|----------|---|-------------|
| A | Action | 41, 42 |
| | ADDEXT | 8 |
| | Address | 75, 78, 110 |
| | Admin Status | 105 |
| | Administrative Status | 67 |
| | Advertise Matching | 110 |
| | Alias Name (Description) | 27 |
| | Alive Check (if inactive) | 61 |
| | Alive Test Period (seconds, 0=disabled) | 49 |
| | Area ID | 105, 108 |
| | Area Range | 110 |
| | Authentication Key | 106 |
| | Authentication Type | 106 |
| B | Bandwidth Management | 21 |
| | Bandwidth on Demand | 21 |
| | Block Time (seconds) | 66 |
| | BOD | 21 |
| C | Cache Hitrate (%) | 82 |
| | Cache Hits | 81 |
| | Client / Server | 55 |
| | Client Identifier | 48 |
| | Connection State | 38 |
| | Control all TCP Services | 26 |
| D | Default Domain | 74 |
| | Default Domains | 76 |
| | Default Interface | 72 |
| | Default Route distribution | 92 |
| | Description | 29, 37 |
| | Destination Address | 39 |
| | Destination IP-Address | 6, 34 |
| | Destination Mask | 34, 39 |

| | |
|------------------------------------|-----------|
| Destination Port | 9, 10, 39 |
| DHCP Assignment | 73 |
| Dialout | 61 |
| Direction | 41, 97 |
| Distribution | 98 |
| Distribution Fraction (in percent) | 31 |
| Distribution Mode | 29 |
| Distribution Policy | 29, 31 |
| Distribution Ratio | 30 |
| DNS | 11, 69 |
| DNS Requests | 81 |
| DNS-Proxy | 11 |
| Domain Name | 11 |
| Domain Name Server | 11, 69 |
| Dynamic Cache | 73 |
| DynDNS Registrierung | 83 |
| E Encryption (recommended) | 65 |
| Export indirect static routes | 106 |
| Extended Routing | 8 |
| External Address | 17 |
| External Mask | 17 |
| External Port | 18 |
| F Filter | 36, 42 |
| First Rule | 43 |
| Flags | 5 |
| Forwarded Domains | 73 |
| Forwarded Requests | 81 |
| G Garbage Collection Timer | 94 |
| Gateway | 49 |
| Gateway IP-Address | 7, 34 |
| Generate Default Route for the AS | 102 |
| H Hold down timer | 94 |
| Host Name | 85 |

| | |
|-------------------------------------|--------------------------------|
| HTTP TCP port | 12 |
| I Ignore | 7 |
| Import external routes | 108 |
| Index | 37, 41 |
| Insert behind Rule | 41 |
| Interface | 24, 33, 36, 43, 47, 77, 85, 96 |
| Interface 1 - 3 | 30 |
| Interface Group ID | 29 |
| Internal Address | 18 |
| Internal Mask | 18 |
| Internal Port | 19 |
| Invalid DNS Packets | 81 |
| IP Address | 45, 48, 58 |
| IP address pool LAN (DHCP) | 47 |
| IP address pool WAN (PPP) | 45 |
| IP-Address | 97 |
| IPCP Assignment | 73 |
| K Kette | 36 |
| L LAN | 7, 35 |
| Lease Time (Minutes) | 48 |
| Load Balancing | 21 |
| Local | 8 |
| Local Nameservers | 76 |
| Login Authentication/Authorization | 67 |
| M MAC Address | 48 |
| Mask | 110 |
| Maximum Number of DNS Records | 80 |
| Maximum TCP Download Rate (kbits/s) | 26 |
| Maximum TTL for Neg Cache Entries | 80 |
| Maximum TTL for Pos Cache entries | 80 |
| Metric | 7, 106 |
| Metric Determination | 105, 107 |
| Metric1 offset on interface dormant | 98 |

| | | |
|----------|---|-----------------------|
| | Metric1 offset on interface up | 98 |
| | Minimum Wait | 88 |
| | Mode | 9, 10 |
| | MX | 85 |
| N | Name | 75, 76, 78, 86 |
| | Namensauflösung | 69 |
| | Negative Cache | 72 |
| | NetBT Mode Type | 49 |
| | Netmask | 6, 97 |
| | Network | 6, 34 |
| | Network Address Translation | 14 |
| | Next Rule | 42 |
| | Number of Channels | 42 |
| | Number of consecutive addresses | 45, 48 |
| O | Optimize Download Rate via TCP ACK prioritisation | 24 |
| | OSPF | 89, 102 |
| | Overwrite Global Nameservers | 72 |
| P | Partner / Interface | 7 |
| | Password | 58, 85 |
| | Path | 87 |
| | Permission | 86 |
| | Poisoned Reverse | 92 |
| | Policy | 59, 65 |
| | Pool ID | 45 |
| | Port | 35, 59, 87 |
| | Positive Cache | 71 |
| | PPP Authentication | 66 |
| | PPTP Passthrough | 14 |
| | Primary BOOTP Relay Server | 12 |
| | Primary Domain Name Server | 11 |
| | Primary WINS | 11 |
| | Priority | 59, 64, 97 |
| | Propagate Routes on discard/refuse interfaces | 103 |
| | Protocol | 9, 16, 34, 37, 58, 87 |

| | |
|---------------------------------------|--------|
| Provider | 85 |
| R RADIUS Pakete | 56 |
| Radius Server | 55 |
| Received DNS Packets | 81 |
| Ref | 78 |
| Refuse | 7 |
| Regel | 36 |
| Remote Address | 17 |
| Remote CAPI Server TCP port | 12 |
| Remote Mask | 17 |
| Remote Port | 17 |
| Remote TRACE Server TCP port | 12 |
| Resp | 78 |
| Response | 75 |
| Retransmission timer | 95 |
| Retries | 60 |
| RFC 2091 variable timer | 93 |
| RFC 2453 variable timer | 92 |
| RIP | 89 |
| RIP UDP port | 12 |
| Route Timeout | 94 |
| Route Type | 6 |
| Routing protocols | 89 |
| Routing-Eintrag ändern | 5 |
| Routing-Eintrag hinzufügen | 5 |
| S Secondary BOOTP Relay Server | 12 |
| Secondary Domain Name Server | 11 |
| Secondary WINS | 11 |
| Server | 86 |
| Server Failures | 82 |
| Server's IP Address or Hostname | 63 |
| Service | 16, 34 |
| Silent Deny | 14 |
| SNMP | 51 |
| SNMP listen UDP port | 53 |

| | |
|-----------------------------------|------------|
| SNMP trap broadcasting | 53 |
| SNMP trap community | 53 |
| SNMP trap UDP port | 53 |
| SNMP versions | 52 |
| Source Address | 38 |
| Source Interface | 9 |
| Source IP-Address | 9, 34 |
| Source Mask | 9, 34, 38 |
| Source Port | 9, 10, 38 |
| Specify Port | 39 |
| State | 60 |
| Static Hosts | 73 |
| Status | 27 |
| Successfully Answered Queries | 82 |
| T TACACS+ Accounting | 67 |
| TACACS+ Key (Secret) | 64 |
| TACACS+ Single-Connection | 68 |
| TCP Port | 64 |
| TCP Service Port | 27 |
| TDRC Mode | 25 |
| Timeout (ms) | 60 |
| Timeout (seconds) | 66 |
| TOS Mask | 9, 39 |
| TTL | 75, 77, 78 |
| Type | 33, 38, 48 |
| Type of Service (TOS) | 9, 39 |
| U Unique Source IP Address | 12 |
| Update Timer | 94 |
| User | 85 |
| V Validate | 61 |
| W WAN with transit network | 7, 35 |
| WAN without transit network | 7, 35 |
| Wildcard | 85 |

WINS

11

Index: PPP

| | | |
|----------|------------------------------|------|
| A | Authenticaton Protocol | 4 |
| | Authentisierungsverhandlung | 3 |
| C | Calling Party Number | 3 |
| | CHAP | 4 |
| | CLID | 3, 5 |
| L | Link Quality Monitoring | 6 |
| M | MS-CHAP | 4 |
| P | PAP | 4 |
| | PPP Link Quality Monitoring | 6 |
| | PPPoE Ethernet Interface | 6 |
| R | RADIUS | 5 |
| | Radius Server Authentication | 5 |

Index: BRRP

| | | |
|----------|-------------------------------|----|
| A | Advertisement Interface | 23 |
| | Advertisement Interval | 24 |
| | Advertisement Interval Errors | 31 |
| | Advertisements Received | 31 |
| | Authentication Errors | 31 |
| | Authentication Key | 27 |
| | Authentication Type | 26 |
| | Authentication Type Mismatch | 31 |
| B | Backup | 17 |
| | Become Master | 31 |
| | BRRP States | 15 |
| C | Checksum Errors | 32 |
| I | Initialize | 16 |
| | Invalid Authentication Type | 31 |
| | Invalid Type Packets Received | 32 |
| | IP Address Owner | 5 |
| | IP TTL Errors | 32 |
| M | MAC-Address | 24 |
| | MAC-Adresse | 6 |
| | Master | 18 |
| | Master Action | 12 |
| | Master Down Interval | 25 |
| | Master Interface | 13 |
| | Master Interface Protocol | 11 |
| | Master IP-Address | 23 |
| P | Packet Length Errors | 32 |
| | Pre-empt Mode | 26 |
| | Primary IP Address | 5 |
| | Priority | 23 |

| | | |
|----------|-----------------------------|----------------|
| R | Redundante Netzwerkumgebung | 3 |
| | RFC 2338 | 3 |
| | Router-Redundanzverfahren | 3 |
| S | Slave Admin Action | 14 |
| | Slave Interface | 15 |
| | Slave Interface Protocol | 13 |
| T | Task ID | 10 |
| V | Version Errors | 31 |
| | Virtual Interface | 23 |
| | Virtual Router | 5 |
| | Virtual Router Backup | 6 |
| | Virtual Router ID | 13, 15, 22, 30 |
| | Virtual Router Master | 6 |
| | Virtual Router State | 22, 31 |
| | Virtueller Router | 3 |
| | VRRP Router | 5 |
| W | Watchdog Daemon | 7, 9 |

Index: Credits

| | | |
|----------|--|-------|
| G | Gebühren | 3 |
| I | ISDN Credits | 5 |
| | isdnlogin | 5 |
| M | Maximum Charge | 7 |
| | Maximum Number of Current Incoming Connections | 8 |
| | Maximum Number of Current Outgoing Connections | 8 |
| | Maximum Number of Incoming Connections | 7 |
| | Maximum Number of Outgoing Connections | 7, 10 |
| | Maximum Time for Incoming Connections (sec) | 7 |
| | Maximum Time for Outgoing Connections (sec) | 8, 10 |
| | Measure Time (sec) | 6, 9 |
| P | ppp | 5 |
| | PPPoE | 9 |
| S | Surveillance | 6, 9 |
| | Syslog-Messages | 3 |
| T | Taschengeldkonto | 3 |
| X | xDSL | 9 |

Index: CAPI

| | | |
|----------|----------|---|
| C | CAPI | 4 |
| N | Name | 4 |
| P | Password | 4 |

Index: ATM

| | | |
|----------|------------------------|------------|
| B | Back Route Verify | 12 |
| | Bridging | 11 |
| D | DHCP Hostname | 9, 23 |
| | DHCP MAC Address | 9, 23 |
| E | Encapsulation | 9, 15 |
| | Ethernet Unit (1 - 3) | 3 |
| | ETH-Schnittstellen | 3 |
| I | IP Accounting | 12 |
| | IP Configuration | 8, 14, 23 |
| L | Local IP-Number | 8, 14, 23 |
| | Local Netmask | 8, 14, 23 |
| M | MAC Address | 10, 14, 15 |
| P | Proxy ARP | 12 |
| R | RIP | 13 |
| | V1 | 13 |
| | V2 | 13 |
| | RIP Receive | 12 |
| | RIP Send | 12 |
| S | Second Local IP-Number | 9, 14 |
| | Second Local Netmask | 9, 14 |
| V | VLAN ID | 10, 15 |

Index: QoS

| | | |
|----------|---|--------|
| A | Action | 11 |
| B | Bound Transmit Rate (Shaping) | 25 |
| C | Class | 24 |
| | Class ID | 12, 24 |
| | Class Type | 12 |
| | Congestion Avoidance Algorithm | 26 |
| | Connection State | 7 |
| D | Description | 6 |
| | Destination Address | 7 |
| | Destination Mask | 8 |
| | Destination Port | 8 |
| | Direction | 10 |
| | Dropping Algorithm | 27 |
| F | Filter | 10 |
| I | Index | 6, 10 |
| | Insert behind Rule | 11 |
| | Interface | 18 |
| | IP QoS Classification via | 18 |
| K | Klassifizierung der IP-Pakete | 9 |
| L | Lower Queue Threshold (Bytes) | 27 |
| M | Maximum Burst Size (Number of Bits) | 14 |
| | Maximum Burst Size (Number of Packets) | 14 |
| | Maximum Rate (Bits per Second) | 14 |
| | Maximum Rate (Packets per Second) | 14 |
| | Maximum Transmit Rate (Bits per Second) | 22 |

| | | |
|----------|--|------|
| | MLPPP Fragment Size | 19 |
| | MLPPP Interleave Mode | 19 |
| N | Next Rule | 11 |
| P | Priority | 26 |
| | Protocol | 6 |
| Q | Queueing and Scheduling Algorithm | 20 |
| S | Set Remark Type of Service (TOS) Field | 15 |
| | Set Type of Service (TOS) Field | 13 |
| | Shaping Algorithm | 26 |
| | Source Address | 7 |
| | Source Mask | 7 |
| | Source Port | 7, 8 |
| | Specify Port | 7 |
| | Specify ToS Set Exceed Action | 14 |
| | Specify ToS Set Rate Limitation | 13 |
| | Specify Traffic Shaping | 22 |
| T | TOS Mask | 8 |
| | Transmit Rate (Bits per Second) | 24 |
| | Transmit Rate Burst | 25 |
| | Type | 7 |
| | Type of Service (TOS) | 8 |
| U | Upper Queue Threshold (Bytes) | 27 |
| W | Weight | 25 |

Index: GRE

| | | |
|----------|-------------------------------|---|
| G | Generic Routing Encapsulation | 3 |
| | GRE Local IP Address | 4 |
| | GRE Partner's IP Address | 4 |
| | GRE V.0 | 3 |
| | GRE V.1 | 3 |
| K | Key Used | 5 |
| M | Mtu | 5 |
| N | Name | 4 |
| P | Partner's LAN IP Address | 4 |
| | Partner's LAN IP Mask | 4 |
| V | Value | 5 |
| | Virtuelles Interface | 3 |

Index: L2TP

| | | |
|----------|---|---------|
| D | Data Packets Sequence Numbers | 12 |
| H | Hello Interval | 12 |
| L | L2TP-Tunnelprofile | 7 |
| | LAC | 3, 8 |
| | LNS | 3, 5, 8 |
| | Local Hostname | 9 |
| | Local IP Address | 9 |
| | Local UDP Port (LAC only) | 9 |
| M | Maximum Retry Count | 13 |
| | Maximum Time Between Retries | 12 |
| | Minimum Time Between Retries | 12 |
| P | Port usage for LNS mode | 5 |
| | PPP over L2TP (LAC mode) | 3 |
| | PPP over L2TP (LNS mode) | 3 |
| | Profile Name | 8 |
| R | Remote Hostname | 11 |
| | Remote IP Address - backup (LAC only) | 10 |
| | Remote IP Address (LAC only) | 10 |
| | Remote IP addresses through Radius (LAC only) | 10 |
| | Remote UDP Port (LAC only) | 10 |
| S | SCCRPs | 9 |
| | SCCRQs | 9 |
| | Schicht-2-Tunnelprotokoll | 3 |
| T | Tunnel Password | 11 |
| U | UDP port number for LNS mode | 5 |

Index: Configuration Management

| | | |
|----------|-----------------------------|------|
| A | Aktionen | 3 |
| | Arbeitsspeicher | 3 |
| B | boot | 3 |
| | Boot-Konfigurationsdatei | 3 |
| F | Flash | 3 |
| | Flash EEPROM | 3 |
| K | Konfigurationsinformationen | 3 |
| N | Name in Flash | 4 |
| | New Name in Flash | 4 |
| O | Operation | 4, 5 |
| R | RAM | 3 |
| S | Start Operation | 5 |
| | State of last operation | 4 |
| T | TFTP File Name | 4 |
| | TFTP Server IP Address | 4 |
| | TFTP-Server | 3 |
| | Type of last operation | 4 |
| U | Unix | 3 |
| W | Windows | 3 |

Index: Monitoring and Debugging

| | | |
|----------|-------------------------------|------------|
| A | Active Connections | 16 |
| | Admin Status | 38 |
| | Adminstatus | 21 |
| | ADSL | 6 |
| | Advertisement Interval Errors | 61 |
| | Advertisements Received | 61 |
| | Age | 41 |
| | Area | 40 |
| | ATM Interface | 43 |
| | ATM/OAM | 6 |
| | Authentication Errors | 61 |
| | Authentication Type Mismatch | 61 |
| B | Backup Designed Router (BDR) | 38 |
| | Become Master | 61 |
| | BRRP | 6 |
| C | CEA | 35 |
| | Charge | 12 |
| | Checksum Errors | 62 |
| | Class | 67 |
| | Compress | 24 |
| | Contents | 23 |
| | Corrected blocks | 53 |
| | CRC anomalies | 57 |
| | Current attenuation | 52 |
| | Current loop attenuation | 57 |
| | Current noise margin | 52 |
| | Current output power | 52 |
| | Current SNR margin | 57 |
| | Current status | 52, 56, 57 |
| D | Designed Router (DR) | 38 |
| | Dropped Octets | 69 |

| | | |
|----------|----------------------------------|------------|
| | Dropped Packets | 69 |
| | Duration | 16 |
| E | End to End | 47, 50 |
| | Errored seconds (ES) | 52, 57 |
| | EXTENDED | 16 |
| F | Framing (LOF) | 52 |
| I | In | 35 |
| | InOctets | 68 |
| | InPkts | 68 |
| | Interface | 37, 39, 63 |
| | Interface Name | 15 |
| | Interfaces | 5, 37 |
| | Invalid Authentication Type | 61 |
| | Invalid Type Packets Received | 62 |
| | IP QoS | 6 |
| | IP TTL Errors | 62 |
| | IPSec | 6, 29 |
| | ISDN Credits | 5 |
| | ISDN Monitor | 5 |
| L | Level | 23 |
| | Link State ID | 41 |
| | Local | 34 |
| | Local ID | 33 |
| | Loss of sync word (LOSW) seconds | 57 |
| | LPort | 34 |
| | LSDB | 40 |
| M | max. Mails/min | 22 |
| | Maximum Transmit Rate | 64 |
| | Messages | 6, 24 |
| N | Neighbor | 39 |
| | Nominal Transmit Rate | 64 |

| | | |
|----------|--|--------------------|
| | Number of Current Connections | 12 |
| | Number of Current Incoming Connections | 12 |
| | Number of Current Outgoing Connections | 12 |
| | Number of Incoming Connections | 11 |
| | Number of Outgoing Connections | 12, 13 |
| O | OctetsDropped | 68 |
| | Octs | 67 |
| | Operation | 16 |
| | Operational Status | 15, 43, 46, 49, 63 |
| | Originator | 22 |
| | Out | 35 |
| | OutOctets | 68 |
| | OutPkts | 68 |
| P | Packet Lenght Errors | 62 |
| | Packets In | 31 |
| | Peers Blocked | 30 |
| | Peers Dormant | 30 |
| | Peers Up | 30 |
| | Pkts | 67 |
| | PktsDropped | 68 |
| | Power (LRP) | 52 |
| | Pto | 34 |
| Q | Queued Octets | 69 |
| | Queued Packets | 69 |
| R | Received blocks | 52, 57 |
| | Received Errors | 16, 44 |
| | Received Octets | 16, 43, 64 |
| | Received Packets | 15, 64 |
| | Receiver | 23 |
| | Remote | 34 |
| | Remote ID | 32 |
| | Remote IP | 32 |
| | Retx Queue | 39 |

| | | |
|----------|---|----------------|
| | Router ID | 39, 41 |
| | RPort | 35 |
| | RX Rate (Kb/s) | 43 |
| S | SAs Phase 1 | 30 |
| | SAs Phase 2 | 31 |
| | Segment | 47, 50 |
| | Select subsystems | 24 |
| | Sequence | 41 |
| | Severely errored seconds (SES) | 57 |
| | SHDSL | 6 |
| | SHDSL interface | 55 |
| | Signal (LOS) | 52 |
| | SMTP Server | 22 |
| | SSHD | 6 |
| | START OPERATION | 16 |
| | State | 38, 39, 40 |
| T | TARSEH | 32, 33 |
| | TCP/IP | 6 |
| | Time for Incoming Connections | 12 |
| | Time for Outgoing Connections | 12 |
| | Time for Outgoing Connections (sec) | 13 |
| | Time till end of measure interval (sec) | 11, 13 |
| | Timeout | 24 |
| | TOS | 68 |
| | Transmit Discards | 44 |
| | Transmit Errors | 16, 44 |
| | Transmit Octets | 16, 44, 64, 69 |
| | Transmit Packets | 16, 64, 69 |
| | Transmitted blocks | 53, 57 |
| | TX Rate (Kb/s) | 44 |
| | Tx rate (Kb/s) | 52 |
| | Type | 40 |
| U | Unavailable seconds (UAS) | 57 |
| | Uncorrect blocks | 53 |

| | | |
|----------|----------------------------------|----|
| V | Vendor ID | 51 |
| | Version Errors | 61 |
| | Version Number | 51 |
| | Virtual channel connection (VCC) | 48 |
| | Virtual path connection (VPC) | 45 |
| | Virtual Router ID | 60 |
| | Virtual Router State | 61 |
| X | xDSL Credits | 5 |

