



Index: Licenses

A	Available subsystems	4
D	Description	5
E	Ex works state	4
H	Hardware serial number	3
K	Key	3, 5
L	License data	
	Activating extra licenses	5
	License serial number	3
	PIN	3
	Serial number	3
	Software license ID	3
	License serial number	3
M	Mask	5
O	Online licensing	3, 6
P	PIN	3
S	Serial number	3, 5
	Software license ID	3





Index: System

Numerics	1st Event index	30
A	Action	19
	Activity Monitor	7
B	Basic system data	3
C	Central server	13
	CLID	13, 14
	Client IP address	8
	Client UDP port	8
	Compare value	26
	Condition	26
	Contact	4
	Current time	38
D	Description	22, 29
	DownAction	16
E	End time	27
	End value	27
	Event protocol	9
	Eventlist condition	30
	Execute command	31
	External Activity Monitor	7
	External system logging	9
F	Facility	10
	FirstIfIndex	16, 19
G	Group	15
H	Hosts	14



I	Index	22, 29
	Index value	25, 31
	Index variable	25, 31
	Interface	18, 31
	Interfaces	14
	Interval	15
	IP address	15
K	Keepalive Monitoring	13
L	LAN	13
	Last change	33
	Level	10
	Local PPP ID (default)	3
	Location	4
	Log host	9, 10
M	Maximum number of syslog entries	5
	Message level for the syslog table	5
	Mode	30
	Monitored event	24
N	New date	38
	New Time	38
	New time	38
	Next index	23
	Notify	32
P	Password settings	35
	Activity Monitor	35
	admin	35
	Ex works state	35
	HTTP server	35
	read	35
	write	35



R	Range	17, 19
S	Set value active	32
	Source IP	15
	Start time	27
	Status	27, 32
	Subsystems	9
	Syslog messages	9
	Display	3
	Number	3
	Priority	3
	Syslog output on serial console	4
	System name	3
	System time	37
	Accounting	37
	Automatic	37
	Manual	37
T	Table	24, 31
	Time and date	37
	Time is currently controlled by	38
	Timestamp	11
	Trigger	18
	Type	8, 10, 23
U	Update interval	8
V	Value inactive	32
	Variable	25, 31



Index: Ethernet

A	Advanced settings	7, 13
B	Back Route Verify	7, 8, 9
	Bridging	6
D	DHCP MAC address	4
E	Encapsulation	5
	ETH interfaces	3
	Ethernet unit	3
I	IP accounting	7, 8, 9
	IP configuration	4, 11, 12
L	Local IP number	11
	Local netmask	11
M	MAC address	5, 11, 12
	Mode	5
P	Proxy ARP	7, 8, 9
R	RIP	7, 9
	V1	9
	V2	9
	RIP receive	9
	RIP send	8
	Route	7
	Routing	7
	Routing table	7
S	Second local IP number	4
	Second local netmask	4



V	Virtual interfaces	11
	VLAN ID	5, 12
W	WAN partner	8



Index: ISDN

B	B-channel 1	6
	B-channel 2	6
	Bearer	11
	BRI	3
D	D-channel	6
I	IPSec	12
	ISDN Login	9, 12
	ISDN switch type	5, 6
	Item	11
L	leased dte, dce	6
	Leased line	5
M	Mode	11
N	Number	11
P	Point to multipoint	5
	Point to point	5
	PPP (routing)	9, 12
	PPP DOVB	12
R	Result of autoconfiguration	4
S	SPID B-channel 1	7
	SPID B-channel 1+2	7
	SPID B-channel 2	7





Index: AUX

A	Active profile	5
	Analog connections	3
	Analog/GSM interface	3
D	Dispatch item	6
E	Escape char	7
G	GSM modem	3, 7
	GSM SIM PIN	7
I	Init sequence	7
L	Line speed	5
M	Modem	3
P	Profile	5
	Profile configuration	5
S	Serial port	4



Index: WAN Partner

A	Advanced settings	48
	Authentication	11
	Authentication negotiation	11
B	Back Route Verification	50
	Back Route Verify	51
	Bandwidth on Demand (BoD)	22
	Basic IP settings	37
	Bridge	55
	Bridging Mode	55
	C	Callback
Calling Line Identification		7
Channel bundling		16, 18
Closed User Group		35
Compression		6, 7
CUG index		35
D		D-channel queue length
	Default route	37, 40, 41
	Delay after connection failure	16
	Delay after connection failure (sec)	17
	Destination IP address	43, 46
	Destination port	47
	Direction	34
	Dynamic Name Server Negotiation	52, 53
	E	Enable NAT
Encapsulation		5, 6
Encryption		6
Encryption key (RX)		26
Encryption key (TX)		26
Encryption key negotiation		26
Extended interface settings		22



	Extended IP routing	44
	Extended routing	44
F	Flags	41
G	Gateway IP Address	41
	Gateway IP address	44
	Gear down threshold	24
	Gear up threshold	24
I	Idle for dynamic short hold (%)	17
	IP	37
	IP accounting	50, 51
	IP transit network	39
	ISDN ports to use	34
K	Keepalives	12
L	Layer 1 protocol	16, 17, 21
	Line utilization sample (sec)	24
	Line utilization weighting	23
	Link Quality Monitoring	12
	Local IP address	39
	Local PPP ID	11
	Local PPTP VPN IP Address	41
M	Maximum number of dialup channels	25
	Metric	44, 46
	Mode	23, 26, 46
	More routing	41
N	Netmask	44, 46
	Network	43, 44, 46
	Number	33
P	Partner / Interface	46



Partner IP address	39
Partner name	3, 5
Partner PPP ID	11
PPP password	11
PPTP VPN Partner's IP Address	40
Pro	41
Protocol	3, 47
Proxy ARP	50, 51, 53
R Remote IP address	40
Remote netmask	40
Remote X.25 address	18
RIP	49
RIP receive	51, 52
RIP send	51, 52
Route	37
Route announce	50, 51
Route type	43, 45
Routing settings	37
S Short hold	15
Source interface	46
Source IP address	46
Source mask	46
Source port	47, 48
Special interface types	19
State	3
Static short hold (sec)	17
T TOS mask	46
Total number of channels	18
Type of Service (TOS)	46
U Use Gateway	40
V Van Jacobson Header Compression via IP Interface	52 40



W WAN partner numbers

33



Index: Security

Numerics

3des	44
A	
Access restrictions	13
Action	11, 20, 31
Admin status	6, 27
Adminstatus	27
aes128	44
aes192	44
aes256	44
Alias	32, 34
arc4	44
B	
blowfish	44
C	
cast128	44
Category	9
Chain	14
Challenge response	43
Classification	5
ClientAliveCountMax	41
ClientAliveInterval	42
Compression	39
Connection state	17
D	
Day	10
Deny Silent	23
Description	16
Destination	30
Destination address	18
Destination mask	18
Destination port	18
Dynamic packet filtering	25

E	Expiring date	6
F	Filter	13, 14, 20
	Filter list	8
	Filtered interfaces	6
	First rule	23
	From	10
	Full filtering	28
H	History entries	7
I	ICMP type	32
	Index	16, 20
	Insert behind Rule	20
	Interface	14, 23, 35, 51
	IP access lists	26
	IP address	34, 51
	IP mask	35
	IP range	34
L	Local filter	27
	Logging level	28, 40
	Login Grace Time	41
M	Mask	51
	Max. # of Clients	38
	md5	45
	md5-96	45
	Mode	34
N	NAT	26
	Network access control	13
	Next rule	21
O	Orange filter ticket	6
	Order	21



	Other inactivity timeout	36
P	Password	43
	Port	33
	Port # used for Connections	38
	PPTP inactivity Timeout	36
	Print LastLog	39
	Print Motd	39
	Priority	11
	Protocol	16, 32
	Protocol version	43
	Public key	43
R	Range	33
	Reporting method	23
	ripemd160	45
	Rule chains	19
S	Safety feature	25
	Service	31, 50
	shal	45
	shal-96	45
	SIF	26
	Source	18, 30
	Source address	17
	Source mask	17
	Source port	17, 18
	Specify Port	17
T	TCP inactivity Timeout	36
	TCP Keepalives	41
	Ticket status	6
	To	11
	TOS mask	18
	Type	17
	Type of Service (TOS)	18



U	UDP inactivity Timeout	36
	URL-based content filtering service	5
V	Verify interface	51
	Verify IP address	50
	Verify reverse mapping	39

Index: PPTP

B	Back Route Verification	34
	Back Route Verify	35
C	Closed User Group	20
	CUG index	20
D	Default route	26
	Delay after connection failure	12
	Destination IP address	28, 30
	Destination port	31, 32
	Direction	18
	Dynamic Name Server Negotiation	36, 37
E	Enable NAT	26
I	IP accounting	34, 35
	ISDN ports to use	19
M	Metric	29, 31
	Mode	31
N	Netmask	29, 30
	Network	28, 30
	Number	17
P	Protocol	31
	Proxy Arp	34, 35, 37
R	Remote IP address	26
	Remote netmask	26
	RIP	33
	RIP receive	35, 36
	RIP send	35, 36
	Route announce	34, 35



	Route type	28, 30
	Routing	33
	Routing protocol	33
	Routing table	33
S	Source interface	31
	Source IP address	31
	Source mask	31
	Source port	31, 32
T	TOS mask	31
	Type of Service (TOS)	31
W	WAN partner numbers	17

Index: IPsec

Numerics

1 (768-bit MODP)	31, 58
2 (1024-bit MODP)	31, 58
3DES	27, 40, 54, 67
5 (1536-bit MODP)	32, 59

A

A	6
abort	91
Action	8, 43, 45, 49
Admin status	12
aggressive	33, 60
aggressive-only	33, 60
AH (Authentication Header)	39, 66
Algorithm	70
Authentication method	52
auto/base64/binary	80
Autosave	74
Available encryption and message hash algorithms	27

B

Block time	53
Blowfish	27, 40, 54, 67

C

CA certificate	73
CA certificates	34, 53, 61
CA domain	74
CAST	27, 40, 54, 67
CEA	101
Certificate authority certificates	76
Certname	75
clear config	90
Combination of encryption and message hash algorithms for IKE phase 1	26
Cookies size	87
CRL	34, 61
CRLs	81

D	default	33, 60
	DES	27, 40, 54, 67
	Description	7, 11, 43, 48, 51, 70, 77, 78
	Description (Idx 1)	63
	dhcp	9, 44, 50
	Direct ISDN call	15
	DN	76
	DNS	76
	Don't Send Cert Chains	86
	Don't Send Cert Req Payl.	86
	Don't Send CRLs	86
	Don't Send Initial Contact	86
	Don't Send Key Hash Payl.	86
	drop	45
	DSA signatures	32, 59
	dump messages	90
	DynDNS service	15
E	Email	76
	Enable IPsec	4
	ESP (Encapsulated Security Payload)	38, 65
F	First active rule	6
	Flags	77
	force Comp	40, 67
	Force trusted	80
G	Group	52
H	Heartbeats	37, 52, 64
	host	8, 44, 49
I	ID Protect Mode	18
	id_protect	33, 60
	id-protect-only	33, 60
	Ignore Cert Req Payloads	85



IKE (Phase 1) defaults	4
Import a certificate/CRL using	79
In	101
Incoming ISDN number	16
Interoperability flags	85
IP	76
IP address transfer	18
IPComP	39, 66
IPsec (Phase 2) defaults	4
ISDN callback	16
K Kb	57
Key size (bits)	71
Key to enroll	72
L Lifetime	36, 52, 63
Lifetime restriction based on	57
Local	100
Type	7, 43, 48
Local address	5
Local certificate	53
Local ID	53, 98
Local/Remote	
Type	44, 49
LPort	100
M M/R	6
Matching policy	58
Max. Symmetric Key Length	87
MD5	40, 67
MD5 (Message Digest #5)	27, 54
Method	73
Method of operation	18
Mode	52
Modifying IKE and IPsec settings	23
MODP	31

N	Name	80
	Nat-Traversal	26, 53
	net	8, 44, 49
	no Comp	39, 66
	NULL	40, 67
O	Oper status	12
	Out	101
	Outgoing ISDN number	16
	Own certificates	76
	own/peer	9, 45, 50
P	Packets in	97
	pass	45
	Password	74
	Peer address	12
	Peer certificates	76
	Peer IDs	13
	Peers blocked	96
	Peers dormant	96
	Peers up	96
	Phase 1	
	Authentication method	32, 59
	Group	31, 58
	Lifetime	56
	Local certificate	34, 61
	Local ID	34, 60
	Mode	33, 60
	NAT Traversal	34
	Proposal	26, 53
	Phase 2	
	Lifetime	41, 68
	Proposal	38, 65
	Please enter certificate data	80
	Port	6
	Preshared key	13



Preshared keys	32, 59
Profile	43
Propagate PMTU	38, 65
Proposal	6, 36, 52, 63
protect	45
Proto	6
Protocol	7, 43, 48
Pto	100
R RADIUS authentication	87
range	9, 44, 50
Remote	100
Type	8, 43, 48
Remote address	6
Remote ID	98
Remote IP	98
Request cert	71
RID	76
Rijndael	27, 40, 54, 67
RipeMD 160	28, 55
RPort	100
RSA encryption	32, 59
RSA Public Exponent	71
RSA signatures	32, 59
S SAs phase 1	96
SAs phase 2	96
Seconds	57
Serial no.	77
Server	75, 80
Setup Tool Wizard	3
SHA1	40, 67
SHA1 (Secure Hash Algorithm #1)	28, 55
skip	91
start (wizard)	91
Start of IKE phase 1 negotiation	18
State of last enrollment	75



Step 1 (NAT settings)	91
Step 2 (creation of proposals)	91
Step 3 (define authentication method)	91
Step 4 (request certificate)	92
Step 5 (own certificate)	92
Step 6 (CA certificate)	92
Step 7 (CRL server / peer certificate)	92
Step 8 (peer)	93
Step 9 (peer traffic / peer interface)	93
Subject Alternative Names	75
Subject Alternative Names – Type	75
Subject Alternative Names – Value	75
Subject Alternative Names (optional)	74
Subject name	74, 77
Sync SAs With Local Ifc	87
T TARSEH	98, 99
The IPsec Wizard step by step	91
Tiger 192	28, 55
Transfer own IP address over ISDN:	16
Trust ICMP Messages	86
Twofish	27, 40, 54, 67
Type	76
Type of certificate	78, 79
U URI	76
Use PFS	36, 41, 63, 68
Use Zero Cookies	87
V View proposals	28, 38, 55
Virtual interface	14
W What to do?	90



Index: PPP

A	Authentication Negotiation	3
	Authentication Protocol	4
C	Calling party number	3
	CHAP	4
	CLID	3, 5
L	Link Quality Monitoring	5
M	MS-CHAP	4
P	PAP	4
	PPP Link Quality Monitoring	5
	PPPoE Ethernet Interface	6
R	RADIUS	5
	Radius Server Authentication	5

