

Index: Licenses

A	Auslieferungszustand	4
D	Description	6
H	Hardware-Seriennummer	3
K	Key	3, 6, 7
L	LicenseSerialNumber	3
	Lizenzdaten	
	Freischalten von Zusatzlizenzen	6
	LicenseSerialNumber	3
	PIN	3
	Serialnumber	3
	Software License ID	3
M	Mask	6
O	Online-Lizenzierung	3, 7
P	PIN	3
S	Serialnumber	3, 6
	Software License ID	3
V	Verfügbare Subsysteme	4

Index: System

Numerics

1. Event Index	29
A Action	18
Activity Monitor	7
C Change System Time	36
CLID	13
Client IP Address	8
Client UDP Port	8
Compare value	26
Condition	25
Contact	4
Current System Time	36
D Description	21, 29
DownAction	15
E End time	26
End value	26
Eventlist Condition	30
Execute command	30
External Activity Monitor	7
External System Logging	9
F Facility	10
FirstIfIndex	16, 18
G Group	14
Grundlegenden Systemdaten	3
H Hosts	13
I Index	21, 29

	Index value	24, 31
	Index variable	24, 31
	Interface	17, 30
	Interfaces	13
	Interval	14
	IPAddress	14
K	Keepalive Monitoring	13
L	LAN	13
	Last Change	32
	Level	10
	Local PPP ID (default)	3
	Location	4
	Log Host	9, 10
M	Maximum Number of Acctlog Entries	5
	Maximum Number of Syslog Entries	5
	Message level for the syslog table	5
	Method	11
	Mode	29
	Monitored event	23
N	Name/Address	37
	Next Index	22
	Notify	32
P	Password settings	33
	Activity Monitor	33
	admin	33
	Auslieferungszustand	33
	HTTP Server	33
	read	33
	write	33
	Protocol	37
	Protokoll der Ereignisse	9

R	Range	16, 18
S	Set value active	31
	Source IP	15
	Start time	26
	Status	27, 32
	Subsysteme	9
	Syslog Messages	9
	Syslog output on serial console	4
	System Name	3
	System Time Offset from GMT	37
	Systemzeit	35
	Accounting	35
	automatisch	35
	manuell	35
T	Table	23, 31
	Time and Date	35
	Time Update Interval	36
	Timestamp	11
	Trials	15
	Trigger	17
	Type	8, 10, 22
U	Update Interval (sec)	8
	Update System Time from ISDN	36
V	value inactive	31
	Variable	23, 31
Z	Zentraler Server	13

Index: External Systems

A	Access Points	3
	Admin. Password	11
	AP MAC Address	8
	Authentisierungsverhandlung	3
C	Calling Party Number	3
	CLID	3
D	Discovery	3
	discovery	7
G	Gateway Address	11
I	Interface	4, 6, 8
	IP Address	11
	IP Status	9
L	Last Change	10
	Last Run	5
N	Netmask	11
	Node Name	10
O	Operation	4, 7, 9
R	Result	5, 10

Index: Auxiliary

A	Access Point Name (APN)	7
	Active Profile	5
	Additional Init Sequence	7
	Analog-/GSM-Interface	3
	Analoge Anschlüsse	3
G	GSM Modem	3
I	Incoming Dispatch Item	6
L	Line speed	5
M	Modem	3
	Modem Escape Character	7
P	Profile 1 bis 4	5
	Profilkonfiguration	5
S	Serial Port	4
	SIM card uses PIN	6

Index: Ethernet

A	Advanced Settings	8, 15
B	Back Route Verify	8, 10, 11
	Bridging	8
D	DHCP Hostname	7
	DHCP MAC Address	7
E	Encapsulation	7, 14
	Ethernet Unit (1 - 3)	3
	ETH-Schnittstellen	3
I	IP Accounting	8, 10, 11
	IP Configuration	6, 13, 15
L	Local IP-Number	6, 13
	Local Netmask	6, 13
M	MAC Address	7, 13, 14
P	Proxy ARP	8, 10, 11
R	RIP	8, 9, 11
	V1	11
	V2	11
	RIP Receive	11
	RIP Send	11
	Route	8
	Routing	9
	Routing-Tabelle	8
S	Second Local IP-Number	6, 13
	Second Local Netmask	7, 13

V	Virtual Interfaces	12
	VLAN ID	8, 14
W	WAN Partner	10

Index: ISDN

A	Anlagenanschluß (Point to Point)	5
B	Basic Rate Interface (BRI)	3
	B-Channel 1	6
	B-Channel 2	7
	Bearer	11
D	data	11
	D-Channel	6
	DOVB	12
F	Festverbindung (Leased line)	5
I	Incoming Call Answering	9, 13
	IPSec	12
	ISDN Login	10, 12
	ISDN S0	3
	ISDN Switch Type	3, 5, 6
	Item	11
L	Leased dte, dce	6, 7
	Leased line (Festverbindung)	5
M	Mehrgeräteanschluß (Point to multipoint)	5
	Mode	11
N	Number	11
P	Point to multipoint (Mehrgeräteanschluß)	5
	Point to Point (Anlagenanschluß)	5
	PPP (routing)	12
	PPP 64k	12
	PPP V.110 (1200...38400)	12

	PPP V.120	12
R	Result of autoconfiguration	4
S	SPID B-Channel 1	7
	SPID B-Channel 1+2	7
	SPID B-Channel 2	7
V	voice	11

Index: ADSL

A	ADSL Configured Mode	5
	ADSL Trained Mode	4
	Annex Type	5
M	Maximum threshold (kb/s)	6
P	Physical connection established	3
T	Transmit shaping	5

Index: SHDSL

A	Actual Line Speed	6
	Additional Wire Pairs	9
C	Clock Rate Mode	9
E	Equipment Type	6
M	Maximum Rate (kbit/s)	10
	Minimum Rate (kbit/s)	10
O	Operating Mode	6
P	Physical Connection	5
R	Requested Rate (kbit/s)	11
W	Wire Mode	7

Index: Wireless LAN

Numerics	802.11 b/g mixed	24
A	Accept Address	16
	Access Point	4
	ACL Filter	15
	Active Probing	7
	AdminStatus	11, 16, 21
B	Bridging enable	18
C	Channel	5
D	Default Key	12
E	Ena.	20
	Enter Preshared Key	13
K	Key	13
L	local communication	17
	Local IP	20
	Local IP-Address	22
	local IP-Number	17
	Local Netmask	22
	local Netmask	17
	Location	4
M	MAC Address	20
	Max. Clients	11
	Maximum Bitrate	24
	Mode	21
N	Name is visible	11

	Network Name	11
	Network/Mask	20
	NITRO Burst	25
O	Operation Mode	4
P	Partner IP-Address	22
	Proxy ARP	18
R	Radio band	5
	Remote IP	20
	Remote Netmask	22
	Remote Network	22
	Remote WDS MAC Address	22
S	Second Local IP-Number	17
	Second Local Netmask	18
	Security Mode	12
	SSID	8, 11
T	Timeout (minutes)	26
	TX Power (dBm)	25
U	Usage area	5
V	vss	7
W	wds	20
	WEP	8
	Wireless Mode	24
	WPA	8
	WPA/WPA2 mixed mode	14
	WPA2 preauthentication	14

Index: WAN Partner

A	Advanced Settings	52
	Authentication	11
	Authentisierungsverhandlung	11
B	Back Route Verification	54
	Back Route Verify	55
	Bandwidth On Demand (=BOD)	25
	Basic IP-Settings	41
	Bridge	59
	Bridging-Modus	59
C	Callback	15, 17, 20
	Calling Line Identification	7
	Channel-Bundling	16, 19
	Closed User Group	40
	Compression	6, 7
	CUG-Index	40
D	D-Channel Queue Length	28
	Default Route	41, 44, 45
	Delay after Connection Failure	16
	Delay after Connection Failure (sec)	18
	Destination IP-Address	47, 50
	Destination Port	51, 52
	Direction	38
	Dynamic Name Server Negotiation	56, 58
	E	Enable NAT
Encapsulation		5, 6
Encryption		6
Encryption Key Negotiation		29
Erweitertes IP-Routing		48
Extended Interface Settings		25
Extended Routing		48

F	Flags	46
G	Gateway IP Address	45
	Gateway IP-Address	48
	Gear Down Threshold	27
	Gear Up Threshold	27
	Geschlossene Benutzergruppe	40
	GPRS/UMTS Interface	18
I	Idle for Dynamic Short Hold (%)	17
	IP	41
	IP Accounting	54, 55
	IP Transit Network	43
	ISDN Ports to use	38
K	Keepalives	12
L	Layer 1 Protocol	16, 18, 22
	Line Utilization Sample (sec)	27
	Line Utilization Weighting	26
	Link Quality Monitoring	12
	Local IP Address	43
	Local PPP ID	11
	Local PPTP VPN IP Address	45
M	Maximum Number of Dialup Channels	28
	Metric	48, 51
	Mode	26, 30, 50, 51
	More Routing	46
N	Netmask	48, 50
	Network	47, 48, 50
	Number	38
P	Partner / Interface	48, 50
	Partner IP Address	43

Partner Name	5
Partner PPP ID	11
Partnername	3
PPP Password	11
PPPoE Ethernet Interface	29
PPPoE Service Name	29
PPTP VPN Partner's IP Address	44
Pro	46
Protocol	3, 51
Proxy Arp	54, 56, 57
R	
Remote IP Address	44
Remote Netmask	44
RIP	53
RIP Receive	55, 56
RIP Send	55, 56
Route	41
Route Announce	54, 55
Route Type	47, 50
Routing-Einstellungen	41
Rufnummern des WAN Partners	37
RX Key	29
S	
Shorthold	15
Source Interface	51
Source IP-Address	51
Source Mask	51
Source Port	51, 52
Special Interface Types	20
State	3
Static Short Hold (sec)	17
T	
TOS Mask	51
Total Number of Channels	19
TX Key	29
Type of Service (TOS)	51

U	Use Gateway	45
V	Van Jacobson Header Compression via IP Interface	56 44

Index: Security

Numerics

	3des	47
A	Action	11, 21, 33
	Admin Status	6
	Adminstatus	27
	aes128	47
	aes192	47
	aes256	47
	Alias	34, 36
	arc4	47
B	blowfish	47
C	cast128	47
	Category	9
	Challenge Response	46
	ClientAliveCountMax	44
	ClientAliveInterval	44
	Compression	41
	Connection State	17
D	Day	10
	Deny Silent	23
	Description	16
	Destination	32
	Destination Address	18
	Destination Mask	18
	Destination Port	18
	Dynamische Paketfilterung	25
E	Expiring Date	6
F	Filter	13, 14, 21

	Filtered Interfaces	6
	Filterliste	8
	First Rule	23
	From	10
	Full Filtering	28
H	History Entries	7
I	ICMP Type	34
	Index	16, 20
	Insert behind Rule	20
	Interface	23, 36, 56
	IP Access Lists	26
	IP Address	36, 56
	IP-Mask	36
	IP-Range	36
K	Kategorisierung	5
	Kette	14
L	Local Filter	28
	Logging Level	29, 42
	Login Grace Time	43
M	Mask	56
	Max. # of Clients	41
	md5	48
	md5-96	48
	Mode	36
N	NAT	26
	Netzwerkzugangskontrolle	13
	Next Rule	21
O	Orange Filter Ticket	6
	Other inactivity Timeout	38

P	Password	46
	Port	34
	Port # used for Connections	41
	PPTP inactivity Timeout	38
	Print LastLog	42
	Print Motd	41
	Priority	11
	Protocol	17, 34
	Protocol Version	45
	Public Key	45
R	Range	35
	Regel	14
	Regelketten	19
	Reihenfolge	21
	Reporting Method	23
	ripemd160	48
S	Schnittstelle	15
	Service	32, 55
	shal	48
	shal-96	48
	Sicherheitsfunktion	25
	SIF	26
	Source	18, 31
	Source Address	17
	Source Mask	17
	Source Port	18
	Specify Port	18
T	TCP inactivity Timeout	37
	TCP Keepalives	43
	Ticket Status	6
	To	11
	TOS Mask	18
	Type	17

	Type of Service (TOS)	18
U	UDP inactivity Timeout	37
	URL-basierter Content Filtering Dienst	5
V	Verify Interface	56
	Verify IP Address	55
	Verify Reverse Mapping	41
Z	Zugangsbeschränkungen	13

Index: PPTP

B	Back Route Verification	37
	Back Route Verify	38
C	Closed User Group	24
	CUG-Index	24
D	Default Route	28
	Delay after Connection Failure	14
	Destination IP-Address	31, 33
	Destination Port	34, 35
	Direction	21
	Dynamic Name Server Negotiation	39, 41
E	Enable NAT	28
G	Geschlossene Benutzergruppe	24
I	IP Accounting	37, 38
	IP Address Negotiation	28
	ISDN Ports to use	22
M	Metric	31, 34
	Mode	33, 34
N	Netmask	31, 33
	Network	31, 33
	Number	20
P	Partner / Interface	33
	Protocol	34
	Proxy Arp	37, 39, 40
R	Remote IP Address	29

Remote Netmask	29
RIP	36
RIP Receive	38, 39
RIP Send	38, 39
Route Announce	37, 39
Route Type	31, 33
Routing	36
Routing-Protokoll	36
Routing-Tabelle	36
Rufnummern des WAN Partners	19
S Source Interface	34
Source IP-Address	34
Source Mask	34
Source Port	34, 35
T TOS Mask	34
Type of Service (TOS)	34

Index: IPSec

Numerics

1 (768 bit MODP)	38, 70
2 (1024 bit MODP)	39, 71
3DES	32, 48, 65, 81
5 (1536 bit MODP)	39, 71

A

A	6
abort	111
ACTION	14
Action	8, 52, 54, 57
Admin Status	12, 15
aggressive	40, 72
aggressive-only	41, 73
AH (Authentication Header)	47, 80
Algorithm	86
Anpassung der IKE- und IPSec-Einstellungen	26
Authentication Method	29, 62
auto/base64/binary	99
autodetect best possible mode (D channel only)	24
autodetect best possible mode (D or B channel)	24
Autosave	89

B

Beginn der IKE-Phase-1-Aushandlung	22
Block Time	31, 64
Blowfish	32, 48, 65, 81

C

CA Certificates	31, 41, 64, 73
CA-Certificate	90
CA-Domain	90
CAST	32, 48, 65, 81
CEA	121
Certificate Authority Certificates	95
Certname	92
clear config	110
Cookies Size	107

CRL	41, 73
CRLs	102
D	
D-Channel Mode	25
default	40, 72
Der IPSec- Wizard Schritt für Schritt	111
DES	32, 48, 65, 81
Description	7, 12, 15, 51, 56, 61, 86, 96, 97
Description (Idx 0)	29, 44, 77
dhcp	9, 53, 58
DN	92
DNS	92
Dont Send Cert Chains	106
Dont send Cert Req Payl.	106
Dont send CRLs	106
Dont Send Initial Contact	107
Dont send Key Hash Payl.	106
drop	54
DSA Signatures	39, 71
dump messages	110
E	
Edit Lifetimes	35, 68
Email	92
Enable IPSec	4
Erste aktive Regel	6
ESP (Encapsulated Security Payload)	46, 80
F	
Filename	92
Flags	96
force Comp	48, 81
Funktionsweise	21
G	
Group	29, 62
H	
Heartbeats	30, 45, 63, 78
host	8, 52, 57

I	id_protect	40, 72
	ID-Protect-Modus	21
	id-protect-only	40, 72
	Ignore Cert Req Payloads	105
	IKE (Phase 1) Defaults	4
	Import a Certificate/CRL using	98
	In	121
	Incoming ISDN Number	19
	Interface IP Settings	17
	Interoperabilitäts-Flags	105
	IP	92
	IPComP	47, 80
	IPsec (Phase 2) Defaults	4
	ISDN Callback	19, 20
K	Kb	38, 70
	Key Size (Bits)	87
	Key to enroll	88
	Kombination aus Verschlüsselungs- und Message Hash-Algorithmen für IKE Phase 1	31
L	Lifetime Policy	29, 36, 44, 62, 68, 78
	LLC	25
	LLC-and-SUBADDR	25
	Local	120
	Type	8, 51, 57
	Local Address	5, 12
	Local Certificate	31, 64
	Local ID	31, 64, 119
	Local/Remote	
	Type	52, 57
	LPort	120
M	M/R	6
	Max. Symmetric Key Length	107
	MD5	49, 82

	MD5 (Message Digest #5)	33, 65
	Messages	13
	Method	89
	Mode	24, 29, 62
	MODP	38
N	Name	99
	NAT Traversal	42, 74
	Nat-Traversal	31
	Nat-Traversals	64
	net	9, 53, 58
	no Comp	48, 81
	NONE	93
	NULL	48, 49, 81, 82
O	Oper Status	12
	Out	121
	Outgoing ISDN Number	19
	Own Certificates	95
	own/peer	9, 53, 59
P	Packets In	117
	pass	54
	Password	90
	Peer Address	15
	Peer Certificates	95
	Peer IDs	16
	Peers Blocked	116
	Peers Dormant	116
	Peers Up	116

Phase 1	
Authentication Method	39, 71
Group	38, 70
Lifetime Policy	67
Local Certificate	41, 73
Local ID	41, 73
Mode	40, 72
Proposal	31, 64
Phase 2	
Lifetime	50, 83
Proposal	46, 79
PKCS#12-Unterstützung	99
Please enter certificate data	98
Port	6
Pre Shared Key	16
Pre Shared Keys	39, 71
Profile	52
Propagate PMTU	46, 79
Proposal	6, 29, 44, 62, 78
protect	54
Proto	6
Protocol	7, 51, 56
Pto	120
R	
RA-Certificate (Encrypt)	95
RA-Certificate (Sign)	94
RADIUS Authentication	107
range	9, 53, 58
Registration-Authority-Zertifikate im SCEP	93
Remote	120
Type	8, 52, 57
Remote Address	6, 12
Remote ID	118
Remote IP	118
Request Cert	87
RID	92
Rijndael	32, 48, 65, 81

RipeMD 160	33, 66
RPort	121
RSA Encryption	40, 72
RSA Public Exponent	87
RSA Signatures	39, 71

S SAs Phase 1	13, 116
SAs Phase 2	13, 117
Schritt 1 (NAT-Einstellungen)	111
Schritt 2 (Erstellung der Proposals)	111
Schritt 3 (Authentisierungsart festlegen)	112
Schritt 4 (Zertifikat beantragen)	112
Schritt 5 (Eigenes Zertifikat)	112
Schritt 6 (CA-Zertifikat)	112
Schritt 7 (CRL Server / Peer Certificate)	113
Schritt 8 (Peer)	113
Schritt 9 (Peer Traffic / Peer Interface)	113
Seconds	38, 70
Serial No	96
Server	91, 99
Setup Tool Wizard	3
SHA1	49, 82
SHA1 (Secure Hash Algorithm #1)	33, 66
Signing algorithm to use	91
skip	111
start (wizard)	111
Start Wizard	109
State of Last Enrollment	91
SUBADDR	25
Subject Alternative Names	92
Subject Alternative Names – Type	92
Subject Alternative Names – Value	92
Subject Alternative Names (optional)	91
Subject Name	90
Subject Names	96
Sync SAs With Local Ifc	107

T	TARSEH	118, 119
	Tiger 192	33, 66
	Traffic List Settings	17
	Transfer own IP Address over ISDN	23
	Trust ICMP Messages	106
	try specific D channel mode, fall back on B	24
	Twofish	32, 48, 65, 81
	Type	92
	Type of Certificate	97, 98
U	Übertragung der IP-Adresse	22
	URI	92
	use B channel	24
	Use PFS	44, 50, 78, 83
	use specific D channel mode	24
	Use Zero Cookies	107
V	Verfügbaren Verschlüsselungs- und Message Hash-Algorithmen	32
	View Proposals	34, 46, 67
	Virtual Interface	17
W	What to do?	110

Index: IP

A	Action	43, 44
	ADDEXT	10
	Address	77, 80, 112
	Admin Status	107
	Administrative Status	70
	Advertise Matching	112
	Alias Name (Description)	29
	Alive Check (if inactive)	64
	Alive Test Period (seconds, 0=disabled)	51
	Area ID	107, 110
	Area Range	112
	Authentication Key	108
	Authentication Type	108
B	Bandwidth Management	23
	Bandwidth on Demand	23
	Block Time (seconds)	69
	BOD	23
C	Cache Hitrate (%)	84
	Cache Hits	83
	Client / Server	57
	Client Identifier	50
	Connection State	40
	Control all TCP Services	28
D	Default Domain	76
	Default Domains	78
	Default Interface	74
	Default Route distribution	94
	Description	31, 39
	Destination Address	41
	Destination IP-Address	8, 36
	Destination Mask	36, 41

Destination Port	11, 12, 41
DHCP Assignment	75
Dialout	63
Direction	43, 99
Distribution	100
Distribution Fraction (in percent)	33
Distribution Mode	31
Distribution Policy	31, 33
Distribution Ratio	32
DNS	13, 71
DNS Requests	83
DNS-Proxy	13
Domain Name	13
Domain Name Server	13, 71
Dynamic Cache	75
DynDNS Registrierung	85
E Encryption (recommended)	68
Export indirect static routes	108
Extended Routing	10
External Address	19
External Mask	19
External Port	20
F Filter	38, 44
First Rule	45
Flags	7
Forwarded Domains	75
Forwarded Requests	83
G Garbage Collection Timer	96
Gateway	51
Gateway IP-Address	9, 36
Generate Default Route for the AS	104
H Hold down timer	96
Host Name	87

HTTP TCP port	14
I Ignore	9
Import external routes	110
Index	39, 43
Insert behind Rule	43
Interface	26, 35, 38, 45, 49, 79, 87, 98
Interface 1 - 3	32
Interface Group ID	31
Internal Address	20
Internal Mask	20
Internal Port	21
Invalid DNS Packets	83
IP Address	47, 50, 60
IP address pool LAN (DHCP)	49
IP address pool WAN (PPP)	47
IP-Address	99
IPCP Assignment	75
K Kette	38
L LAN	9, 37
Lease Time (Minutes)	50
Load Balancing	23
Local	10
Local Nameservers	78
Login Authentication/Authorization	69
M MAC Address	50
Mask	112
Maximum Number of DNS Records	82
Maximum TCP Download Rate (kbits/s)	28
Maximum TTL for Neg Cache Entries	82
Maximum TTL for Pos Cache entries	82
Metric	9, 108
Metric Determination	107, 109
Metric1 offset on interface dormant	100

	Metric1 offset on interface up	100
	Minimum Wait	90
	Mode	11, 12
	MX	87
N	Name	77, 78, 80, 88
	Namensauflösung	71
	Negative Cache	74
	NetBT Mode Type	51
	Netmask	8, 99
	Network	8, 36
	Network Address Translation	16
	Next Rule	44
	Number of Channels	44
	Number of consecutive addresses	47, 50
O	Optimize Download Rate via TCP ACK prioritisation	26
	OSPF	91, 104
	Overwrite Global Nameservers	74
P	Partner / Interface	9
	Password	60, 87
	Path	89
	Permission	88
	Poisoned Reverse	94
	Policy	61, 67
	Pool ID	47
	Port	37, 61, 89
	Positive Cache	73
	PPP Authentication	69
	PPTP Passthrough	16
	Primary BOOTP Relay Server	14
	Primary Domain Name Server	13
	Primary WINS	13
	Priority	61, 66, 99
	Propagate Routes on discard/refuse interfaces	105
	Protocol	11, 18, 36, 39, 60, 89

Provider	87
R RADIUS Pakete	58
Radius Server	57
Received DNS Packets	83
Ref	80
Refuse	9
Regel	38
Remote Address	19
Remote CAPI Server TCP port	14
Remote Mask	19
Remote Port	19
Remote TRACE Server TCP port	14
Resp	80
Response	77
Retransmission timer	97
Retries	62
RFC 2091 variable timer	95
RFC 2453 variable timer	94
RIP	91
RIP UDP port	14
Route Timeout	96
Route Type	8
Routing protocols	91
Routing-Eintrag ändern	7
Routing-Eintrag hinzufügen	7
S Secondary BOOTP Relay Server	14
Secondary Domain Name Server	13
Secondary WINS	13
Server	88
Server Failures	84
Server's IP Address or Hostname	66
Service	18, 36
Silent Deny	16
SNMP	53
SNMP listen UDP port	55

SNMP trap broadcasting	55
SNMP trap community	55
SNMP trap UDP port	55
SNMP versions	54
Source Address	40
Source Interface	11
Source IP-Address	11, 36
Source Mask	11, 36, 40
Source Port	11, 12, 40
Specify Port	41
State	62
Static Hosts	75
Status	29
Successfully Answered Queries	84
T TACACS+ Accounting	69
TACACS+ Key (Secret)	67
TACACS+ Single-Connection	70
TCP Port	67
TCP Service Port	29
TDRC Mode	27
Timeout (ms)	62
Timeout (seconds)	68
TOS Mask	11, 41
TTL	77, 79, 80
Type	35, 40, 50
Type of Service (TOS)	11, 41
U Unique Source IP Address	14
Update Timer	96
User	87
V Validate	63
W WAN with transit network	9, 37
WAN without transit network	9, 37
Wildcard	87

WINS

13

Index: PPP

A	Authenticaton Protocol	4
	Authentisierungsverhandlung	3
C	Calling Party Number	3
	CHAP	4
	CLID	3, 5
L	Link Quality Monitoring	6
M	MS-CHAP	4
P	PAP	4
	PPP Link Quality Monitoring	6
	PPPoE Ethernet Interface	6
R	RADIUS	5
	Radius Server Authentication	5

Index: X.25

A	Allow Incoming XOT Calls	46
B	Back Route Verification	39
	Back Route Verify	40
C	Closed User Group	79
	CUG-Index	79
D	Default Route	30
	Delay after Connection Failure	27
	Delay after Connection Failure (sec)	27
	Destination IP-Address	32, 35
	Destination Link	21
	Destination Link Address (LLC)	21
	Destination Port	36, 37, 47
	Destination X.25 Address	21
	Disconnect Timeout	17
E	Enable NAT	30
	Erweitertes IP-Routing	33
	Extended Routing	33
G	Gateway IP-Address	33
	Geschlossene Benutzergruppe	79
H	Highest Two-Way-Channel (HTC)	16
I	Incoming Partner Source IP Address	47
	Interface Name	46
	IP Accounting	39, 40
	IP Transit Network	29
L	L2 Window Size	16

	L3 Mode	14
	L3 Packet Size	14
	L3 Window Size	14
	Layer 2 Behaviour	16
	Link	14
	Local IP Address	29
	Local X.25 Address	11
	Logical Channel Number 0	15
	Lowest Two-Way-Channel (LTC)	16
M	Mask	47
	Max Number of XOT Links	47
	Metric	21, 33, 36
	Mode	35, 36
	MTU	48
N	Netmask	33, 35
	Network	32, 33, 35
O	Outgoing Partner Destination IP Address	47
P	Packet Switching	3
	Paketvermittelt	4
	Partner / Interface	33, 35
	Partner IP Address	29
	Protocol	36
	Proxy Arp	39, 41, 42
R	Remote IP Address	30
	Remote Netmask	30
	RIP	38
	RIP Receive	40, 41
	RIP Send	40, 41
	Route Announce	39, 41
	Route Type	32, 35

S	Shorthold	27
	Sicher	4
	Source Interface	36
	Source IP Address	47
	Source IP-Address	36
	Source Link	21
	Source Mask	36
	Source Port	36, 37
T	Static Short Hold (sec)	27
	TOS Mask	36
V	Type of Service (TOS)	36
	Van Jacobson Header Compression	41
W	Verbindungsorientiert	3
	Window size/Packetsize Neg.	15
X	XOT TCP port	12

Index: FR

B	Back Route Verification	31
	Back Route Verify	32
D	Default Route	22
	Destination IP-Address	24, 27
	Destination Port	28, 29
E	Enable NAT	22
	Erweitertes IP-Routing	25
	Extended Routing	25
G	Gateway IP-Address	25
I	IP Accounting	31, 32
	IP Transit Network	21
L	Local IP Address	21
M	Metric	25, 28
	Mode	27, 28
N	Netmask	25, 27
	Network	24, 25, 27
P	Partner / Interface	25, 27
	Partner IP Address	21
	Protocol	28
	Proxy Arp	31, 33, 34
R	Remote IP Address	22
	Remote Netmask	22
	RIP	30
	RIP Receive	32, 33

	RIP Send	32, 33
	Route Announce	31, 33
	Route Type	24, 27
S	Source Interface	28
	Source IP-Address	28
	Source Mask	28
	Source Port	28, 29
T	TOS Mask	28
	Type of Service (TOS)	28
V	Van Jacobson Header Compression	33

Index: BRRP

A	Advertisement Interface	23
	Advertisement Interval	24
	Advertisement Interval Errors	31
	Advertisements Received	31
	Authentication Errors	31
	Authentication Key	27
	Authentication Type	26
	Authentication Type Mismatch	31
B	Backup	17
	Become Master	31
	BRRP States	15
C	Checksum Errors	32
I	Initialize	16
	Invalid Authentication Type	31
	Invalid Type Packets Received	32
	IP Address Owner	5
	IP TTL Errors	32
M	MAC-Address	24
	MAC-Adresse	6
	Master	18
	Master Action	12
	Master Down Interval	25
	Master Interface	13
	Master Interface Protocol	11
	Master IP-Address	23
P	Packet Length Errors	32
	Pre-empt Mode	26
	Primary IP Address	5
	Priority	23

R	Redundante Netzwerkumgebung	3
	RFC 2338	3
	Router-Redundanzverfahren	3
S	Slave Admin Action	14
	Slave Interface	15
	Slave Interface Protocol	13
T	Task ID	10
V	Version Errors	31
	Virtual Interface	23
	Virtual Router	5
	Virtual Router Backup	6
	Virtual Router ID	12, 15, 22, 30
	Virtual Router Master	6
	Virtual Router State	22, 31
	Virtueller Router	3
	VRRP Router	5
W	Watchdog Daemon	7, 9

Index: Credits

G	Gebühren	3
I	ISDN Credits	5
	isdnlogin	5
M	Maximum Charge	7
	Maximum Number of Current Incoming Connections	8
	Maximum Number of Current Outgoing Connections	8
	Maximum Number of Incoming Connections	7
	Maximum Number of Outgoing Connections	7, 10
	Maximum Time for Incoming Connections (sec)	7
	Maximum Time for Outgoing Connections (sec)	8, 10
	Measure Time (sec)	6, 9
P	ppp	5
	PPPoE	9
S	Surveillance	6, 9
	Syslog-Messages	3
T	Taschengeldkonto	3
X	xDSL	9

Index: CAPI

C	CAPI	4
N	Name	4
P	Password	4

Index: ATM

B	Back Route Verify	12
	Bridging	11
D	DHCP Hostname	9, 23
	DHCP MAC Address	9, 23
E	Encapsulation	9, 15
	Ethernet Unit (1 - 3)	3
	ETH-Schnittstellen	3
I	IP Accounting	12
	IP Configuration	8, 14, 23
L	Local IP-Number	8, 14, 23
	Local Netmask	8, 14, 23
M	MAC Address	10, 14, 15
P	Proxy ARP	12
R	RIP	13
	V1	13
	V2	13
	RIP Receive	12
	RIP Send	12
S	Second Local IP-Number	9, 14
	Second Local Netmask	9, 14
V	VLAN ID	10, 15

Index: QoS

A	Action	11
B	Bound Transmit Rate (Shaping)	25
C	Class	24
	Class ID	12, 24
	Class Type	12
	Congestion Avoidance Algorithm	26
	Connection State	7
D	Description	6
	Destination Address	7
	Destination Mask	8
	Destination Port	8
	Direction	10
	Dropping Algorithm	27
F	Filter	10
I	Index	6, 10
	Insert behind Rule	11
	Interface	18
	IP QoS Classification via	18
K	Klassifizierung der IP-Pakete	9
L	Lower Queue Threshold (Bytes)	27
M	Maximum Burst Size (Number of Bits)	14
	Maximum Burst Size (Number of Packets)	14
	Maximum Rate (Bits per Second)	14
	Maximum Rate (Packets per Second)	14
	Maximum Transmit Rate (Bits per Second)	22

	MLPPP Fragment Size	19
	MLPPP Interleave Mode	19
N	Next Rule	11
P	Priority	26
	Protocol	6
Q	Queueing and Scheduling Algorithm	20
S	Set Remark Type of Service (TOS) Field	15
	Set Type of Service (TOS) Field	13
	Shaping Algorithm	26
	Source Address	7
	Source Mask	7
	Source Port	7, 8
	Specify Port	7
	Specify ToS Set Exceed Action	14
	Specify ToS Set Rate Limitation	13
	Specify Traffic Shaping	22
T	TOS Mask	8
	Transmit Rate (Bits per Second)	24
	Transmit Rate Burst	25
	Type	7
	Type of Service (TOS)	8
U	Upper Queue Threshold (Bytes)	27
W	Weight	25

Index: VoIP

A	Adminstatus	6
D	Destination Port	7
E	Echtzeitverhalten	3
H	H.323-Standard	3
L	Low Latency Transmission	7
P	Protocol	7
	Proxy Settings	6
	Proxy Type	6
S	Sprach- und Bildübertragung	3

Index: GRE

G	Generic Routing Encapsulation	3
	GRE Local IP Address	4
	GRE Partner's IP Address	4
	GRE V.0	3
	GRE V.1	3
K	Key Used	5
M	Mtu	5
N	Name	4
P	Partner's LAN IP Address	4
	Partner's LAN IP Mask	4
V	Value	5
	Virtuelles Interface	3

Index: L2TP

D	Data Packets Sequence Numbers	12
H	Hello Interval	12
L	L2TP-Tunnelprofile	7
	LAC	3, 8
	LNS	3, 5, 8
	Local Hostname	9
	Local IP Address	9
	Local UDP Port (LAC only)	9
M	Maximum Retry Count	13
	Maximum Time Between Retries	12
	Minimum Time Between Retries	12
P	Port usage for LNS mode	5
	PPP over L2TP (LAC mode)	3
	PPP over L2TP (LNS mode)	3
	Profile Name	8
R	RADIUS Group ID	10
	Remote Hostname	11
	Remote IP Address - backup (LAC only)	10
	Remote IP Address (LAC only)	10
	Remote IP addresses through Radius (LAC only)	10
	Remote UDP Port (LAC only)	10
S	SCCRPs	9
	SCCRQs	9
	Schicht-2-Tunnelprotokoll	3
T	Tunnel Password	11

U UDP port number for LNS mode

5

Index: Configuration Management

A	Aktionen	3
	Arbeitsspeicher	3
B	boot	3
	Boot-Konfigurationsdatei	3
F	Flash	3
	Flash EEPROM	3
K	Konfigurationsinformationen	3
N	Name in Flash	4
	New Name in Flash	4
O	Operation	4, 5
R	RAM	3
S	Start Operation	5
	State of last operation	4
T	TFTP File Name	4
	TFTP Server IP Address	4
	TFTP-Server	3
	Type of last operation	4
U	Unix	3
W	Windows	3

Index: Monitoring and Debugging

A	Active Connections	20
	Admin Status	42
	Adminstatus	25
	ADSL	6
	Advertisement Interval Errors	65
	Advertisements Received	65
	Age	45
	Area	44
	ATM Interface	47
	ATM/OAM	6
	Authentication Errors	65
	Authentication Type Mismatch	65
B	Backup Designed Router (BDR)	42
	Become Master	65
	BRRP	6
C	CEA	39
	Charge	12
	Checksum Errors	66
	Class	71
	Compress	28
	Contents	27
	Corrected blocks	57
	CRC anomalies	61
	Current attenuation	56
	Current loop attenuation	61
	Current noise margin	56
	Current output power	56
	Current SNR margin	61
	Current status	56, 60, 61
D	Designed Router (DR)	42
	Dropped Octets	73

	Dropped Packets	73
	Duration	20
E	End to End	51, 54
	Errored seconds (ES)	56, 61
	EXTENDED	20
F	Framing (LOF)	56
I	In	39
	InOctets	72
	InPkts	72
	Interface	41, 43, 67
	Interface Name	19
	Interfaces	6, 41
	Invalid Authentication Type	65
	Invalid Type Packets Received	66
	IP QoS	6
	IP TTL Errors	66
	IPSec	6, 33
	ISDN Credits	5
	ISDN Monitor	5
L	Level	27
	Link State ID	45
	Local	38
	Local ID	37
	Loss of sync word (LOSW) seconds	61
	LPort	38
	LSDB	44
M	max. Mails/min	26
	Maximum Transmit Rate	68
	Messages	6, 28
N	Neighbor	43
	Nominal Transmit Rate	68

	Number of Current Connections	12
	Number of Current Incoming Connections	12
	Number of Current Outgoing Connections	12
	Number of Incoming Connections	11
	Number of Outgoing Connections	12, 13
O	OctetsDropped	72
	Octs	71
	Operation	20
	Operational Status	19, 47, 50, 53, 67
	Originator	26
	OSPF	6
	Out	39
	OutOctets	72
	OutPkts	72
P	Packet Length Errors	66
	Packets In	35
	Peers Blocked	34
	Peers Dormant	34
	Peers Up	34
	Pkts	71
	PktsDropped	72
	Power (LRP)	56
	Pto	38
Q	Queued Octets	73
	Queued Packets	73
R	Received blocks	56, 61
	Received Errors	20, 48
	Received Octets	20, 47, 68
	Received Packets	19, 68
	Receiver	27
	Remote	38
	Remote ID	36
	Remote IP	36

	Retx Queue	43
	Router ID	43, 45
	RPort	39
	RX Rate (Kb/s)	47
S	SAs Phase 1	34
	SAs Phase 2	35
	Segment	51, 54
	Select subsystems	28
	Sequence	45
	Severely errored seconds (SES)	61
	SHDSL	6
	Signal (LOS)	56
	SMTP Server	26
	SSHD	6
	START OPERATION	20
	State	42, 43, 44
T	TARSEH	36, 37
	TCP/IP	6
	Time for Incoming Connections	12
	Time for Outgoing Connections	12
	Time for Outgoing Connections (sec)	13
	Time till end of measure interval (sec)	11, 13
	Timeout	28
	TOS	72
	Transmit Discards	48
	Transmit Errors	20, 48
	Transmit Octets	20, 48, 68, 73
	Transmit Packets	20, 68, 73
	Transmitted blocks	57, 61
	TX Rate (Kb/s)	48
	Tx rate (Kb/s)	56
	Type	44
U	Unavailable seconds (UAS)	61
	Uncorrect blocks	57

V	Vendor ID	55
	Version Errors	65
	Version Number	55
	Virtual channel connection (VCC)	52
	Virtual path connection (VPC)	49
	Virtual Router ID	64
	Virtual Router State	65
X	X.25 Monitor	5
	xDSL Credits	5

